



MONOTECH SAE: 30

V2230-00

MONOTECH oils are mono grade automotive engine oils designed for a wide range of petrol and diesel engines. Primarily recommended for use as a single oil in mixed fleets containing both light and heavy duty, four stroke diesel and petrol engines, both naturally aspirated and turbocharged or where a mono grade oil is recommended. The mid sulphated ash content ensures its use for mixed fleet operators including those with petrol engines with catalytic converters

SUMMARY OF BENEFITS

- Can be used in non-engine applications where oils of its performance level are suitable, such as manual and powershift transmissions and mobile hydraulic systems.
- Also recommended for generator sets and high-speed diesel engines in marine service

SPECIFICATIONS

<ul style="list-style-type: none">• DAIMLER BENZ DB 227.0• API CF-4, CF-2, CF/SG• MIL-L-2104E/2104D• MIL-L-2104F	<ul style="list-style-type: none">• DETROIT DIESEL 7SE-270• MERCEDES BENZ 228.0• JAPAN JAPANESE CD• CATERPILLAR TO -2	<ul style="list-style-type: none">• ALLISON C3• ALLISON C4• MACK EO-K/2• ACEA E 2
---	--	--

TECHNICAL DATA

CHARACTERISTICS	MONOTECH SAE 30
Specific gravity at 15 C	0.878
Kinematic viscosity at 40 C, mm ² /s (cSt)	90
Kinematic viscosity at 100 C, mm ² /s (cSt)	10.5
Viscosity index	100.0

- Safety Data Sheet for this product can be obtained by visiting Vixol Australia Pty Ltd Website www.vixol.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

Vixol Australia Pty Ltd
7 Foden Avenue Campbellfield Vic 3061 Australia
Tel: +61 03 9333 7701 Local sales: 1300 0894684
Email: sales@vixol.com.au www.vixol.com.au