

**BTX / SKYCO Product Specifications
Roller Shade Systems**

Manual Sorina M

1

Part 1 – General

1.01 Summary:

Scope of work is to provide roller shades that are operated by BTX / SKYCO manual lift system along with accessories, attachment hardware, and equipment necessary to complete satisfactory installation.

1.02 Turnkey responsibility for motorized roller shade systems:

- A. To ensure control of responsibility for satisfactory performance and installation of the manual roller shade systems, the design, engineering and installation shall be assigned to a single manufacturer and his authorized dealer/installer.
- B. The base building contractor (main contractor) shall provide and coordinate the following items with the window shade contractor/installer for all window shade systems.
 - 1. Shade pockets recessed into ceiling
 - 2. Necessary Mounting Hardware

1.03 Submittals

- A. Manufacturing literature to describe assembly, materials, installation instructions, and specific data. Include any pertinent wiring diagrams.
- B. Shop drawings are to include, but are not limited to, all components, fasteners, and installation methods.
- C. Window Systems are custom-built based on measurements taken in the field.

1.04 Warranty

- A. Manufacturer shall provide five (5) year warranty from the date of installation on all shade motors. All operating control and electronic accessory components shall carry a one (1) year limited warranty against defects in materials and workmanship.

1.05 Delivery and storage

- A. Systems shall be delivered to the site in original manufacturer's containers.
- B. Containers shall be uniquely labeled to identify the corresponding window openings and locations.
- C. All materials shall be stored in a dry, secure place protected from weather, water and heat, surface contaminants, construction traffic and all other potential damage.

**BTX / SKYCO Product Specifications
Roller Shade Systems**

Manual Sorina M

2

Part 2 – Products

2.01 Manufacturer:

- A. BTX Intelligent Fashion
2517 Manana Dr
Dallas, TX 75220
(800) 422-8839
- B. SKYCO Shading Systems
3411 W Fordham Ave.
Santa Ana, CA 92704
(800) 777-5926

2.02 Components:

- A. Clutch shall be comprised of multi-banded steel springs that create the pressure necessary to keep the shade in the desired position. System to be symmetrical for left or right-hand installation. Clutch permits torque to be transmitted to the shade roller only in one direction. In the other direction the roller is nearly free to rotate so that the weight of the shade material prevents movement in the reverse direction.
- B. Tube shall be 50mm extruded aluminum.
- C. Hook-mount or tab-mount control end bracket shall be zinc-plated steel and allow both the control end to drop into the bracket for ease of installation.
- D. Idler insert shall match the tube shape internally and is provided with a round plastic, spring-loaded shaft for mounting in the bracket. Inserts are made from injection molded plastic.
- E. Adaptors allows the clutch and idler mechanisms to fit the tube and shall be manufactured from injection molded plastic
- F. Double-sided tube tape is used and for fabric attachment.
- G. Bottom Bar shall be extruded aluminum and inserts into pocket in shade fabric to ensure uniform weight distribution and operation.
- H. Fascia Panel and Backplate shall be 4" extruded aluminum to enclose motor and roller and give a finished look to the assembly. Unit configuration may accommodate 5" or 7" fascia panel variations.
- I. Fascia Bracket Set shall be made of stamped steel either 4", 5", or 7" in width and allow for mounting of shade system with fascia panel either inside, outside, or to the ceiling. A self-lubricated bearing will be attached on the idler side bracket.
- J. Side Channels and Sill Channels shall be made of extruded aluminum and prevent light from entering along the edges of the shade for blackout situations.

**BTX / SKYCO Product Specifications
Roller Shade Systems**

Manual Sorina M

3

Pile Inserts fit into side channels to further enhance light blocking and reduce wear on shade fabric.

- K. Shade Pocket and Pocket Enclosure shall be made of extruded aluminum for optional mounting in recessed ceiling pocket.
- L. Fabric shall be specified by designer/decorator/end-user. Please refer to BTX / SKYCO sample cards for specifics on color selection, parameters/guidelines and attributes.

2.03 Controls:

- A. System shall be controlled by a stainless steel pulling chain with metal ball stop to limit the extension of the shade. The system is reversible for either right or left-handed operation. Systems are to be provided with tensioner device installed at the bottom of the chain loop for compliance with industry safety regulations.

Part 3 – Execution

3.01 Inspection and Preparation:

- A. Qualified installer shall be responsible for window measurements prior to installation, installation conditions, and preparation of all mounting surfaces.

3.02 Installation:

- A. System installation shall be in accordance with BTX / SKYCO mounting instructions.

3.03 Maintenance:

- A. Lift system components should not require routine maintenance under normal operating conditions.
- B. For fabric care refer to fabric manufacturer's care and use directions.