Fire Safety Inspection Report / Order to Remedy				
Name of Occupant	Group Division		Occupancy	
Building Address	Town/Community		Inspection Date	
Name of Owner or Authorized Agent	Contact Person for Inspection		Phone No.	
Address of Owner or Authorized Agent	Inspector(s) & Phon	e No.	Reporting No.	

ın	MANITOBA	Inspection Observations	Meets	MB Fire	Code
ID	FIRE CODE ARTICLE		Yes	No	N/A
Α		EXTERIOR			
1	MFC 2.5.1.5.	Fire department access is maintained clear of obstructions.			
2	MFC 6.4.1.1.	Private fire hydrants are serviced / maintained clear of obstructions.(NFPA 25)			
3	MFC 2.5.1.4.	Fire department connections are accessible and free of obstructions.			
4	MFC 2.7.1.6.	Means of egress shall be maintained in good repair and free of obstructions			
5	MFC 3.1.1.4.	Exterior natural gas or propane installations are protected. (CAN/CSA-B149.1)			
6	MFC 2.6.1.6.	Chimneys are visibly maintained and in good repair.			
7	MFC 3.3.5.3	Flammable gases are stored outdoors in an approved manner.			
В		MECHANICAL SERVICE SPACES			
1	MFC 2.6.1.6.	Heating, ventilation and air conditioning systems are operated, tested and maintained in good operating condition.			
2	MFC 2.6.1.6.	Fuel-fired heating system must be inspected annually, by a person acceptable to the Authority Having Jurisdiction (MB Amendment)			
3	MFC 2.6.1.5.	Clearances are maintained between heating equipment and combustible materials and/or construction.			
4	MFC 2.4.1.1.	Combustibles have not accumulated in the service rooms or spaces.			
5	MFC 2.2.2.4.	Doors to service rooms are kept closed.			
6	MFC 2.2.2.4.	Closure devices for service room doors are operational.			
С		EARLY WARNING EQUIPMENT			
1	MFC 2.1.3.1.	An acceptable fire alarm and detection system is installed.			
2	MFC 6.3.1.1.	The fire alarm system is operational.			
3	MFC 6.3.1.2.	Fire alarm system is inspected and tested monthly. Ref (CAN/ULC - S536 Standard for the inspection & testing of fire alarm systems)			
4	MFC 6.3.1.2.	Fire alarm system is inspected and tested annually. Ref (CAN/ULC-S536 Standard for the inspection & testing of fire alarm systems)			
5	MFC 2.1.3.3.	Approved smoke alarms are installed as required.			
6	MFC 6.7.1.1.	Smoke alarms are inspected, tested and maintained in operating condition.			
7	MFC 2.1.3.8.	Installations of carbon monoxide detection and warning equipment must be acceptable to the Authority Having Jurisdiction (MB Amendment)			
8	MFC 6.7.1.1.	Carbon monoxide detectors are inspected, tested and maintained in operating condition.			
D		HOUSE KEEPING			
1	MFC 2.4.1.1.	Combustible materials are not permitted to accumulate in quantities or locations that will constitute an undue fire hazard.			
2	MFC 2.3.1.3.	Decorative materials attached to walls or ceilings have not exceeded the room or area's flame-spread rating.			
3	MFC 2.4.1.3.	Non-combustible waste receptacles are used for materials that are subject to spontaneous ignition.			
4	MFC 2.4.1.4.	Lint traps for laundry equipment are cleaned after each use.			
5	MFC 2.10.3.1.	Combustible materials such as artwork and teaching materials that are attached to walls have not exceeded 20% of the wall area. (Day Care/Schools) In schools – 20% of wall area in classrooms and 5% wall area in hallways			
6	MFC 2.10.3.2.	Waste receptacles are made of non-combustible materials. (Day Care/Schools)			
Е		SMOKING			

1	MFC 2.4.2.1.	Smoking is not permitted in areas where conditions are such that a fire or explosion hazard may be created.		
2	MFC 2.4.2.1.	Where smoking is permitted, adequate ash trays are provided, and smoking materials are properly disposed of.		

F		STORAGE OF HAZARDOUS GOODS	Yes	No	N/A
1	MFC 2.4.4.1.	Flammable and combustible liquids are labelled, stored and handled in an approved manner in conformance with MFC Part 4.			
2	MFC 2.4.4.1.	Storage cabinets are properly identified (MFC 4.2.10.4.)			
3	MFC 3.2.8.2.	Flammable gases are stored indoors in an approved manner.			
G		FIRE SUPPRESSION EQUIPMENT			
	MFC 2.1.5.1.	Portable fire extinguishers are installed as required.			
1	WFC 2.1.5.1.	Ref. (N.F.P.A. 10 Standard for Portable Fire Extinguishers)			
2	MFC 6.2.1.1.	Portable fire extinguishers are inspected, tested and maintained in operating condition. Ref. (N.F.P.A. 10 Standard for portable fire extinguishers)			
3	MFC 6.4.1.1.	Sprinkler systems and/or Standpipe systems are inspected, tested and maintained in operating condition. Ref. (N.F.P.A. 25 Standard for testing and maintenance. of water-based fire protect systems)			
4	MFC 2.6.1.9.	Fixed fire suppression and ventilation systems for cooking equipment are installed, inspected and maintained in operating condition. Ref: (N.F.P.A. 96 Standard for ventilation control and fire protection of commercial cooking operations).			
Н		FIRE SEPARATIONS			
1	MFC 2.2.1.2.	Integrity of the fire separations is maintained.			
2	MFC 2.2.2.1.	Required openings in fire separations are protected with closures in accordance with MBC			
3	MFC 2.2.2.4.	Fusible links and other heat-actuated devices are undamaged and free of paint or dirt			
4	MFC 2.2.2.4.	Closures in fire separations are not blocked or wedged open.			
5	MFC 2.2.2.4.	Closures in fire separations are maintained in good working order at all times.			
6	MFC 2.2.2.4.	Fire dampers/ Fire Stop flaps inspected annually for damage / obstruction			
7	MFC 2.2.2.4	Fire dampers/ Fire Stop flaps tested 1yr after install then every 4 or 6years Ref. (N.F.P.A. 80 Standard for Fire Doors and Other Opening Protectives)			
I		OCCUPANT SAFETY			
1	MFC 2.7.1.1.	Adequate means of egress is provided. (ref. MBC 3.3.1.3)			
2	MFC 2.7.1.6.	Means of egress are maintained in good repair and free of obstructions.			
3	MFC 2.7.1.1.	Required exit doors are equipped with quick release exit hardware.			
4	MFC 2.7.1.1.	Required exit doors open in the direction of travel. (ref. MBC 3.4.6.11)			
5	MFC 2.7.2.1.	Exit doors are maintained and operate freely.			
6	MFC 2.8.3.2.	Fire drills are conducted as required. (MB Amendment - Schools)			
7	MFC 2.8.2.14	Emergency evacuation plans are posted and maintained.			
J		ELECTRICAL			
1	MFC 2.4.7.1.	Extension cords are being used in a proper manner. (Temporary Use Only)			
2	MFC 2.4.7.1.	Electrical equipment and wiring are maintained in good condition.			
3	MFC 2.4.7.1.	There are no visible bare or exposed wires.	\boxtimes		
4	MFC 2.4.7.1.	There is no visible overloading of electrical circuits.			
5	MFC 2.4.7.1.	Switches or receptacles are in good condition.			
6	MFC 2.4.7.1.	Distribution panels are accessible, covered and labelled. (1m clear distance)			
K		EMERGENCY LIGHTING. STANDBY POWER AND EXIT SIGNS			
1	MFC 2.7.3.1.	There is adequate exit lighting; exit signs and emergency lighting provided. (ref. MBC 3.4.5.1; MBC 3.2.7)			
2	MFC 2.7.3.1.	Exit lighting and exit signs are continuously illuminated. (MBC 3.4.5.1)			
3	MFC 2.7.3.1.	Exit signs are readily visible.			
4	MFC 2.7.3.1.	Emergency lighting equipment is maintained in operating condition.			
5	MFC 6.5.1.1.	Emergency lighting is inspected and tested monthly / annually as required.			
6	MFC 6.5.1.1.	Emergency Stand-by Power Unit maintained and in operating condition			
L		RECORDS MANAGEMENT Record Logs are to be maintained for the following:			
1	MFC 2.2.1.2. Division C	Portable fire extinguisher; inspection, testing and maintenance			
2	MFC 2.2.1.2. Division C	Sprinkler system; inspection, testing and maintenance			
3	MFC 2.2.1.2. Division C	Standpipe system; inspection, testing and maintenance			
4	MFC 2.2.1.2. Division C	Fixed fire suppression system; inspection, testing and maintenance			

5	MFC 2.2.1.2. Division C	Emergency lighting and exit sign lighting; inspection, testing maintenance		
6	MFC 2.2.1.2. Division C	Fire alarm and detection system; inspection, testing and maintenance		
7	MFC 2.2.1.2. Division C.	Smoke Alarms; inspection, testing and maintenance		
8	MFC 2.2.1.2. Division C	Emergency power system; inspection, testing and maintenance		
9	MFC 2.8.2.1.	Fire safety plans are current and reviewed annually		
10	MFC 2.2.1.2. Division C.	Fire drill record logs are maintained		
11	MFC 2.2.1.2. Division C.	Carbon Monoxide detector logs maintained		
12	MFC 2.2.1.2. Division C.	Fire/Smoke Dampers: Inspection, testing and maintenance		

The following deficiencies have been identified and require the following corrective action(s), to be completed by the noted compliance date.

ID	MFC Article No.	Deficiency	Corrective Action	Compliance Date

Additional information as required may be made on additional pages and shall become part of this inspection report.

Administrative Penalty:

The required corrective action(s) listed above are to be completed by the noted compliance date, or you may be subject to an Administrative Penalty, as provided for under section 15.1(1) of *The Fires Prevention and Emergency Response Act*

Request for Review of Order:

In accordance with Section 15 of The Fires Prevention and Emergency Response Act (C.C.S.M.c. F80), you have the right to request, in writing, a review of this order by the Manitoba Fire Commissioner within 14 days of issue, or the period specified for compliance if it is less than 14 days. Should you choose to waive that right; the order will be considered final. Your request must include:

- a) a copy of the order
- b) your name and contact information, and
- c) the reason(s) for the request.

Please submit your request to: Fire Commissioner

Office of the Fire Commissioner

600-401 York Ave. Winnipeg, MB R3C 0P8

Date	
Inspector(s) Name	
Inspector(s) Signature	
Authority Having Jurisdiction	
Address	Phone No.
Report provided to:	

The report is solely based on conditions existing on The	ne Owner or their Authorized Agent shall be solely			
responsible for carrying out the provisions of the Manitoba Fire Code.				