

Размеры (мм)			Грузоподъемность		Рабочая скорость	Тип подшипника
			Динамическая	Статическая	Смазка	
			cr	cor	min1	
d	D	B	кН	кН		
19	35	10	6	3.3	12000	6003/19
20	47	14	12.8	6.7	15000	692204TN
20	47	45.18	12.8	6.7	10000	204 WR Z22 SFA
20	52	21	16	7.9	8000	62304-2RSR
20	60	31.6	16	7.9	8000	690204C3S3
20	80	15	16	7.9	8000	500504-2RSRTNC3
24.2	47	19.8	10.1	5.9	8000	696205-2RSRTN
25	52	12	14	7.9	8000	420205
25	52	18	47	7.9	8000	62205-2RSR
25	62	24	20.6	11.2	7000	62305-2RSR
25	67	19	20.6	11.2	9000	691305TN
25.4	52	15	14	7.9	12000	6205/254UGC3
26	47	19.6	10.1	5.9	8000	696405-2RSEACRT NC3L21
27	47	8	9.1	5.55	15000	6005 S0F2
30	55	13	13.2	8.2	7000	6006A-2RSRTN
30	55	18.9	13.2	8.2	7000	696906-2ZRC3
30	62	16	19.5	11.4	7500	96108006
30	62.1	24.5	13.2	8.2	7000	697106
30	65	21	25	14	6000	630374-2RSTNC4
30	65	21	25	14	6000	697006-2RSTNC4
30	72	19	26.5	15	6000	96108005
30	72	28	28.3	16	7000	10/330 PZ
30	75	19	30.7	19.6	9000	697706MPA
30	75	19	32.9	17.6	9000	698806MBC3
33	66	17	17.8	11.2	9000	65907
35	72	17	25.7	15.6	7000	6207RSDNBTNEL
35	72	25	25.7	15.6	7000	88507
60	110	25	52.4	36.3	4000	6212-2RSR/B25
63.5	100.3	21.8	25.4	22.3	5500	691013
70	148	45	48.4	39.7	3600	690916M
210	290	23.5	54.9	73.7	1800	690342