



*Product Data Sheet*

---

## FOXATAR (OX-506)

Coaltar Epoxy

### PRODUCT DESCRIPTION

High build polyamide cured coaltar epoxy coating.

### RECOMMENDED USE

Can be used in a wide variety of immersion conditions, typically splash zone areas of offshore platforms and drilling rigs, pilling and bridges and tank lining. or factory and site application, and as an industrial maintenance coating

### CHARACTERISTICS

- 
- For tank lining, intermittent or continuous immersion service in crude oil, salt solution, fresh water and seawater
  -

at  
er  
.  
For  
ma  
rin  
e  
str  
uct  
ure  
s,  
pili  
ng,  
hull  
s  
an  
d  
shi  
p  
bot  
to  
ms  
.  
Go  
od  
res  
ista  
nc  
e  
ag  
ain  
st  
ch  
em  
ical  
ly  
poll  
ute  
d  
wat  
er.  
(  
c  
c  
c  
c  
e  
k  
r  
e  
s  
i  
c  
r  
r  
e  
s  
i  
s  
t  
e  
r  
c  
e

.

.

PHYSICAL DATA

Colour

---

**Gloss Level**

**Volume Solid**

**Dry Film Thickness**  
**Number of Coat**

**Theoretical Coverage**

**Temperature Resistance**

VOC

:  
2  
7  
(

Flash Point

(

:  
2  
7  
(  
(

Shelf Life  
Pack Size

2  
C  
h  
e  
s  
t  
r  
i  
t

**SURFACE PREPARATION**

Dry abrasive blast in accordance with ISO – Sa 2.5 or SSPC – SP 10 “Near White”. Blast to achieve a 50 – 100 microns anchor profile as indicated by a Keane Tator Surface Profile Comparator.  
Remove abrasive residue or dust from surface.

APPLICATION DATA

Application Methods

A  
i  
r  
l  
e  
s  
s  
e  
s  
p  
r  
e  
y

C  
c  
r  
v  
e  
r  
t  
i  
c  
r  
e  
l

S  
F  
r  
e  
y

E  
r  
u  
s  
r  
c  
r  
f  
c  
l  
e  
r

Mixing Ratio By Volume

**Thinner**

**Surface Temperature**

**Drying Time**

1  
C  
C  
C  
r  
E  
r  
y  
C  
v  
e  
r  
C  
C  
a  
t  
i  
r  
C  
I  
r  
t  
e  
r  
v  
a  
I



F  
u  
l  
l  
C  
u  
r  
e

Pot Life



**SAFETY PRECAUTION**

*Keep away from heat, spark and Open flames. Avoid breathing of vapour on skin and eye contact. Keep container closed and store in cool, ventilated area when not in use. Proper ventilation and protective measures must be provided during mixing, application and drying, to keep vapour concentration within safe limits and to protect against toxic hazard.*

*Necessary safety equipment must be used and ventilation requirements carefully observed, especially in confined or enclosed spaces, such as tank interior and building.*

---

**DISCLAIMER**

*The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.*

**ISSUED: January 2009**