

XML API INTERFACE

AUTHOR

Steve Harris

UPDATED

2024-07-15

Introduction

The MyAffiliates platform has been designed with an Applications Programming Interface (API) allowing developers and clients to interact with the system in an scripted or automated fashion. The API has a number of functions which take input parameters and return results in XML

This API can be called using both GET and POST methods.

Security

Accessing the engine API should only ever be done using server-side code. The API should never be accessed via JavaScript or other methods that are open to inspection by third parties.

Authentication

Authentication with the XML API is done by authenticating with an admin account username and password in a basic HTTP/1.0 authentication request. The admin account being used must have an access level that has been given permission to the feeds module. This admin account can be restricted to this module only if required.

Feed 1: User Feed

This feeds returns a list of affiliates as filtered by the input parameters

Parameters	Description	Type	Possible values
USERNAME	[optional] Match a specific username	string	
USER_ID	[optional] Match a specific user_id	integer	
USER_HASH_ID	[optional] Match a specific user hash_id	string	
JOIN_DATE	[optional] Match a specific join date	date	
JOIN_DATE_TO	[optional] Match a specific join date range	date	
STATUS	[optional] Match a specific status	String	new,accepted,denied,suspended,verified
VARIABLE_NAME & VARIABLE_VALUE	[optional] Return affiliates matching a specific user variable name. Must be combined with VARIABLE_VALUE or this parameter is ignored.	String	Match a specific user_variable name with the name VARIABLE_NAME partially or exactly containing value VARIABLE_VALUE. Because internally a 'LIKE' is done in the query for VARIABLE_VALUE, % can be used as a wildcard character int his field only.
INCLUDE	[optional] Specify a CSV of block elements to include in the response. If the parameter is not supplied, all blocks are included. If the parameter is supplied without a value, all blocks are excluded.	CSV	• COMMENTS • TAGS • CAMPAIGNS • VARIABLES • DETAILS • SUBSCRIPTIONS • SUBSCRIPTION_VARIABLES • PAYMENT_DETAILS

Example Usage - This would return all affiliates who have a status of 'new'

https://admin.example.com/feeds.php?FEED_ID=1&STATUS=new

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Example Output

```
<USERS>
  <USER ID="6">
    <USERNAME>eeeeeeee</USERNAME>
    <PARENT_ID>12</PARENT_ID>
    <PARENT_USERNAME>testuser2</PARENT_USERNAME>
    <ADMIN_ID>0</ADMIN_ID>
    <ADMIN_USERNAME/>
    <EMAIL>test@domain.com</EMAIL>
    <COUNTRY/>
    <STATUS>accepted</STATUS>
    <JOIN_DATE>2007-02-19 01:00:23</JOIN_DATE>
    <CURRENCY>USD</CURRENCY>
    <BALANCE>120.03</BALANCE>
    <PAYMENT_TYPE>0</PAYMENT_TYPE>
    <MINIMUM_PAYMENT>0.00</MINIMUM_PAYMENT>
    <LANGUAGE ID="0">English</LANGUAGE>
    <USER_COMMENTS>
      <COMMENT DATE="2007-02-01" COMMENT="Internal Tracking Account , do not pay."/>
    </USER_COMMENTS>
    <USER_TAGS/>
    <USER_CAMPAIGNS>
      <CAMPAIGN CAMPAIGN_ID="7" DESCRIPTION="poker.co.nz"/>
      <CAMPAIGN CAMPAIGN_ID="101" DESCRIPTION="myspace"/>
    </USER_CAMPAIGNS>
    <USER_VARIABLES>
      <VARIABLE NAME="1_2" VALUE="5"/>
      <VARIABLE NAME="USERVARIABLE_ABN" VALUE=""/>
      <VARIABLE NAME="affiliate_id" VALUE="6"/>
      <VARIABLE NAME="uservar_1033" VALUE="2008-11-13"/>
    </USER_VARIABLES>
    <USER_DETAILS/>
    <SUBSCRIPTIONS>
      <SUBSCRIPTION PLAN_NAME="Revshare" DESCRIPTION="" BILLING_DISPLAY=""
        PLAN_ID="1" CUSTOMER_GROUP="0" DISCARD_NEGATIVE_EARNINGS="0"
        START_DATE="2007-11-01"/>
      <SUBSCRIPTION PLAN_NAME="Revshare" DESCRIPTION="" BILLING_DISPLAY=""
        PLAN_ID="1" CUSTOMER_GROUP="1" DISCARD_NEGATIVE_EARNINGS="0"
        START_DATE="2007-10-01"/>
      <SUBSCRIPTION PLAN_NAME="Revshare" DESCRIPTION="" BILLING_DISPLAY=""
        PLAN_ID="1" CUSTOMER_GROUP="2" DISCARD_NEGATIVE_EARNINGS="0"
        START_DATE="2005-12-01"/>
    </SUBSCRIPTIONS>
    <SUBSCRIPTION_VARIABLES>
      <SUBSCRIPTION_VARIABLE NAME="plantest" PLAN_ID="1033" CUSTOMER_GROUP="0"
        DATE="0000-00-00" VALUE="123"/>
    </SUBSCRIPTION_VARIABLES>
    <USER_PAYMENT_DETAILS>
      <PAYMENT_TYPE_1 NAME="NETELLER" ID="1"/>
      <PAYMENT_TYPE_2 NAME="CHECK" ID="2"/>
      <PAYMENT_TYPE_3 NAME="WIRE_TRANSFER" ID="3"/>
      <PAYMENT_TYPE_4 NAME="PLAYER_ACCOUNT" ID="4"/>
      <PAYMENT_TYPE_5 NAME="EPASSPORTE" ID="5"/>
    </USER_PAYMENT_DETAILS>
  </USER>
</USERS>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 2: User Details Feed

This feed allows the getting and setting of a specific user detail field for all users specified. It also facilitates the ability to pull a specific user_detail field for a specific user.

Parameters	Description	Type	Possible values
USER_IDS	[Match one or more user_id's (comma separated if more than one). When specifying more than one user ID you MUST specify both fields below. All users in this parameter will then have the detail set as per the settings below	integer	
DETAIL_NAME	Name of the user detail field you wish to fetch or update.	string	
DETAIL_VALUE	Value that you wish to set the user detail field specified above too for all users in the USER_ID parameter.	String	

Example Usage - This would show the user details called firstname for affiliate id 1

http://admin.example.com/feeds.php?FEED_ID=2&USER_IDS=1&DETAIL_NAME=firstname

Example Output

```
<USERS>
  <USER>
    <USER_ID>1</USER_ID>
    <FIRSTNAME>Calum</FIRSTNAME>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

```
</USER>
</USERS>
```

Example Usage - This would set the firstname for affiliate id 1,2,3 and 4 to testing

http://admin.example.com/feeds.php?FEED_ID=2&USER_IDS=1,2,3,4&DETAIL_NAME=firstna me&DETAIL_VALUE=testing

Feed 3: User Status Feed

This feed outputs the status of a selected list of users. It can also optionally update the status of those users.

Parameters	Description	Type	Possible values
USER_IDS	Match one or more user_id's (comma separated if more than one).	integer	
SETSTATUS	[optional] The status to set the user(s) to	string	New, accepted, denied, suspended, verified.

Example Usage - This would return the user status of the affiliates with an id of 1,2,3

http://admin.example.com/feeds.php?FEED_ID=3&USER_IDS=1,2,3

Example Output

```
<USERS>
  <USER ID="13">
    <STATUS>accepted</STATUS>
  </USER>
</USERS>
```

Example Usage - This would set the status of affiliates with ids of 1,2,3 to accepted

http://admin.example.com/feeds.php?FEED_ID=3&USER_IDS=1,2,3,4&SETSTATUS=accepted

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 4: Decode Token

This feed allows you to specify a number of tokens and decode them and output the details pertaining to the details within the token(s).

Parameters	Description	Type	Possible values
TOKENS	A comma-separated list of tokens to decode	String	

Example Usage - This would return the decoding of a token

http://admin.example.com/feeds.php?FEED_ID=4&TOKENS=iPf0f63L7Qdhg6W02I1rgWNd7ZgqdRLk

Example Output

```
<TOKENS>
  <TOKEN PREFIX="iPf0f63L7Qdhg6W02I1rgWNd7ZgqdRLk" USER_ID="7" SETUP_ID="3" MEDIA_ID="0"
  BANNER_ID="1" CAMPAIGN_ID="1" AUTHCODE="0" REFERRING_URL="http://www.google.com"
  IP_ADDRESS="127.0.0.1" COUNTRY="ES" TIME_STAMP="2010-12-14T09:36:26+10:00">
    <USER USERNAME="testuser" STATUS="new"/>
    <SETUP SITE_ID="1" SITE_NAME="Test Site" SITE_URL="http://www.yoursite.com"
    OPERATION_ID="1" PLAN_ID="3" OBJECT_ID="3" OBJECT_DESCRIPTION="Home Page, with shorter
    query strings.">
      <OBJECT_DATA>
        <DATA VALUE="http://www.yoursite.com?s=%USER_VAR:subordinate%&t=%PREFIX%"/>
      </OBJECT_DATA>
    </SETUP>
  </TOKEN>
</TOKENS>
```

Feed 5: Encode Token

This feed allows you to generate a list of URLs and tokens for a specific user and links

Parameters	Description	Type	Possible values
USER_ID	The affiliate id to encode in the token	integer	
SETUP_ID	The setup_id (link_id) to use in this token	integer	
MEDIA_ID	[optional] Media id	integer	defaults to 0 if not specified
BANNER_ID	[optional] banner_id (the campaign id)	integer	defaults to 1 if not specified
AUTHCODE	[optional] Authcode	integer	defaults to 0 if not specified
VERSION	[optional] Version of the API to use	integer	defaults to a value of 338

Example Usage (Version 338) - This would generate a token with the parameters supplied:

http://admin.example.com/feeds.php?FEED_ID=5&USER_ID=1&SETUP_ID=7

Example Output (Version 338)

```
<TOKENS USER_ID="2" SETUP_ID="7" AUTHCODE="0" BANNER_ID="1" MEDIA_ID="1">
  <TOKEN>PQ4YXsO2q5nKto_EPcZApMni_MQzyHn0</TOKEN>
  <LINK_CODE>
    http://record.yoursite.com/_PQ4YXsO2q5nKto_EPcZApMni_MQzyHn0/1/
  </LINK_CODE>
</TOKENS>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 6: User Transactions Feed

This feed returns one or more user transactions. Each transaction is listed as a separate node. This API can also be used to update selected details within the selected transactions.

Parameters	Description	Type	Possible values
FROM_DATE	Show transactions from selected date onwards	date	
TO_DATE	[optional] Show transactions to selected date (Default of today)	date	
USER_ID	[optional] Match a specific user_id	integer	
TRANSACTION_TYPE	[optional] Match a specific transaction type. See mapping below	integer	1,2,3,4,5,6,7,8,9
or			
TRANSACTION_ID	[optional] Target a specific transaction ID or Transaction ID's NOTE: If specified, overrides all other	Integer or CSV	1131, 1132
To update a transaction or a set of transactions, specify the transactions to be updated using the TRANSACTION_ID parameter above as well as the fields below, adding &ACTION=update The FIELD_VALUE will be applied to all transactions specified in the TRANSACTION_ID field. (eg: FEED_ID=6&TRANSACTION_ID=XXXXXXX&UPDATE_FIELD=visible&FIELD_VALUE=yes&ACTION=update)			
UPDATE_FIELD	[optional] specify a field to update for all specified transactions	String	Options are: • “reference” • “visible” • “reason” • “state”
FIELD_VALUE	[optional] specify a value to set for all specified transactions Visibility affects the affiliates ability to see a	integer	“visible” values can be: • “yes” • “no” • “void” For “reference”, a string.

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

	transaction and for it to affect their wallet balance. Voiding a transaction is like deleting it (without actually deleting it). Reference is some identifier, transaction ID or some other piece of information relating to the transaction. Reason is some identifier, transaction ID or some other piece of information relating to the transaction.		For "reason", a string. For "state" value can be • 1 • 2 • 3 • 4 • 5 • 6 See the Transaction State mapping table below which illustrates the association for transaction "state" values
--	--	--	---

Example Usage - This returns all transactions for the user with an ID of 12 where transactions are dated between the 2011-12-31 and 2012-01-31

http://admin.example.com/feeds.php?FEED_ID=6&FROM_DATE=2011-12-31&TO_DATE=2012-01-31&USER_ID=12

Example Output (As of 3.3.9)

```
<TRANSACTIONS>
  <TRANSACTION TRANSACTION_ID="24590">
    <USER_ID>12</USER_ID>
    <EMAIL>test@myaffiliates.com</EMAIL>
    <USER_PAYMENT_TYPE PAYMENT_TYPE_ID="2" PAYMENT_TYPE="Check">
      <PAYMENT_DETAILS>
        <DETAIL_NAME="Pay to details" DETAIL_VALUE="Check details"/>
        <DETAIL_NAME="Pay to details" DETAIL_VALUE="Check details"/>
      </PAYMENT_DETAILS>
    </USER_PAYMENT_TYPE>
    <OCCURRED>2012-12-31 00:00:00</OCCURRED>
    <TRANSACTION_TYPE>1</TRANSACTION_TYPE>
    <REFERENCE>1</REFERENCE>
    <REASON/>
    <AMOUNT>2.92</AMOUNT>

    <CONVERTED_AMOUNT>-3188.42</CONVERTED_AMOUNT>
    <CONVERTED_CURRENCY>AUD</CONVERTED_CURRENCY>
    <VISIBLE>yes</VISIBLE>
    <PLAYER_GROUP_ID>0</PLAYER_GROUP_ID>
    <STATE>1</STATE>
    <VISIBLE>yes</VISIBLE>
  </TRANSACTION>
</TRANSACTIONS>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Transaction IDs mapping below:

Transaction type	Description
1	Commission earned
2	Payment issued
3	Payment offset
4	Administrative adjustment
5	Internal - DO NOT USE
6	P2P Payment Out
7	P2P Payment In
8	Internal - Do not use
9	Trailing commission
11	Manual payment issued

Transaction State mapping below:

Transaction state	Description
1	Pending
2	Approved
3	Paid
4	Denied
5	Dead
6	Rejected

Feed 7: Email Match-Up Tool

This feed will output a list of users for each specified media and setup. The output includes javascript and html code for any of the media specified as well as email address, username and user_id. This feed can take a while to execute depending on the number of affiliates.

Parameters	Description	Type	Possible values
MEDIA_IDS	A CSV of media ID's to generate marketing code for	Integer	
SETUP_IDS	A CSV of setup (link) ID's to generate marketing code for	integer	

Example Usage - This would generate marketing code for media 133, setup 8

http://admin.example.com/feeds.php?FEED_ID=7&MEDIA_IDS=133&SETUP_IDS=8

Example Output

```
<USERS>
  <USER USER_ID="1" SETUP_ID="2" MEDIA_ID="1">
    <USER_ID>1</USER_ID>
    <MEDIA_ID>1</MEDIA_ID>
    <SETUP_ID>2</SETUP_ID>
    <USERNAME>user1</USERNAME>
    <STATUS>accepted</STATUS>
    <EMAIL>user1@example.com</EMAIL>
    <PLAN_ID>1</PLAN_ID>
    <TOKEN>ieQz0IK_kMIWqcfzuvZcQMni_MQzyHn0</TOKEN>
    <JAVASCRIPT_CODE><script type="text/javascript"
src="http://js.demo.myaffiliates.com/?prefix=ieQz0IK_kMIWqcfzuvZcQMni_MQzyHn0&media=1&campai
gn=1"></script></JAVASCRIPT_CODE>
    <HTML_CODE />
  </USER>
</USERS>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 8: Create Player

This feed facilitates the creation of a new player entity in the system.

Parameters	Description	Type	Possible values
CLIENT_REFERENCE	The clients unique reference for the player/customer	Alphanumeric	
CLIENT_GROUP	The customer group this player should belong to	Alphanumeric	
JOIN_DATE	The date this player record is created on	date	
DISPLAY_NAME	The visual display name for this player displayed to the affiliate	alphanumeric	Please insert same value as for CLIENT_REFERENCE
TOKEN	The token to create this player with	alphanumeric	
COUNTRY	The ISO 2-character country code the customer belongs to	STRING (eg. GB, US, AU, SE)	

Example Usage - This would generate a player with the following parameters

http://www.yoursite.com.com/feeds.php?FEED_ID=8&CLIENT_REFERENCE=12345&CLIENT_GROUP=casino&JOIN_DATE=2012-06-01&TOKEN=ieQz0IK_kMLUOsJNOfgKeWNd7ZgqdRLk&DISPLAY_NAME=holdfold23&COUNTRY=GB

Example Output

```
<PLAYER>
  <ZBAN_PLAYER_ID>3015835</ZBAN_PLAYER_ID>
</PLAYER>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 10: Customer Feed

This feed returns customer (player) records based on a number of search criteria.

Parameters	Description	Type	Possible values
PLAYER_ID	[optional] The MyAffiliates unique customer id	integer	
FROM_DATE	[optional] Shows customers who joined on or after this date	date	Where date range is expected, TO_DATE is also to be supplied
TO_DATE	[optional] Shows customers who joined on or before this date	date	
AFFILIATE_ID	[optional] Customer must belong to a specific affiliate id	integer	
AFFILIATE_NAME	[optional] Customer must belong to a specific affiliate username	alphanumeric	
DISPLAY_INFO	[optional] Search by the public display information field for a customer	alphanumeric	
CLIENT_ID	[optional] Search by the clients unique id for this customer	alphanumeric	
SOURCE_GROUP	[optional] Customer must belong to this group	alphanumeric	
CUSTOMER_SUSPENDED	[optional] Toggles between showing suspended customers (value = 1) or active customers (value = 0). Defaults to 0	integer	1,0

Example Usage - This would return players that joined on June 1, 2012:

http://admin.example.com/feeds.php?FEED_ID=10&FROM_DATE=2012-06-01&TO_DATE=2012-06-01&SOURCE_GROUP=casino

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Example Output

```
<PLAYERS>
  <PLAYER ZBAN_PLAYER_ID="123456" CLIENT_ID="5_2623139" AFFILIATE_ID="1"
  AFFILIATE_USERNAME="myaffiliates" JOIN_DATE="2012-06-01" DISPLAY_INFO="johnny14" SOURCE_GROUP="casino"
  STATUS="Active" CAMPAIGN_ID="1" PLAN_ID="2" PLAN_NAME="Revshare" OBJECT_ID="999"
  OBJECT_DESCRIPTION="Home Page" MEDIA_ID="0" MEDIA_DESCRIPTION="" PAYLOAD=""
  REFERRER="http://www.examplerreferrer.com/" />
</PLAYERS>
```

Feed 13: Create Campaign

This feed allows campaigns to be created for an affiliate.

Parameters	Description	Type	Possible values
CAMPAIGN_ID	The unique affiliate campaign id	integer	
USER_ID	The affiliate ID to create the campaign for	integer	
DESCRIPTION	The description of the campaign	alphanumeric	

Example Usage - This creates campaign 10 called “My Test Campaign”

http://admin.example.com/feeds.php?FEED_ID=13&CAMPAIGN_ID=1&USER_ID=1&DESCRIPTION=My%20Test%20Campaign

Example Output

```
<CAMPAIGNS>
  <ITEM TACKING_ID="2001" USER_ID="1" DESCRIPTION="My Test Campaign" />
</CAMPAIGNS>
```

Feed 14: Create Landing Page

This feed allows landing pages to be created

Parameters	Description	Type	Possible values
OBJECT_ID	The unique object_id of this new landing page	integer	
OBJECT_DATA	The value of the landing page object. Usually a URL	alphanumeric	
DESCRIPTION	Description of this landing page	alphanumeric	
PLANS	CSV of plan IDs	integer	
TRACKING_URL_ID	ID of tracking URLs	integer	
CLICK_OPERATION_ID	Valid Operation ID	integer	
IMPRESSION_OPERATION_ID	Valid Operation ID	integer	
TAG_SET	A CSV of tag ID's to give to this landing page	integer, csv	
ACTIVE	Should this landing page be active 'active' or not 'deleted'	alphanumeric	active,deleted

Example Usage - This creates a new landing page

http://admin.example.com/feeds.php?FEED_ID=14&OBJECT_ID=86&DESCRIPTION=InsertOverXML&OBJECT_DATA=http://www.google.com&&PLANS=1,2&TRACKING_URL_ID=1&CLICK_OPERATION_ID=1&IMPRESSION_OPERATION_ID=2&ACTIVE=active

Example Output

```
<OBJECTS>
  <ITEM ID="15550"/>
</OBJECTS>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 15: Offline Codes

This feed returns a player token based on an offline code. The token for a code will be generated when the CODE parameter is supplied. Otherwise all codes will be listed without the token. Tokens that are marked as inactive or end dates have passed will still be returned. It's up to the client to determine if those codes should be honored or not.

Parameters	Description	Type	Possible values
BRAND_ID	The unique brand ID the bonus code belongs to	integer	
CODE	[optional] The offline code	alphanumeric	
FULL_DETAILS	[optional] Show all available details for the codes	boolean	0 or 1

Example Usage - This returns all offline code with full details but without the generated token.

http://admin.example.com/feeds.php?FEED_ID=15&BRAND_ID=1&FULL_DETAILS=1

Example Output

```
<OFFLINE_CODES>
  <CODE NAME="FREE100">
    <BRAND NAME="MyBrand">1</BRAND>
    <USER USERNAME="testuser">631</USER>
    <ACTIVE>active</ACTIVE>
    <START_END>2012-06-30</START_END>
    <END_DATE>2012-07-01</END_DATE>
    <CREATED>2012-06-28 17:13:01</CREATED>
    <MODIFIED>2012-06-28 17:16:07</MODIFIED>
  </CODE>
  <CODE NAME="FREE200">
    <BRAND NAME="MyBrand">1</BRAND>
    <USER USERNAME="testuser">631</USER>
    <ACTIVE>inactive</ACTIVE>
    <START_END>0000-00-00</START_END>
    <END_DATE>0000-00-00</END_DATE>
    <CREATED>2012-06-28 17:13:01</CREATED>
    <MODIFIED>2012-06-28 17:16:07</MODIFIED>
  </CODE>
</OFFLINE_CODES>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Example Usage - This returns the token for a particular offline code with minimal details.

http://admin.example.com/feeds.php?FEED_ID=15&BRAND_ID=1&CODE=FREE100

Example Output

```
<OFFLINE_CODES>
  <CODE NAME="FREE100">
    <TOKEN>1JydKj68UUXmd8i72uhfoGNd7ZgqdRLk</TOKEN>
    <BRAND>1</BRAND>
    <ACTIVE>active</ACTIVE>
    <START_END>2012-06-30</START_END>
    <END_DATE>2012-07-01</END_DATE>
  </CODE>
</OFFLINE_CODES>
```

Feed 16: Media Feed

This feed will grant the ability to create and update media

Parameters	Description	Type	Possible values
ACTION	[required] Match a specific action	string	new, update (values are case sensitive)
XML	[required] Matches XML requirements	integer	For examples, see below

Example Usage - This will create a new media

http://admin.example.com/feeds.php?FEED_ID=16&ACTION=new&XML=<med..

Example XML Input - Create New Media

```
<media>
  <medium>
    <mediaType>11</mediaType>
    <creative>ad_123456</creative>
    <creativeSSL>ad_123456</creativeSSL>
    <title>This is a new media</title>
    <defaultLandingPage>
      >51</defaultLandingPage> <!-- optional -->
    <preview>http://www.example.com/preview.jpg</preview> <!-- not required -->
    <metadata name="width">120</metadata>
    <metadata name="height">600</metadata>
    <tag id="12" />
    <tag id="23" />
    <tag id="52" />
    <active enabled="true" />
    <externalId>123456</externalId>
    <expiry>2012-06-01</expiry>
  </medium>
</media>
```

Example XML Input - Update Media

```
<media>
  <medium>
    +!-- required -->
    <mediaId>17543</mediaId>
    <mediaType>11</mediaType>
    <creative>ad_123456</creative>
    <creativeSSL>ad_123456</creativeSSL>
    <title>This is a new media</title>
    <defaultLandingPage>44</defaultLandingPage> <!-- optional -->
    <metadata name="width">120</metadata>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

```
<metadata name="height">600</metadata>
<tag id="12" />
<tag id="23" />
<tag id="52" />
<active enabled="true" />
<externalId>123456</externalId>
<expiry>2012-06-01</expiry>
</medium>
</media>
```

Example Output - Create New Media

```
<media>
  <medium action="new" success="true">
    <media_id>674</media_id>
    <mediaType>11</mediaType>
    <title>This is a new media</title>
    <creative>ad_123456</creative>
    <creativeSSL>ad_123456</creativeSSL>
    <metadata>width=120 \n height=600 \n</metadata>
    <preview>http://www.example.com/preview.jpg</preview>
    <media_variables media_id="674" variable_name="externalId" variable_value="123456"/>
    <media_variables media_id="674" variable_name="expiry" variable_value="2012-06-01"/>
    <landing_page_id>51</landing_page_id>
    <tags media_id="674">12</tags>
    <tags media_id="674">23</tags>
    <tags media_id="674">52</tags>
  </medium>
</media>
```

Example Output - Update Media

```
<media>
  <medium action="update" success="true">
    <media_id>674</media_id>
    <mediaType>11</mediaType>
    <title>This is a new media</title>
    <creative>ad_123456</creative>
    <creativeSSL>ad_123456</creativeSSL>
    <metadata>width=120 \n height=600 \n</metadata>
    <active>active</active>
    <metadata>11</metadata>
    <metadata>11</metadata>
    <media_variables media_id="672" variable_name="external_id" variable_value="123456"/>
    <media_variables media_id="672" variable_name="end_date" variable_value="2012-06-01"/>
    <landing_page_id>44</landing_page_id>
    <tags id="672">12</tags>
    <tags id="672">23</tags>
    <tags id="672">52</tags>
  </medium>
</media>
```

Feed 17: View Campaigns

This feed returns information about campaigns (trackers) within MyAffiliates

Parameters	Description	Type	Possible values
USER_ID	Match a specific affiliate	integer	1
CAMPAIGN_ID	Match a specific campaign	integer	1
METADATA	Do a reverse search for trackers based on their metadata value	string	A string Use the % placeholder as a wildcard eg. %fred%
CREATED_DATE_FROM & CREATED_DATE_TO	return campaigns created between these two datetime values	datetime	2012-01-01 00:00:00 2012-01-01 23:59:59
MODIFIED_DATE_FROM & MODIFIED_DATE_TO	return campaigns modified between these two datetime values	datetime	2012-01-01 00:00:00 2012-01-01 23:59:59

Example Usage - This would return all trackers created on October 1, 2012

http://admin.example.com/feeds.php?FEED_ID=17&CREATED_DATE_FROM=2012-10-01 00:00:00&CREATED_DATE_TO=2012-10-01 23:59:59

Example XML Output

```
<CAMPAIGNS>
  <CAMPAIGN USER_ID="1" USERNAME="affiliate77" CAMPAIGN_ID="1" DESCRIPTION="MY SEO campaign"
    DATE_CREATED="2012-10-12 01:35:44" DATE_MODIFIED="2012-10-15 14:23:03" SPEND="" METADATA="1234"/>
</CAMPAIGNS>
```

Feed 20: Media details

Parameters	Description	Type	Possible values
MEDIA	Media id to retrieve information for	Integer	102

Example Usage - This will return the details for the specified media item by id

http://admin.example.com/feeds.php?FEED_ID=20&MEDIA=102

Example XML Output

```
<media>
  <id>1450</id>
  <media_type id="10" name="Banners"/>
  <title>This is a new media</title>
  <creative>ad_123456</creative>
  <creativeSSL>SSL</creativeSSL>
  <active>active</active>
  <media_source>http://media.example.com/media/example.gif</media_source>
  <preview_image/>
  <description/>
  <created_on>2013-04-30 13:01:10</created_on>
  <last_accessed/>
  <properties>
    <property name="width" value="250"/>
    <property name="height" value="250"/>
  </properties>
  <tag>
    <tag id="115" name="English" type="media_link"/>
    <tag id="53" name="US" type="media_link"/>
    <tag id="16" name="250x250" type="media"/>
    <tag id="8" name="Casino" type="media"/>
    <tag id="3" name="English" type="media"/>
    <tag id="12" name="Slots" type="media"/>
  </tag>
</media>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 22: Remapped Players

This feed returns the players who were remapped between the past date and to date.

Parameters	Description	Type	Possible values
FROM_DATE	Shows players who remapped on or after this date	Date	YYYY-MM-DD
TO_DATE	Shows players who remapped on or before this date	Date	YYYY-MM-DD

Example Usage - This would return players who were remapped between 2010-01-01 and 2014-01-01.

http://admin.example.com/feeds.php?FEED_ID=22&FROM_DATE=2010-01-01&TO_DATE=2014-01-01

Example Output

```
<PLAYERS>
  <PLAYER
    SOURCE_GROUP="XXXXXXX"
    SOURCE_KEY="111111"
    PLAYER_ID="1"
    DISPLAY_INFO="test@test.com"
    JOIN_DATE="2010-03-10"
    FROM_DATE="2012-04-01"
    TO_DATE="2013-10-02"
    AFFILIATE_ID="1"
    AFFILIATE_NAME="user"
    PLAN_NAME="CPA"
    SITE_NAME="test.com"
    LANDING_PAGE="MainPage"
    TRACKING_ID="1"
    MEDIA_ID="0" />
</PLAYERS>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 25: Affiliate Earnings

This feed returns the affiliate earnings

Parameters	Description	Type	Possible values
FROM_DATE	Show affiliate earnings after this date	date	YYYY-MM-DD
TO_DATE	Show affiliate earnings before this date	date	YYYY-MM-DD
USER_ID	ID of the affiliate	integer	1

Example Usage - This would return affiliate earnings between 2013-12-01 and 2013-12-07.

http://admin.example.com/feeds.php?FEED_ID=25&FROM_DATE=2013-12-01&TO_DATE=2013-12-07

Example Output

```
<EARNINGS FROM_DATE="2013-12-01" TO_DATE="2013-12-07">
  <USER USER_ID="176">
    <PLAN PLAN_ID="1">
      <PLAYER_GROUP PLAYER_GROUP_ID="0">
        <ABSOLUTE_EARNINGS>-0.49</ABSOLUTE_EARNINGS>
        <EFFECTIVE_EARNINGS>0.00</EFFECTIVE_EARNINGS>
      </PLAYER_GROUP>
    </PLAN>
  </USER>
  <USER USER_ID="176">
    <PLAN PLAN_ID="1">
      <PLAYER_GROUP PLAYER_GROUP_ID="1">
        <ABSOLUTE_EARNINGS>692.97</ABSOLUTE_EARNINGS>
        <EFFECTIVE_EARNINGS>692.97</EFFECTIVE_EARNINGS>
      </PLAYER_GROUP>
    </PLAN>
  </USER>
  <USER USER_ID="176">
    <PLAN PLAN_ID="2">
      <PLAYER_GROUP PLAYER_GROUP_ID="0">
        <ABSOLUTE_EARNINGS>0.00</ABSOLUTE_EARNINGS>
        <EFFECTIVE_EARNINGS>0.00</EFFECTIVE_EARNINGS>
      </PLAYER_GROUP>
    </PLAN>
  </USER>
</EARNINGS>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Feed 26: Affiliate Account Creation

This feed facilitates the creation of a new affiliate entity in the system. It allows for shell accounts (if set up) and full accounts.

Shell account creation

Parameters	Description	Type	Possible values
account_type	Set this to shell to create a shell account, otherwise leave unset or empty to create a full account.	n/a	shell
PARAM_username	Must be unique	alphanumeric only	
PARAM_password	Must conform to the password policy	string	
PARAM_email	Must be unique	email	
PARAM_country	[optional] Two letter country code. Leave empty or set to XX for <i>Unspecified</i>	string	E.g. UK, US, AU, SE
PARAM_referrer_token	[optional] subaffiliate token	string	
PARAM_plans	[optional] Specify one or Channel IDs to subscribe the affiliate to. The affiliate will also be subscribed to any default channels unless PARAM_PLAN_FORCE is set to 1.	csv	E.g. 1,5,8
PARAM_PLAN_FORCE	[optional] For use with PARAM_plans. When set to 1, the new affiliate will not be subscribed to any default channels and instead only be subscribed to the channels listed in PARAM_plans. This parameter defaults to 0.	boolean	0 or 1

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Example usage for shell account creation

It is recommended to use a POST request so that passwords can not be seen in the URL.

```
curl
http://www.yoursite.com/feeds.php?FEE
D_ID=26 \

-u feed_user:feed_password \

-d account_type=shell \

-d PARAM_username=joebloggs \

-d
PARAM_password=Random$$Password123 \

-d PARAM_email=joebloggs@example.com
\

-d PARAM_country=AU
```

Example formatted response upon an error

```
<?xml version="1.0" encoding="utf-8"?>

<ACCOUNT>

  <INIT ERROR_COUNT="2">

    <ERROR DETAIL="username">

      <MSG>Username not available</MSG>

    </ERROR>

    <ERROR DETAIL="email">

      <MSG>An account with this email already exists.</MSG>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

</ERROR>

</INIT>

</ACCOUNT>

Example formatted response upon successful shell account creation

```
<?xml version="1.0" encoding="utf-8"?>
```

```
<ACCOUNT STATUS="new"  
VALIDATION_CODE="5912b1esds408.23b2913d1sdsbefef6036fsdfee731c5.60234649">
```

```
<INIT ERROR_COUNT="0"></INIT>
```

```
<USERNAME>joebloggs</USERNAME>
```

```
<PASSWORD>Random##Password123</PASSWORD>
```

```
<PARENT>0</PARENT>
```

```
<USERID>3822</USERID>
```

```
<COUNTRY>AU</COUNTRY>
```

```
<LANGUAGE>0</LANGUAGE>
```

```
<EMAIL>joebloggs@example.com</EMAIL>
```

```
</ACCOUNT>
```

Full account creation

All parameters described above as well as all other parameters that have been defined as full affiliate signup fields. Please interrogate the feed to see what is required.

Note that all fields other than *account_type* are prefixed with *PARAM_*

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

Example usage for full account creation

It is recommended to use a POST request so that passwords can not be seen in the URL.

```
curl http://www.yoursite.com/feeds.php?FEED_ID=26 \  
  
-u feed_user:feed_password \  
  
-d PARAM_username=joebloggs22 \  
  
-d PARAM_password=Random$$Password123 \  
  
-d PARAM_email=joebloggs22@example.com \  
  
-d PARAM_country=AU
```

Example formatted response upon an error. This is an example only, your affiliate detail setup will be different.

```
<?xml version="1.0" encoding="utf-8"?>
```

```
<ACCOUNT>
```

```
<INIT ERROR_COUNT="7">
```

```
<ERROR DETAIL="first_name">
```

```
<MSG>First name is missing.</MSG>
```

```
</ERROR>
```

```
<ERROR DETAIL="last_name">
```

```
<MSG>Last name is missing.</MSG>
```

```
</ERROR>
```

```
<ERROR DETAIL="dob">
```

```
<MSG>Date of birth is missing</MSG>
```

```
</ERROR>
```

```
<ERROR DETAIL="address">
```

```
<MSG>Address is missing.</MSG>
```

```
</ERROR>
```

```
<ERROR DETAIL="zip">
```

```
<MSG>Zip / Postcode is missing.</MSG>
```

```
</ERROR>
```

```
<ERROR DETAIL="city">
```

```
<MSG>City is missing</MSG>
```

```
</ERROR>
```

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

<ERROR DETAIL="agreement">

<MSG>You must agree to the terms and conditions.</MSG>

</ERROR>

</INIT>

</ACCOUNT>

The above indicates some missing required parameters. Note that supplying parameters must be prefixed with PARAM_, for example, supplying a value for *first_name* must be submitted as *PARAM_first_name*

Feed 27: Transaction Creation (Manual and Administrative)

This feed can be used to create the following types of transactions:

- Manual Payment Issued Transaction
- Administrative Adjustment Transaction

Parameters	Description	Type	Possible values
USER_ID	The ID of the affiliate to create the transaction for.	Integer	>1
TRANSACTION_TYPE	This field identifies which type of transaction will be created. Only valid types are: • 4: Administrative Adjustment • 11: Manual Payment Issued	Integer	4 or 11
TRANSACTION_DATE	The date of the transaction.	string: Date (YYYY-MM-DD)	YYYY-MM-DD
DISPLAY_DATE	The date that will be displayed for the transaction..	string: Date (YYYY-MM-DD)	YYYY-MM-DD
AMOUNT	Transaction amount.	Decimal	-40.66

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

	If Manual the amount must be negative, if Administrative the amount can be positive or negative.		
CONVERTED_AMOUNT	The amount for the transaction converted to the affiliates currency. This field only applies to manual payment issued transactions, and is only required when the affiliate currency is not the same as the system currency.	Decimal	-60.44
VISIBILITY	Set if the transaction is visible.	boolean	yes or no
STATUS	Sets the internal status of the transaction.	string	• Pending • Approved • Paid • Denied • Dead • Rejected.
ASSIGNEE	[optional] The ID of an affiliate manager the transaction is assigned to.	Integer	
WALLET	[optional] The wallet the transaction is created within. This may be required where your program uses the wallet feature. Contact MyAffiliates support for a list of ID for the wallets in your program.	String	
REFERENCE	[optional] Max string of 255	string	
NOTES	[optional] Transaction notes, max string 255	string	
COMMENT	[optional] Add a comment to the new transaction.	string	

PRIVATE AND CONFIDENTIAL

www.myaffiliates.com
support@myaffiliates.com

If successful this feed returns the newly created Transaction ID, otherwise it returns a XML document with the list of errors.

Example Successful Usage:

https://admin.myaffiliates.test/feeds.php?FEED_ID=27&TRANSACTION_TYPE=11&USER_ID=1&TRANSACTION_DATE=2024-03-24&DISPLAY_DATE=2024-03-24&AMOUNT=-40.666&CONVERTED_AMOUNT=-60&REFERENCE=myref&VISIBILITY=yes&STATUS=Pending&ASSIGNEE=&WALLET=01HN98K8TWGQC24VY0988BTDPV&NOTES=foo%20is%20the%20way%20of%20life&COMMENT=foo

Successful Response:

```
<?xml version="1.0"?>
<TRANSACTION TRANSACTION_ID="29704" />
```

Example Un-Successful Usage:

https://admin.myaffiliates.test/feeds.php?FEED_ID=27&TRANSACTION_TYPE=2&USER_ID=1&TRANSACTION_DATE=2024-03-24&DISPLAY_DATE=2024-03-24&AMOUNT=-40.666&CONVERTED_AMOUNT=-60&REFERENCE=myref&VISIBILITY=yes&STATUS=Pending&ASSIGNEE=&WALLET=01HN98K8TWGQC24VY0988BTDPV&NOTES=foo%20is%20the%20way%20of%20life&COMMENT=foo

Un-Successful Response:

```
<?xml version="1.0"?>
<ERRORS>
  <ERROR_REASON>TRANSACTION_TYPE invalid type. Only Manual payment issued(TRANSACTION_TYPE
= 11) and Administrative adjustment(TRANSACTION_TYPE = 4) transaction types can be
created.</ERROR_REASON>
</ERRORS>
```