

FOXAFLEX (OD-303)

Elastomeric Acrylic

DESCRIPTION

FOXAFLEX is a high quality emulsion based on special resin with elasticity properties .

PRINCIPLE CHARACTERISTIC

Good elasticity properties. For interior and exterior paint Excellent adhesion.

High durability.

Could be wash / wipe, not fading and

smelly. Easy to clean Lead and mercury free Alkali Resistant

RECOMMENDED USE

For protection and decoration wall with elongation appearance.

SYSTEM SPECIFICATION

Prime

r (1 coat)

: FOXASEALER WB : OD-101

Finish

(2

: FOXAFLEX : OD-303 coat)

SPECIFICATION DATA AT 20°C

Semi gloss

Gloss Colou See colours card

Specif ic gravit

 1.30 ± 0.1 kg/litre

Solids by volum

Coverage theoretical

40±2%

Varies considerably according to the roughness

and porosity of the surface 5

-7 m² / litre (on smooth surfaces of average

porosity)

30 mi ทเม te s

(d ер en d

on

Touch dry

temperature & humidity)

Dryin g time

•	2
	_
h	0
u	r
S	

Hard dry

Painti ng

interv al

Min 1 hours

Shelf life

12 month (cool and dry place)

SURFACE PREPARATION

Allow the new surface to dry out completely.

Remove all loose or defective paint by thorough brushing and scrapping, using a stiff fibre brush or high pressure water jet.

A good surface preparation is improve performance / life service.

Make a good minor defect with a suitable grade filler (FOXAFILLER) for holes or cracks.

Surface after thorough preparation should be sealed with FOXASEALER. NOTE: Do not apply during wet weather.

INSTRUCTION FOR USE

Stir well before use, to achieve uniformity of colour and good homogeneity. Use the suitable roll for the best result. It is recommended to apply two (2) layers, in order to get better result. Clean all equipment with clean water immediately after use.

RECOMMENDED THINNING

Method of application	Air Spray	Roller/Brush
Thinner No	Water	Water
Thinning	10–15%	0–10%
Nozzle orifice	2 mm	-
Nozzle pressure	4 bar / 57 psi	-

SAFETY PRECAUTION

Keep container tightly close and keep out from the children

Keep away from food, drink, and animal feeding stuff.

Care must be taken when transporting paint. Keep container is a secure up-right position.

Avoid contact with skin and eyes.

Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.

Ensure that there is adequate ventilation in the area where the product is being applied.

Do not breathe the vapour or spray.

Dispose of any paint waste in accordance with the appropriate.

Environmental Quality Regulation.

HEALTH AND SAFETY

For detailed information on the health and safety hazards and precaution for use of this product, please see the **MATERIAL SAFETY DATA SHEET**.

PACKING SIZE AND STORAGE

Packing size Storage

5 and 20 litres.

The product must be storage in accordance with national regulation. Preferred storage conditions are the keep the containers in the dry space provided with adequate ventilation. The container should be sealed tightly.