

Product Data Sheet

FOXAPOX LINING (OX-509)

Polyamine Epoxy

PRODUCT DESCRIPTION

High solid polyamine cured epoxy lining.

RECOMMENDED USE

Two components high solids epoxy for tank lining, interior of steel tanks, pipelines, hopper cars and splash zone.

CHARACTERISTICS

- Tank coating with good chemical resistance against a wide range of chemicals. Good immersion resistance to water, fuel and a wide range of chemicals.
- Is. Lining for concrete.
- a

ct
wi
th
dr
y
fo
o
d
s.
R
e
si
st
a
nt
to
s
al
t
a
n
d
fr
e
s
h
w
at
er

• .
Hi
g
hl
y
a
br
a
si
o
n
a
n
d
i
m
p
a
ct
re
si
st
a
nt
• .

PHYSICAL DATA

C
ol
o
ur

Gross Level

Volume Solid

Dry Film Thickness Number of Coats

Theoretical Coverage
Temp 95° C (dry), 50° R
es

is C
ta (w
n et
ce)

V
O
C

Fl
as
h
P
oi
nt

S
h
el
f
Li
fe
P
ac
k
Si
ze

St
ee
l
Dry
abrasive
blast
in
accor
dance
with
ISO –
Sa 2.5
or
SSPC
– SP
10
“Near
White”
. Blast
to
achiev
e a 25
– 50
micron
s
ancho
r
profile
of as
indicat
e with
a
Ke
ane
Tat
or

SURFACE PREPARATION

Surface Profile Comparator. Remove abrasive residue or dust from surface.

Application Methods
/irless for any

APPLICATION DATA

C
C
r
v
e
r
t
i
c
r
e
l
e
p
r
e
y

Mixing Ratio by Volume

Thinner

Surface Temperature
Dr the
yi de
n w
g poi
Ti nt
m to
e pre

ve
nt
co
nd
en
sati
on

] c
c
c
t
r
y

] r
r
c
l
c
r
l
r
y
l
c
f
e
c
e
t

F
u
l
l
C
u
r
r
e

P
ot
Li
fe

SAFETY PRECAUTION

Keep away from heat, spark and Open flames. Avoid breathing of vapour on skin and eye contact. Keep container closed and store in cool, ventilated area when not in use. Proper ventilation and protective measures must be provided during mixing, application and drying,

to keep vapour concentration within safe limits and to protect against toxic hazard. Necessary safety equipment must be used and ventilation requirements carefully observed, especially in confined or enclosed spaces, such as tank interior and building.

DISCLAIMER

The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.

January 2009