

FOXAPOX LINING (OX-509)

Polyamine Epoxy

PRODUCT DESCRIPTION High solid polyamine cured epoxy lining.

RECOMMENDED USE Two components high solids epoxy for tank lining, interior of steel tanks,

pipelines, hopper cars and splash zone.

CHARACTERISTICS

• Tank coatin g with good chemi cal resista nce agains t a wide range of C r ϵ ε Goo d imm ersio n resis tant to

wate r, fuel and а wide rang e of che mica ls. Li ni n g fo r С 0 nt • a

Dr y Fi I m T hi ck n es s N u m b er of C o at

SURFACE PREPARATION

Shelf Life P ас k Si ze St ее Dry abrasi ve blast in accor dance with ISO – Sa 2.5 or SSPC – SP 10 "Near White" . Blast to achiev e a 25 - 50 micron s ancho profile of as indicat e with a Ke ane Tat or

APPLICATION DATA

Sur fac e Pro file Co mp arat or. Re mo ve abr asi ve resi due or dus t fro m surf ace

A p p lic at ion M et h o d s / i r l e s s s r r a

У

SAFETY PRECAUTION

Keep away from heat, spark and Open flames. Avoid breathin g of vapour on skin and eye contact. Keep contact Keep containe r closed and store in cool, ventilate d area when not in use. Proper ventilati on and protectiv e measure s must be provided during mixing, applicati on and drying,

to keep vapour concentration within safe limits and to protect against topic hazard.

Necessary safety equipment must be used and ventilation requirements carefully observed, especially in confined or enclosed spaces, such as tank interior and building.

DISCLAIMER

The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.

January 2009