

◆ 电气性能/ Electrical		
-阻抗Impedance	75 Ω	
-额定电流/ Rated Current	16A rms	
-额定电压/ Insulation Resistance	50V ac	
-绝缘电阻/ Insulation Resistance	>5G Ω	
-绝缘强度/ Dielectric Strength	0.5 KVac	
-内触点电阻/Inner pin resisitace	$\leq 3m \Omega$	
◆ 机械性能/ Mechanical		
-使用寿命/ Lifetime	>2,000 Mating Cycles	
-可穿线径OD	$\Phi 4.0-7.0mm$	
-插入力 Insertion force	< 25N	
◆ 材料/ Material		
1.外壳/Housing	铝合金+铅黄铜 AL Alloy+Brass	
2. 触点插针/ Pin & Twist 锁定外壳	铅黄铜棒 HPb59-1	
外接触环 / Outside ring	铍铜	
夹线板/Cable Crimp	黄铜带H62	
绝缘套 Insulator	尼龙6+30%玻纤 PA6+30%GF	
3. 绝缘管Insulation tube	PP	
◆ 电镀/ Plating		
1.外壳/ Housing	阳极氧化-红Anodized - red	
2. Twist锁定外壳housing	镀镍/ Nickel Plating	
3. 点插针/ Pin/夹线板/Cable Crimp/外接触环 / Outside ring	镀金/ Gold Plating	

制图 Drawer		审核 Checker	批准 Ratifier	单位 Unit
				mm
日期 Date		宁波金三湖科技有限公司 NINGBO JIN S H U TECHNOLOGY NINGBO CO.,LTD.		
地址:浙江省宁波市海曙区石碶街道谢家湾工业园区 Address: Xiejiachan industrial park , Shiqi street, haishu district, Ningbo city,Zhejiang province, China.				
电话TEL:+86 574 88658456 传真FAX:+86 574 88657334 盖章 Stamp mail: sales@jincabls.com 手机M.T.:+86-15968077279				



单位:mm