



PUMP-SALE-SPECS REV J (11.05.2025)

FP SERIES FOAM PUMP SPECIFICATION

Foam pump shall be **100% made in USA** including castings and machining and shall have the following design components and function. Foam pump manufacturer **shall have** an ISO certified QC program in place with current certification.

Foam pump shall have Duplex Stainless-steel shafts to withstand sea water flush and any brand foam concentrate. Only 1 shaft seal is permitted, and shaft seal shall be capable of **DRY** operation for 10 minutes. Shaft seal shall be simple to repair and replace in the field. Shaft seal materials are 316 stainless casing with double PTFE lips that allow for hydro test pressure to 350 psig without leakage.

Pump rotors shall be herringbone gear design using corrosion resistant materials. Made from bronze alloy and composite materials allowing for continuous operation on water or foam concentrate.

Foam pump connections shall be Groove, NPT, or ANSI 150# FF flange. Pump connections and end covers shall use O ring seals for leak free operation and simple field replacement.

UL and FM Foam pump shall be capable of 261 PSI (18 bar) operation as standard, not a heavy-duty version. Non-UL & FM foam pumps are capable of 300 PSI (21 bar).

Pump shall be quiet and have smooth operation.

Pump shafts shall be supported by composite bushings that are field replaceable and capable of extended operation on water or foam concentrate.

Foam pump **shall not** utilize replaceable casing liners, ball bearings, or timing gears.



PUMP-SALE-SPECS REV J (11.05.2025)

FOAM PUMP MATERIAL SPECIFICATION - ALL MODELS

- BODY : BRONZE ALLOY OR 316 STAINLESS STEEL
- END CASE : BRONZE ALLOY OR 316 STAINLESS STEEL
- SHAFTS : DUPLEX STAINLESS STEEL
- ROTOR : BRONZE ALLOY + COMPOSITE
- BUSHINGS : COMPOSITE
- LIP SEAL : 316 STAINLESS STEEL + PTFE
- RETAINER : 316 STAINLESS STEEL
- CASING SEAL : O-RING
- CONNECTOR SEAL : O-RING