

RBR-64 Industrial Digital Printer



SPECIFICATIONS:-

| | |
|----------------------------|--|
| Machine model | XC11-64 |
| Printer Head | 64 pcs ricoh print head (Arrangement 4×16) |
| Print Thickness | 2-30 mm range is adjustable |
| Max. Print width | 1900 mm / 2700 mm / 3200 mm |
| Max. Fabric width | 1950 mm / 2750 mm / 3250 mm |
| Production mode | 2000 m ² /h (1 pass) 1000 m ² /h (2 pass) 660 m ² /h (3 pass) |
| Image type | JPEG/TIFF/BMP file format, RGB/CMYK color mode |
| Ink Color | Ten colors optional : CMYK/CMYK LC LM Gray Red Orange Blue |
| Types of ink | Reactive/Disperse/pigment/Acid/reducing ink |
| RIP Software | Neostampa/Wasatch/Texprint |
| Transfer Medium | Continuous conveyor belt, automatic unwinding and rewinding |
| Head Cleaning | Auto head cleaning & auto scraping device |
| Power | Power ≤ 40kW (No oven included, the oven is separately equipped) |
| Power supply | 380vac plus or minus 10%, three phase five wire |
| Compressed air | Air flow 0.3m ³ /min, air pressure 0.8mpa |
| Working environment | Temperature 18-28 degrees, humidity 50%-70% |
| Width | 1900 mm / 2700 mm / 3200 mm |
| Overall dimensions | 5480mm(L)×5600mm(W)×2900mm(H)/6280mm(L)×5600mm(W)×2900mm(H)/ 6780mm(L)×5600mm(W)×2900mm(H)/ |
| Weight | 10500 KG / 12000 KG / 13000 KG |

