RBR-64 Industrial Digital Printer



SPECIFICATIONS:-

Machine model	XC11-64
Printer Head	64 pcs ricoh print head (Arrangement 4×16)
Print Thickness	2-30 mm range is adjustable
Max. Print width	1900 mm / 2700 mm / 3200 mm
Max. Fabric width	1950 mm / 2750 mm / 3250 mm
Production mode	2000 m^2/h (1 pass) 1000 m^2/h (2 pass) 660 m^2/h (3 pass)
Image type	JPEG/TIFF/BMP file format, RGB/CMYK color mode
Ink Color	Ten colors optional : CMYK/CMYK LC LM Gray Red Orange Blue
Types of ink	Reactive/Disperse/pigment/Acid/reducing ink
RIP Software	Neostampa/Wasatch/Texprint
Transfer Medium	Continuous conveyor belt, automatic unwinding and rewinding
Head Cleaning	Auto head cleaning & auto scraping device
Power	Power ≤ 40kW (No oven included, the oven is separately equipped)
Power supply	380vac plus or minus 10%, three phase five wire
Compressed air	Air flow 0.3m^3/min, air pressure 0.8mpa
Working environment	Temperature 18-28 degrees, humidity 50%-70%
Width	1900 mm / 2700 mm / 3200 mm
Overall dimensions	5480mm(L)×5600mm(W)×2900mm(H)/6280mm(L)×5600mm(W)×2900mm(H)/ 6780mm(L)×5600mm(W)×2900mm(H)/
Weight	10500 KG / 12000 KG / 13000 KG