



## MOLYLITH EP2 BLACK

### V8130-00

**MOLYLITH EP2 BLACK GREASE** is a lubricating grease formulated to meet the extreme conditions encountered on off-highway construction equipment as well as heavy duty applications. This product is a Lithium Complex thickened grease blended with high viscosity base fluids for exceptional film strength and is fortified with 3% molybdenum disulphide for additional load carrying capacity and antiwear performance.

## SUMMARY OF BENEFITS

MOLYLITH EP2 BLACK GREASE is ideal for wet environments and better performance at high temperatures. Because it is lithium complex thickened grease, MOLYLITH BLACK GREASE EP2 has a high dropping point which also provides excellent protection in high temperature environments. Ideally suited for Truck and Farm applications.

## SPECIFICATIONS AND TECHNICAL DATA

| NLGI GRADE                     | 2               |
|--------------------------------|-----------------|
| THICKENER TYPE                 | LITHIUM COMPLEX |
| TEXTURE                        | TACKY           |
| COLOUR                         | GREY/BLACK      |
| DROPPING POINT °C              | 250 min         |
| FOUR BALL WELD LOAD, KGS       | 500             |
| BASE OIL VISCOSITY @40°C cST   | 460             |
| OPERATING TEMPERATURE RANGE °C | -20 to 150      |

- Safety Data Sheet for this product can be obtained by visiting Vixol Australia Pty Ltd Website [www.vixol.com.au](http://www.vixol.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

Vixol Australia Pty Ltd  
7 Foden Avenue Campbellfield Vic 3061 Australia  
Tel: +61 03 9333 7701 Local sales: 1300 0894684  
Email: [sales@vixol.com.au](mailto:sales@vixol.com.au) [www.vixol.com.au](http://www.vixol.com.au)