

Frame	Aluminium, 3.4kg, for 100mm quick release rear hub, IS type disc brake and sidepull road brake mounts. Road brake reach 45-50mm.
Fork	Aluminium, 585g, 380mm axle-to-crown, 170mm long 1⅝ aluminium straight steerer, road sidepull brake mount. Brake reach 53mm.
Headset	Semi integrated zero-stack ahead 1⅝ (SHIS ZS44/28.6 ZS44/30)
Stem	25.4mm steerer, 25.4mm handlebar clamp, length 100mm, +-25°
Handlebars	Aluminium, 54cm wide, bar end ergo grips
Brakes	Tektro R315 road sidepull, cable housing length 30/140cm
Front wheel	100mm wide hub with allen key spindle (compatible with standard quick releases), 6000RS cartridge bearings, 622x20 rim, 32 stainless 281mm long 13G spokes, 25-622 Kenda Kriterium tire. Max tire width 32mm
Rear wheel	100mm wide hub with allen key spindle (compatible with standard quick releases), 6000RS cartridge bearings, 622x20 rim, 32 stainless 281mm long 13G spokes, 25-622 Kenda Kriterium tire. Max tire width 28mm

Notes:

There's an extension collar available to get more ground clearance to the frame. Frame height is optimized for smooth race tracks and could be too little if your roads are less perfect. We recommend ordering an extension collar with every Race max 28 unless you know you don't need it.

