

SUPER OUTBOARD OIL is a premium low smoke engine oil formulated with an ashless additive system, designed for all water cooled two stroke outboard engines including oil injected and pre-mix systems. SUPER OUTBOARD OIL is self-mixing and suitable for oil injection systems often fitted to modern two stroke outboards.

SUMMARY OF BENEFITS

- Approved by the National Manufacturers Association (NMMA) for service TC-W3 - Superior friction and wear control.	SUPER OUTBOARD OIL should be mixed according to the ratio recommended by the manufacturer. It can be used at fuel/oil ratios of up to 100/1 however, 50/1 ratio is advised in the absence of engine recommendations.
--	---

SPECIFICATIONS

Suitable for all outboard two stroke engines operating on leaded or unleaded petrol with or without injection lubrication

- EVINRUDE
- MERCURY
- YAMAHA
- TOHATSU

- JOHNSON
- FORCE
- SUZUKI
- MARINER

TECHNICAL DATA

CHARACTERISTICS	OUTBOARD TCW-III
Specific gravity at 15 C	0.8716
Kinematic viscosity at 40 C, mm ² /s (cSt)	50.3
Kinematic viscosity at 100 C, mm ² /s (cSt)	7.5
Viscosity index	110
Colour	Blue

- Safety Data Sheet for this product can be obtained by visiting Vixol Australia Pty Ltd Website www.vixol.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C