

large-sized cylindrical

Nesscap's large-sized cylindrical EDLC cells range from 650F to 3400F in capacitance with operating voltage of 2.7V and 3.0V. These cells were developed to meet market requirements for robustness, compact size, high energy density, and long cycle life.

These cells incorporate superior leakage protection and industry leading

shock, rotation and vibration safeguards.

These cells are available with threaded or weldable terminals.

Line-Up



Size	Rated Voltage (V,DC)	Rated Capacitance (F)	MAX				Volume (ml)	Weight (g)	Part Number	sheet Download
			ESR(mΩ)	Dimension(mm)						
			DC	D	L	WT				
Large Cylindrical Weldable	2.7	2000	0.33	60.2	102.0		307	390	ESHSR-2000C0-002R7A5	
	2.7	1600	0.41	60.2	85.0		259	335	ESHSR-1600C0-002R7A5	

Size	Rated Voltage (V,DC)	Rated Capacitance (F)	MAX	Dimension(mm)				Volume (ml)	Weight (g)	Part Number
			ESR(mΩ)	DC	D	L	W			
Large Cylindrical Weldable	2.7	3000	0.26	60.2	138.0			410	530	ESHSR-3000C0-002R7A5
	2.7	3000	0.26	60.2	139.0			470	535	ESHSR-3000C0-002R7A5T
	2.7	2000	0.33	60.2	103.0			367	395	ESHSR-2000C0-002R7A5T
	2.7	1200	0.48	60.2	74.0			228	280	ESHSR-1200C0-002R7A5
	2.7	1200	0.48	60.2	75.0			288	285	ESHSR-1200C0-002R7A5T
	2.7	650	0.60	60.2	51.5			164	205	ESHSR-0650C0-002R7A5
	2.7	650	0.60	60.2	52.5			223	210	ESHSR-0650C0-002R7A5T

詳細規格請參考附件檔案

業務請洽承實業有限公司, 業務鄭瑞明 Tel : 02 2898 4050, MP : 0916 205145

Email : ray@compplus.com.tw & ray.jeng@seed.net.tw