

# X-TRAN S 75w90

## TRANSMISSION OIL

### DESCRIPTION

This is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its special composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials.

### PROPERTIES

- Excellent activity against high temperature load
- Very strong activity against wear, corrosion and foam
- Low pour point
- Very special EP-properties
- Excellent "Limited Slip" properties
- Widely usable

### APPLICATION

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.). of trucks and four-wheel drive vehicles.

### TYPICALS

Density at 15 °C	0,869 kg/l
Viscosity 40 °C	101,00 mm²/s
Viscosity 100 °C	15,40 mm²/s
Viscosity index	150
Flash point COC	218 °C
Pour point	-40 °C
Total base number	2,1 mgKAOH/g

### SPECIFICATIONS

API GL-4, GL-5, MT-1  
DAF GL5/MIL-PRF-2105E  
IVECO VOITH 3.325-340  
MACK GO-J EO-H  
MAN 341 E-3, 341 Z-2, 342 M-3, 3343 /SL 342 S1/342 SL  
MB 235.6/235.8  
MIL PRF-2105E  
RENAULT B0032/3 Annex 3  
SAE J 2360  
SCANIA STO 1  
ZF TE-ML 02B, TE-ML 05B, TE-ML 07<sup>a</sup>, TE-ML 08, TE-ML 12B, TE-ML 12L,  
TE-ML 12N, TE-ML 16F, TE-ML 17B, TE-ML 19C, TE-ML 21B  
TMS 6816  
DIN 51517

### PACKAGING

1L can (12 x 1L carton)  
5L can (4 x 5L carton)  
20 L drum  
60 L drum  
208 L drum