



Article / Review / Mini Review

## Author's Guide for Manuscript Preparation for Green Chemical and Environmental Engineering (14pt, Roboto) (length of not more than 3 lines is recommended)

Thielscher Labeit<sup>1,\*</sup>, Ericshen Frandsen<sup>2</sup> (12pt, Roboto)

<sup>1</sup> Laboratory of Nanotechnology, Department of Chemical Engineering, Faculty of Industrial Technology, University xx, Rabat, Morocco

(10 font, spacing: 1)

<sup>2</sup> Affiliation, Department, Faculty, University, Address, City, Country

<sup>2</sup> Affiliation, Department, Faculty, University, Address, City, Country

### ARTICLE INFO

**Received:** xx August 20xx

**Revised:** xx November 20xx

**Accepted:** xx December 20xx

**Keywords:**

Biodiesel;

Chlorella sp.;

Microwave;

In Situ Transesterification;  
Energy.

**\*Corresponding author:**

[thielser.labeit@yahoo.com](mailto:thielser.labeit@yahoo.com)

**DOI:** [10.63288/jgcee.v3i1.xx](https://doi.org/10.63288/jgcee.v3i1.xx)

### ABSTRACT

The abstract should be cohesive and adequate, implying the research question and major findings as a standalone paragraph. No references or abbreviations are required in this section. Also, the abstract section should not be less than **one hundred fifty (150) words** and should not exceed **two hundred fifty (250) words**. It should be placed under the title with a single space from the title. Avoid writing a long formula and define all symbols used in the abstract. The abstract should be a single paragraph with the following content: **Background:** highlight the targets of the research; **Methods or process:** concise description of the main processes or methods applied in the research work; **Results:** present the article's main findings or significant results and the author should avoid the discussion of the results in the abstract; **Conclusion:** the main conclusions of the research work that can be drawn should be present without magnify the conclusions. (10pt, Roboto).

## 1. Introduction (12pt)

(Firstline: 0,5cm) The rapid increase in energy consumption, especially in the transportation sector, has led to an energy crisis that has resulted in a decrease in fossil fuel supplies and an increase in environmental pollution [1]. The paper should be organized into logical parts or sections. Any subsection is given a brief numbered heading. The contents include the introduction that should clearly define the nature of the problem, and the references should be made to previously published papers. Theoretical, experimental, results, discussions, and conclusions form the main sections of the paper. The theoretical section extends the analytical background of the article and develops a new formulation of the problem. Calculations are achieved here using the developed equations, and the modifications should be pointed out. Depending on the suggested research methods, the experimental investigation is achieved, using the testing instruments or designing and manufacturing a test rig. Materials and methods are detailed here [2-4]. In the results and discussions section, the significance of the obtained results should be pointed out, and the citations and the discussions of the kinds of literature should be avoided in this section [2], [5], [6]. Sometimes results and discussions are combined in one section. (11pt, Roboto, 1,15).



Next Paragraph. (spacing: 0,0). The manuscript was checked for plagiarism using **Turnitin or iThenticate** ( $\leq 20\%$ ).

## **2. Research and Methodology (12pt)**

### **2.1. Second-Order Heading (11pt)**

#### **2.1.1. Third-Order Headling (11pt)**

(Firstline: 0,5cm) The theoretical section extends the analytical background of the article and develops a new formulation of the problem. Calculations are achieved here using the developed equations, and the modifications should be pointed out. They should be described with sufficient detail to allow others to replicate and build on published results. Please state the manufacturer, city and country from where the materials have been sourced. (11pt, Roboto, 1,15).

### **2.2. Experiments (11pt)**

(Firstline: 0,5cm) The reactors consist of a centrally oriented conversion chamber within their setup and possess several small air holes at the base. The chamber houses the feed to be converted, while the combustion fuel for heat generation occupies the 'heating gap' between the chamber and the reactor itself. (11pt, Roboto, 1,15).

### **2.3. Product characterization (11pt)**


(Firstline: 0,5cm) The products (biomass biochar and hybrid biochar) recovered from the process were characterized to ascertain some of their properties using Scanning Electron Microscope with energy Dispersive X-ray Spectroscopy (SEM-EDS), Fourier Transform Infra-Red Spectroscopy (FTIR) and Brunauer-Emmet-Teller (BET) analysis. Scanning Electron Microscopy (SEM, Phenom proX, Phenom-World BV, Netherlands) was used to study the surface morphology of the particles of the biochar. A double adhesive was placed on a sample stub. The sample was sprinkled on the sample stub and subsequently taken to a sputter coater (Quorum-Q150R Plus E) and coated with 5 nm of gold. (11pt, Roboto, 1,15).

## **3. Results and Discussion (12pt)**

### **3.1. Temperature profile (11pt)**

#### **3.1.1. Third-Order Headling (11pt)**

(Firstline: 0,5cm) This section focuses on the precise description of the experimental or theoretical results. The interpretation of the results and their conclusions should also be presented in this section. Authors should discuss the results and how they can be interpreted from the viewpoint of research works found in the literature and of the working hypotheses. The results and their implications should be discussed in the broadest context possible.



**Figure 1.** The figures with high resolution, with using high-quality graphical tools. Copyright © 2026, ACS. (JPEG and PNG format)

### 3.2. Product yield (11pt)

(Firstline: 0,5cm) The bio-char yield for both processes was computed using the system in eq. 1.

$$m_{Bio-char} = (M_3 - M_2) \tag{1}$$

$$Yield_{Bio-char} = \frac{m_{Bio-char}}{m_{raw}} \times 100 \% \tag{2}$$

(Firstline: 0,5cm) Where  $M_1$  = mass of conversion chamber + Feed (in grams),  $M_2$  = mass of conversion chamber (in grams),  $M_3$  = ... summarized in Table 1.

**Table 1.** Tables should be placed in the main text near to the first appearance in the text

Index	Title A	Title B
Entry A	data	data
Entry B	data	data
Entry C	data	data
Entry D	data	data
Entry E	data	data
Entry F	data	data

### 3.3. Product composition (11pt)

(Firstline: 0,5cm) The composition of the products was determined using Energy Dispersive X-ray spectroscopy (EDS). The spectrums are shown in Figure 2, and the results are summarized in Table 2. The only major component missing is Hydrogen. From the results in Table 2, it can be observed that the hybrid.




Figure 2. The mechanism of the (Software Origin) [14]

### 3.4. Biochar functional groups (11pt)

(Firstline: 0,5cm) Table 3 shows the functional groups of raw .... correspond to the alkoxy (C-OH) group. The peak  $1635\text{ cm}^{-1}$  observed in the biomass spectra, which shifted to  $1620\text{ cm}^{-1}$  and  $1573\text{ cm}^{-1}$  in biomass. Retort heating also underlines the usability of the process even in remote locations or on-site.

### 4. Conclusion (12pt)

A conclusion should point out the distinguished results of the achieved work and should not replicate the abstract. A conclusion may suggest recommendations for work extension and new applications.

**Author contributions:** Conceptualization, xx. and xx; data curation, X.X.; formal analysis, X.X.; investigation, X.X.; methodology, xx.; project administration, X.X, resources, X.X.; software, X.X.; supervision, X.X.; validation, X.X., Y.Y. and Z.Z.; visualization, X.X.; writing—original draft preparation, X.X.; writing—review and editing, X.X. All authors have read and agreed to the published version of the manuscript.

**Acknowledgement:** Acknowledgements may be directed to individuals or institutions that have contributed to the research or a government agency. This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

**Conflict of Interest:** The authors declare no conflicts of interest.

### 5. References (12pt)

References should follow the **IEEE style (Tools Mendeley or Zotero, etc)**. References to journal articles or any work should include the year of publication, full title, the full name of the publication in

which it appeared, volume number and page numbers of the cited article. References to textbooks and technical reports should include the year of publication, full title, publisher, city of publication and the page numbers of the work being cited. Reference numbers are set flush left and form a column of their own, containing the reference. The reference numbers are on the line, enclosed in square brackets. In all references, the given name of the author or editor is abbreviated to the initial only and precedes the last name. Abbreviations should be used where appropriate, for example, Dept. in place of *Department*, Eng. for *Engineering*, and Univ. instead of *University*. A space of (6 pt. line space) is left between two references. The **minimum required number of references is 25**. The forms of writing the references are as follows:

**Journal:**

[No.] Initial(s). Lastname, "Article title," Journal Abbreviation, vol. X, no. Y, pp. xxx–xxx, Month Year.  
<https://doi.org/xxxxx>

[1] A. B. Siregar and C. D. Putra, "Green synthesis of biodiesel from waste cooking oil," J. Green Chem. Environ. Eng., vol. 5, no. 2, pp. 101–110, Jun. 2024.  
<https://doi.org/10.1234/jgcee.v5i2.5678>

[2] L. Chen, Y. Wang, and H. Zhao, "Photocatalytic degradation of organic pollutants using TiO<sub>2</sub>," Chem. Eng. J., vol. 450, no. 1, pp. 120–130, Jan. 2023.  
<https://doi.org/10.1016/j.cej.2022.138123>

[3] M. K. Gupta and S. Patel, "Sustainable hydrogen production via electrolysis," Int. J. Hydrogen Energy, vol. 48, no. 10, pp. 5000–5012, Mar. 2023.  
<https://doi.org/10.1016/j.ijhydene.2022.11.045>

**Conference Proceedings:**

[4] R. K. Ahmad and L. Wijaya, "Catalytic conversion of biomass into biofuel," in Proc. Int. Conf. Sustain. Energy, 2023, pp. 55–60. <https://doi.org/10.1109/icse.2023.1234567>

[5] D. Nguyen and T. Le, "Optimization of wastewater treatment using membrane technology," in Proc. IEEE Int. Conf. Environ. Eng., 2022, pp. 200–205.  
<https://doi.org/10.1109/icee.2022.9876543>

[6] S. Rahman, B. Ali, and M. Hossain, "Solar-driven desalination system design," in Proc. World Renew. Energy Congr., 2021, pp. 89–94. <https://doi.org/10.1016/j.wrec.2021.05.010>

**Book:**

[7] J. Smith, Green Chemistry: Principles and Applications. New York, NY, USA: Springer, 2020.

[8] P. T. Anastas and J. C. Warner, Green Chemistry: Theory and Practice. Oxford, U.K.: Oxford Univ. Press, 1998.

[9] R. A. Sheldon, I. Arends, and U. Hanefeld, Green Chemistry and Catalysis. Weinheim, Germany: Wiley-VCH, 2007.

**Website:**

[10] World Health Organization, "Air pollution and health," 2022. [Online]. Available: <https://www.who.int/news-room/fact-sheets/detail/air-pollution>

**Book Chapter:**

- [11] M. T. Brown, "Sustainable waste management," in Handbook of Environmental Engineering, 2nd ed., R. Kumar, Ed. London, U.K.: Elsevier, 2021, pp. 200–220.

**Submission Requirements:**

Authors must upload the following documents during submission:

- The manuscript follows the journal template (IEEE style)**
- Turnitin similarity report is attached ( $\leq 20\%$ )**
- Graphical abstract is included as a separate file ([template](#))**
- Statement of originality is signed and uploaded ([file](#))**
- All authors' information is complete**

Submissions without these documents will not be processed.