

Merge 2 Single linked lists :

Assuming both SSL are in Increasing order nOutput:

List Called

A: 1 → 3 → 5 → 7 → NULL Second Linked List Called

B: 2 → 4 → 6 → NULL

****After Merge: 1 → 3 → 5 → 7 → 2 → 4 → 6 → NULL ****

After Merge: 1 → 2 → 3 → 4 → 5 → 6 → 7 → NULL

```
merge_sorted(head1, head2)
    if (head1 == null)
        return head2
    if (head2 == null)
        return head1
    if (head1.data <= head2.data)
        mergedHead = head1
        head1 = head1.next
    else
        mergedHead = head2
        head2 = head2.next
    end if
    mergedTail = mergedHead
    while (head1 != null && head2 != null)
        temp = null
        if (head1.data <= head2.data)
            temp = head1
            head1 = head1.next
        else
            temp = head2
            head2 = head2.next
        endif
        mergedTail.next = temp;
        mergedTail = temp;
    end while
    if (head1 != null)
        mergedTail.next = head1
    else if (head2 != null)
        mergedTail.next = head2
    endif
    return mergedHead
```

-----*

Given a pointer to the head of a singly-linked list, print each value from the reversed list.
If the given list is empty, do not print anything.

Linked List : 1 → 2 → 3 → NULL

Example Output Reversed Linked list : 3 → 2 → 1

`PrintReversed(head)`

#input is head node in linkedlist output print list reversed

```
    If(head =null)
        return
    else
        PrintReversed(head.next)
        Print(head.data)
    End if
end
```

-----*

Write an algorithm the deletes nodes with odd values Output:

if the given Linked list is : 10 -> 7 -> 40 -> 9

the list should be : 10-> 40*

`DeleteODD()`

```
    p=head
    if(p.data mod 2==1)
        deleteFirst()
        p=head
    End if
    c=p.next
    WHILE c!= NULL:
        if c.data mod 2==1
            p.next=c.next
        end if
        c =p
        p=p.next
    end while
```

-----*

*Write an algorithm that prints alternant nodes first from head to tail , second from tail to head Example: if the given list is : 10 -> 40 -> 30 -> 60

1. 2. 3. 4

Output 1 (from head to tail) : 10 , 30

Output 2 (from tail to head) : 40 , 60

`printAlter()`

```

c=head
i=1
WHILE c!= NULL:
    if i mod 2==1
        print (c.data)
    endif
    c=c.next
    i=i+1
end while

```

10 -> 40 -> 30 -> 60

```

printAlterFromtail(head,size)
if head=null
    return
else
    printAlterFromtail(head.next,size-1)
    if size mod 2==1
        print(head.data)
    end if
end if

```

60 40

-----*

Write an algorithm that adds an input after all odd position Example:

1. 2. 3. 4

if the given list is : 10 -> 40 -> 30 -> 60 if input : 2

Output: 10->2->40->30->2-> 60

Note: Position of original nodes is : 0 -> 1 -> 2 -> 3 then add before position 1 and 3

```

inserAfterOdd(e)
c=head
i=1
WHILE c!= NULL:
    if i mod 2==1
        n=new Node(e,c.next)
        c.next=n
    end if
    c=c.next
    i=i+1
end while

```