

CSS3 超連結與滑鼠游標特效

© by Roberts Han-Chiuan Luo, 蘿蔔絲. 羅

14-3 超連結與滑鼠游標特效

14-3-1 [超連結特效](#)

14-3-2 [滑鼠游標特效](#)

14-3-1 超連結特效

語法：

```
a {樣式屬性: 屬性值;} /*宣告超連結樣式*/
a:link {樣式屬性: 屬性值;} /*未拜訪過的超連結樣式*/
a:visited {樣式屬性: 屬性值;} /*已拜訪過的超連結樣式*/
a:active {樣式屬性: 屬性值;} /*執行中超連結樣式*/
a:hover {樣式屬性: 屬性值;} /*當滑鼠移到連結時的超連結樣式*/
```

例如：

```
<!-- 例一，課本14-28頁。-->
<style type="text/css">
  a {border: 1px red solid;}
  a:link {color: black;}
  a:visited {color: blue; border: 0px;}
  a:active {color: yellow;}
  a:hover {border: 1px green solid; text-decoration: none;}
</style>
```

注意：在 a 選擇器中設定的樣式會繼承給 a:link, a:visited, a:active, a:hover 選擇器。

```
<!-- 例二，課本14-29頁，範例 ch14_08.htm -->
<style type="text/css">

a {
  border: 1px #A498BD solid;
  color: #4D2078;
  background-color: #EEEEBF;
  height: 20px;
  padding: 5px; /* 把這裡改成 25px, 看看會有什麼不同呢！ */
  width: 120px;
```

```

        text-align:center;
    }

a:hover {
    border: 2px #605080 solid;
    color: #9900CC;
    background-color: #BDAAE2;
}

</style>


<br />
<a href="#">回首頁</a>
<a href="#">與我聯絡</a>
<!-- # 是空連結的意思 -->

```

```

<!-- 例三，課本14-31頁，範例 ch14_09.htm，當滑鼠移到超連結上時會更換另一張圖片 -->
<style type="text/css">
a {
    color: #990000;
    height: 56px;
    width: 200px;
    text-align: center;
    line-height: 55px;
    background-image:
url(http://1.bp.blogspot.com/-RNDVswdLqek/UslwUCBBdyl/AAAAAAAAIT8/5Ngq7Uk_G4w/s1
600/btn2.jpg);
    text-decoration: none;
}

a:hover {
    color:#FFCC00;
    background-image:
url(http://4.bp.blogspot.com/-qTevxyfLR9M/UslwUOCY87I/AAAAAAAAIT4/3aCNstwCpsw/s16
00/btn2a.jpg);
}
</style>

```

```
<a href="#">公司簡介</a>
<a href="#">產品簡介</a>
<a href="#">與我聯絡</a>
<a href="#">回首頁</a>
```

```
<!-- 例四, http://www.w3schools.com/cssref/tryit.asp?filename=trycss\_sel\_link\_more2 -->
<style type="text/css">
a.ex1:hover,a.ex1:active {color:red;}
a.ex2:hover,a.ex2:active {font-size:150%;}
a.ex3:hover,a.ex3:active {background:red;}
a.ex4:hover,a.ex4:active {font-family:monospace;}
a.ex5:visited,a.ex5:link {text-decoration:none;}
a.ex5:hover,a.ex5:active {text-decoration:underline;}
</style>

<p>Mouse over the links to see them change layout.</p>

<p><a class="ex1" href="#">This link changes color</a></p>
<p><a class="ex2" href="#">This link changes font-size</a></p>
<p><a class="ex3" href="#">This link changes background-color</a></p>
<p><a class="ex4" href="#">This link changes font-family</a></p>
<p><a class="ex5" href="#">This link changes text-decoration</a></p>
```

[\[回頁首\]](#)

14-3-2 滑鼠游標特效

語法：

cursor: 滑鼠游標樣式

參考：http://www.w3schools.com/cssref/playit.asp?filename=playcss_cursor&preval=alias

cursor 樣式	cursor 樣式	cursor 樣式
auto (預設值)	help	row-resize
crosshair	progress	e-resize
pointer	not-allowed	ne-resize
text	no-drop	n-resize

move	all-scroll	nw-resize
wait	col-resize	

<!-- 例一，參考課本 14-32頁 -->

<style type="text/css">

 a { cursor: crosshair; }

</style>

<!-- 例二，參考課本 14-33頁，範例 ch14_10.htm -->

<title>自訂滑鼠游標</title>

<style type="text/css">

 body {cursor: url(images/my.cur),

 url(http://1.bp.blogspot.com/-Py_6mt6uwpY/UslwUfdeNGI/AAAAAAAAIUA/VlIgtQYpH7Q/s1600/border.png), auto;} /*先找第一圖，再找第二圖，最後預設*/

</style>

<body>

</body>

[\[回頁首\]](#)