

FOXA ROADLINE SB (OX-101 RL)

PRODUCT DESCRIPTION	A fast drying, acrylic solvent based synthetic gloss enamel. There is no need or a primer or undercoat on most surfaces.
RECOMMENDED USE	Suitable use for road marking.
CHARACTERISTICS	<p>Good gloss and colour retention.</p> <p>Rapid drying-time.</p> <p>Good exterior durability.</p> <p>Good flexibility and abrasion resistance.</p>

PHYSICAL DATA

Colour

Gloss Level

Volume Solid

Dry Film Thickness

Available on request
Satin / Gloss
Approx. 55%
microns

Number of Coat

Theoretical Coverage

Temperature Resistance

Flash Point

Shelf Life

n
s
p
e
r
c
o
a
t
2
5
.
5
s
q
.
m
/
f
o
r
1
0
0
m
i
c
r
o
n
s
M
a
x
i
m
u
m
:
8
0
0
C
(
d
r
y
)
3
6
0
C
A
t
l
e
a
s
t
1
2
m
o
n
t

0.38 — 0.46 (0.0015 — 0.018 in ch) 10 NPa (approx. 1400 psi) 1.8 — 2.0 mm (

Ensure surface is in sound condition. Remove any grease, dust or dirt. If necessary, wash down with water and detergent followed by a rinse with clean water. Allow to dry.

Application Methods

Airless Spray

Nozzle Pressure
Conventional Spray

Nozzle Tip

Nozzle Pressure

Mixing Ratio

Thinner

Surface Temperature

0
.
0
7
1
-
0
.
0
7
9
i
n
c
h
)
0
.
3
M
P
a
(
a
p
p
r
o
x
.
4
3
p
s
i
)
C
n
e
c
o
n
p
o
n
e
n
t
F
C
X
A
N
N
E
R
0
0
1
S
h
o
u
l
d
b
e

100°C - 490°C, at least 30°C above the dew point to prevent condensation 10 minutes

Drying Time

Touch Dry

a
t
2
5
0
C
,
5
m
i
n
u
t
e
s
a
t
3
2
0
C
2
h
c
u
r
s
e
t
2
h
c
(
,
h
c
u
r
s
e
t
2
h
c
(
2
h
c
u
r
s
e
t
2
h
c
(
,
h
c
u
r
s
e

Trough Dry
Overcoating

Minimum

t
s
z
c

c
l
r
l
i
r
i
t
e
c
(
r
c
l
s
h
e
r
e
c
e
r
c
c
r
)
)

Maximum

SAFETY PRECAUTION

Keep away from heat, spark and open flames. Avoid breathing of vapour on skin and eye contact. Keep container closed and store in cool, ventilated area when not in use.
Proper ventilation and protective measures must be provided during mixing, application and drying, to keep vapour concentration within safe limits and to protect against toxic hazard.
Necessary safety equipment must be used and ventilation requirements carefully observed, especially in confined or enclosed spaces, such as tank interior and building.

ISSUED: **January 2010**