JOB SAFETY ANALYSIS FORM

JOB SAFETY ANALYSIS	Job Title: Tire Changer TITLE OF PERSON WHO DOES JOB:		JSA Number		DATE:	□ NEW □REVISED Page: of
			SUPERVISOR:		ANALYSIS BY: REVIEWED BY:	
PLAN		LOCATION:	DEPARTMENT:		APPROVED BY:	
SEQUENCE OF BASIC JOB STEPS		POTENTIAL HAZARDS		RECOMMENDED ACTION OR PROCEDURE		
General Use		Foot injury from dropped object on foot		Wear steel toed safety boots or shoes		
		Trauma from over-inflated tires, bent rims, no properly secured within restraining device		Follow manufacturer's instructions.		
		Eye injury from flying debris		Safety glasses with side shields or goggles		

Pre-Start Checklist:

• Perform pre-operational inspection and document inspection.

PPE Required

- Safety shoes/boots.
- Safety glasses with side shields or goggles.

Equipment Procedures/Requirements:

- Operate equipment in strict accordance with manufacturer's instructions as listed.
- Only authorized users can operate equipment.
- Never stand with any part of the body over tire changer during inflation process.
- Never exceed industry recommendations for inflation (psi).
- During inflation, observe pressure frequently and avoid distraction to prevent over-inflation.
- Report any observed defect or safety hazard to your supervisor immediately.
- Where any object handled would possibly cause injury to feet if dropped, safety shoes/boots will be worn.
- Where any object handled could possibly cause cuts, punctures or abrasions to hands, appropriate gloves will be worn. (Exception: where rotating machinery presents a greater hazard of entangling gloves, they are optional with written justification).

JOB SAFETY ANALYSIS FORM

• Keep hands, hair and loose clothing clear of all moving parts.