

Authentication

All calls must include an `api_key` in the header. For some GET requests, the `api_key` can be a query param.

Create New Trip

URL: `https://api.errands.nyc/k/trips`

Method: POST

Payload (required):

```
{
  "pickupName": "Test Pickup Name",
  "pickupAddress": {
    "street": "908 Driggs Ave",
    "streetLine2": "Unit XYZ",
    "city": "Brooklyn",
    "state": "NY",
    "zipCode": "11205"
  },
  "pickupPhone": "7185048700",
  "dropoffName": "Test Drop off Name",
  "dropoffAddress": {
    "street": "907 Driggs Ave",
    "streetLine2": "",
    "city": "Brooklyn",
    "state": "NY",
    "zipCode": "11205"
  },
  "dropoffPhone": "7185048700",
  "numberOfPackages": 1,
  "packageType": "bag",
}
```

The following optional fields can be added to the payload:

```
{
```

```
"note": "Sample Note",
"poNumber": "Ref123",
"tripScheduleTime": "2023-11-13T21:47:49.625Z",
}
```

In the response you will get the **trip** as json, including the **trip.id** to be used for Status updates and checkups.

- Webhooks and callbacks are currently being tested

"packageType" must be one of the following, all **lowercase**

- bag
- box
- invitation
- luggage
- envelope
- flower
- gift_arrangement
- garment_bag
- open_wrap
- delicate
- other

"pickupPhone" and **"dropoffPhone"**

- Must be real US or Canada phone numbers
- Must be at least 10 digits,
- Only Allowed Area codes
- Leading "1", or "+1" is allowed

Get trip status

Use either one of the following URLs

- For UUID: https://api.errands.nyc/k/trips/{trip_id}?api_key={your API key}

- For order number:
https://api.errands.nyc/k/trips/o/{orderNumber}?api_key={your API key}

Method: GET

`api_key` can be in the header or as a query param

Response:

```
{
  "numberOfPackages":1,
  "paymentStatus":"unpaid",
  ...More...
}
```