

```
#
# XAMPP settings
#

<IfModule env_module>
    SetEnv MIBDIRS "/xampp/php/extras/mibs"
    SetEnv MYSQL_HOME "\\xampp\\mysql\\bin"
    SetEnv OPENSSL_CONF "/xampp/apache/bin/openssl.cnf"
    SetEnv PHP_PEAR_SYSCONF_DIR "\\xampp\\php"
    SetEnv PHPRC "\\xampp\\php"
    SetEnv TMP "\\xampp\\tmp"
</IfModule>

#
# PHP-Module setup
#

LoadFile "/xampp/php/php5ts.dll"
LoadModule php5_module "/xampp/php/php5apache2_4.dll"

<FilesMatch "\.php$" >
    SetHandler application/x-httpd-php
</FilesMatch>

<FilesMatch "\.phps$" >
    SetHandler application/x-httpd-php-source
</FilesMatch>
```

```
#  
# PHP-CGI setup  
#  
#<FilesMatch "\.php$">  
#  SetHandler application/x-httpd-php-cgi  
#</FilesMatch>  
#<IfModule actions_module>  
#  Action application/x-httpd-php-cgi "/php-cgi/php-cgi.exe"  
#</IfModule>
```

```
<IfModule php5_module>  
  PHPINIDir "/xampp/php"  
</IfModule>
```

```
<IfModule mime_module>  
  AddType text/html .php .phps  
</IfModule>
```

```
ScriptAlias /php-cgi/ "/xampp/php/"  
<Directory "/xampp/php">  
  AllowOverride None  
  Options None  
  Require all denied
```

```
<Files "php-cgi.exe">
    Require all granted
</Files>
</Directory>

<Directory "/xampp/cgi-bin">
    <FilesMatch "\.php$">
        SetHandler cgi-script
    </FilesMatch>
    <FilesMatch "\.phps$">
        SetHandler None
    </FilesMatch>
</Directory>

<Directory "/xampp/htdocs/xampp">
    <IfModule php5_module>
        <Files "status.php">
            php_admin_flag safe_mode off
        </Files>
    </IfModule>
    AllowOverride AuthConfig
</Directory>

<IfModule alias_module>
    Alias /security "/xampp/security/htdocs/"
```

```
<Directory "/xampp/security/htdocs">
  <IfModule php5_module>
    <Files "xamppsecurity.php">
      php_admin_flag safe_mode off
    </Files>
  </IfModule>
  AllowOverride AuthConfig
  Require all granted
</Directory>
```

```
Alias /licenses "/xampp/licenses/"
```

```
<Directory "/xampp/licenses">
  Options +Indexes
  <IfModule autoindex_color_module>
    DirectoryIndexTextColor "#000000"
    DirectoryIndexBGColor "#f8e8a0"
    DirectoryIndexLinkColor "#bb3902"
    DirectoryIndexVLinkColor "#bb3902"
    DirectoryIndexALinkColor "#bb3902"
  </IfModule>
  Require all granted
</Directory>
```

```
Alias /phpmyadmin "/xampp/phpMyAdmin/"
```

```
<Directory "/xampp/phpMyAdmin">
```

```
    AllowOverride AuthConfig
    Require all granted
</Directory>

Alias /webalizer "/xampp/webalizer/"
<Directory "/xampp/webalizer">
    <IfModule php5_module>
        <Files "webalizer.php">
            php_admin_flag safe_mode off
        </Files>
    </IfModule>
    AllowOverride AuthConfig
    Require all granted
</Directory>
</IfModule>

#
# New XAMPP security concept
#
<LocationMatch
"^(?i:(?:xampp|security|licenses|phpmyadmin|webalizer|server-status|server-info))">
    Order deny,allow
    Deny from all
    Allow from ::1 127.0.0.0/8 \
        fc00::/7 10.0.0.0/8 172.16.0.0/12 192.168.0.0/16 \
```

fe80::/10 169.254.0.0/16

ErrorDocument 403 /error/XAMPP_FORBIDDEN.html.var

</LocationMatch>