



# VIXOL GEAR OIL 85W-140 GL-5

## V4007-00

**VIXOL GEAR OIL 85W-140 GL-5** is a heavy extreme pressure multi grade differential and gearbox lubricant offering superior wear protection and good low temperature characteristics designed to give maximum protection to gearboxes and differentials in heavy loads and shock-loading.

## SUMMARY OF BENEFITS

- Protects differentials, final drives and axles from heavy loads and shock loading
- High temperature stability and oxidation resistance
- Superior wear protection
- Recommended for heavy duty applications like 4WDs, trucks, trailers, farm machinery, construction equipment and other heavy applications.

## SPECIFICATIONS

- API GL-5
- MT-1
- CHRYSLER MS-9020

## TECHNICAL DATA

CHARACTERISTICS	VIXOL GEAR OIL 85W-140 GL-5
Specific gravity at 15 C	0.8960
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	380
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	28.0
Viscosity index	102

- Safety Data Sheet for this product can be obtained by visiting Vixol Australia Pty Ltd Website [www.vixol.com.au](http://www.vixol.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

Vixol Australia Pty Ltd  
7 Foden Avenue Campbellfield Vic 3061 Australia  
Tel: +61 03 9333 7701 Local sales: 1300 0894684  
Email: [sales@vixol.com.au](mailto:sales@vixol.com.au) [www.vixol.com.au](http://www.vixol.com.au)