



## REMOTE SPOT WATER DETECTOR

WLDR Series

The WLDR series incorporates:

- Single-point standalone detection
- Fail-safe circuitry
- One Relay standard or Two Relay option
- NO/NC form C, relay output
- Weatherproof enclosure

### PRODUCT HIGHLIGHTS

- Monitors variety of liquids
- Alarm on liquid detection, power failure, or internal failure
- Remote sensor terminal block with conductive pins
- Extension cable available with various lengths
- Tri color LED for operation status

### SPECIFICATIONS

| SPECIFICATIONS        |   |
|-----------------------|---|
| POWER SUPPLY          | 12 - 27 Vac/dc  |
| SUPPLY CURRENT        | 125 mA max @ 24 Vac   |
| OPERATING TEMPERATURE | 0 to 50°C (32 to 122°F)                                     |
| ENCLOSURE             | PC with hinged lid and gasket, IP65                         |
| DIMENSIONS            | 133mm L x 80mm W x 64-90mm H (5.3" x 3.1564" x 2.5" - 3.5") |
| ALARM OUTPUT(S)       | Form C relay, rated 1 Amps @ 125 Vac/60Vdc (resistive load) |
| APPROVALS             | CE, RoHS  |
| COUNTRY OF ORIGIN     | Canada  |
|                       |   |
|                       |   |
|                       |   |