

**BTX / SKYCO Product Specifications
Roman Shade Systems**

Motorized B9 Roman System – BTX / SKYCO 45QE AC RF

1

Part 1 – General

1.01 Summary:

Scope of work is to provide roman shades that are operated by BTX / SKYCO motorized lift system along with accessories, attachment hardware, and equipment necessary to complete satisfactory installation.

1.02 Turnkey responsibility for motorized Roman Shade systems:

- A. To ensure control of responsibility for satisfactory performance and installation of the motorized roman shade systems, the design, engineering and installation shall be assigned to a single manufacturer and his authorized dealer/installer.
- B. The base building contractor (main contractor) shall provide and coordinate the following items with the window shade contractor/installer for all window shade systems.
 - 1. Shade pockets recessed into ceiling
 - 2. Power wiring
 - 3. Wire conduits as required
 - 4. Duplex outlets and J-boxes

1.03 Submittals

- A. Manufacturing literature to describe assembly, materials, installation instructions, and specific data. Include any pertinent wiring diagrams.
- B. Shop drawings are to include, but are not limited to, all components, fasteners, and installation methods.
- C. Window Systems are custom-built based on measurements taken in the field.

1.04 Quality Assurance:

- A. Manufacturer's Qualification
 - 1. BTX / SKYCO is the original manufacturer of a unique line of motorized headrail systems, electronic shading devices and controls.
- B. A qualified installer or sub-contractor shall perform installation.
- C. Installation shall conform to Local and National Building Code and any applicable local standards.
- D. Sample system may be provided upon Architect's request and BTX / SKYCO authorization.

**BTX / SKYCO Product Specifications
Roman Shade Systems**

Motorized B9 Roman System – BTX / SKYCO 45QE AC RF

2

1.05 Delivery, Storage, and Handling

- A. Systems shall be delivered to the site in original manufacturer's containers.
- B. Containers shall be uniquely labeled to identify the corresponding window openings and locations.
- C. All materials shall be stored in a dry, secure place protected from weather, water and heat, surface contaminants, construction traffic and all other potential damage.

1.06 Warranty

- A. BTX / SKYCO shall provide five (5) year warranty from the date of shipment on all shade motors. All operating control and electronic accessory components shall carry a one (1) year limited warranty against defects in materials and workmanship.

Part 2 – Products

2.01 Manufacturer:

- A. BTX Window Automation
10763 Sanden Drive
Dallas, TX 75238 USA
(800) 422-8839
- B. Skyco Shading Systems
3411 W Fordham Ave
Santa Ana, CA 92704
(800) 777-5926

2.02 Components:

- A. BTX / SKYCO AC 45QE RF tubular motors shall be asynchronous 120V/60Hz AC rated at 130 watts developing 6 NM torque at 33rpm capable of lifting 50 lbs. Motors shall have a fully encapsulated shock resistant motor coil and be moisture resistant and fire resistant. All motors are UL recognized and equipped with a mechanical brake. Motors shall have a thermal protector for automatic switch-off to prevent overheating. Motor includes internal electronic limit switches. Limit switches shall be easily adjustable in either direction by means of BTX compatible control device. Motor shall have built-in electronic control board for operation of 433 MHz RF remote control or via dry contact direct input.
- B. Tube shall be 50mm extruded aluminum.

BTX / SKYCO Product Specifications Roman Shade Systems

Motorized B9 Roman System – BTX / SKYCO 45QE AC RF

3

- C. Motor bracket shall be either drop-in with slide bearing for adjustability, or fixed, flush-mount for motor head to snap in. Snap-in component shall be made of cast aluminum. Drop-in bracket shall be made of powder-coated steel and allow for adjustment for ease of installation. Idler bracket shall be drop-in, powder-coated steel with adjustable slide bearing for ease of installation.
- D. Idler insert shall match the tube shape internally and is provided with a round steel, retractable spring-loaded shaft for mounting in the bracket. Inserts are made from injection molded plastic.
- E. Fabric Clip or Tape Reel is used and for fabric attachment.
- F. Adaptor Set allows the motor to drive the tube and shall be manufactured from injection molded plastic.

2.03 Controls:

- A. The switching device to activate the system shall be either an RF remote control wall-switch, or via dry contact input. Systems can be controlled individually or as a group. Motors can be integrated into building automation system utilizing BTX / SKYCO wireless RS232 Interface (SmartConnect) or via dry contact input.

Part 3 – Execution

3.01 Inspection and Preparation:

- A. Qualified installer shall be responsible for window measurements prior to installation, installation conditions, and preparation of all mounting surfaces.
- B. The power supplied shall be 110V AC three conductor to the primary switch (hardwire switch, radio, or BTX / SKYCO automated controls). Wiring between primary switch and selected control units shall be in accordance with manufacturer's wiring schematics and specifications. All on site wiring shall be provided by owner.

3.02 Installation:

- A. System installation shall be in accordance with BTX / SKYCO mounting instructions.

3.03 Maintenance:

- A. Roman Shade system components should not require routine maintenance under normal operating conditions.

**BTX / SKYCO Product Specifications
Roman Shade Systems**

Motorized B9 Roman System – BTX / SKYCO 45QE AC RF

4

- 3.01 B. For fabric care refer to fabric manufacturer's care and use directions.