

	<table><tr><td>Star topology is a topology in which all devices are connected to a central hub.</td><td>Bus topology is a topology where each device is connected to a single cable which is known as the backbone.</td></tr><tr><td>In star topology, if the central hub fails then the whole network fails.</td><td>In a Bus topology, the failure of the network cable will cause the whole network to fail.</td></tr></table>	Star topology is a topology in which all devices are connected to a central hub.	Bus topology is a topology where each device is connected to a single cable which is known as the backbone.	In star topology, if the central hub fails then the whole network fails.	In a Bus topology, the failure of the network cable will cause the whole network to fail.			
Star topology is a topology in which all devices are connected to a central hub.	Bus topology is a topology where each device is connected to a single cable which is known as the backbone.							
In star topology, if the central hub fails then the whole network fails.	In a Bus topology, the failure of the network cable will cause the whole network to fail.							
21.	a) '## 3202 noitanimaxE TEEN##' b) dict_items([('sname', 'Aman'), ('age', 27), ('address', 'Delhi')])	1+1						
22.	Row in a Table is a tuple and column is an attribute.	1 mark for each correct definition and 1 mark for an example of each.						
23.	Top-level domain (TLD) refers to the last segment of a domain name, or the part that follows immediately after the "dot" symbol. .com — Commercial businesses. .org — Organizations (generally charitable).	1 mark for stating correct application area of each TDL.						
24.	Maximum values for FROM=3, TO=4 OUTPUT:ii) 30#40#50# Or 250 300	$\frac{1}{2}+\frac{1}{2}+1$ Or 1+1						
25.	<table><tr><th>CHAR</th><th>VARCHAR</th></tr><tr><td>CHAR datatype is used to store character strings of fixed length</td><td>VARCHAR datatype is used to store character strings of variable length</td></tr><tr><td>In CHAR If the length of the string is less than set or fixed-length then it is padded with extra memory space.</td><td>In VARCHAR If the length of the string is less than the set or fixed-length then it will store as it is without padded with extra memory spaces.</td></tr></table> OR a) Degree=5, cardinality=3 b) roll must be primary key because all values are unique and not null.	CHAR	VARCHAR	CHAR datatype is used to store character strings of fixed length	VARCHAR datatype is used to store character strings of variable length	In CHAR If the length of the string is less than set or fixed-length then it is padded with extra memory space.	In VARCHAR If the length of the string is less than the set or fixed-length then it will store as it is without padded with extra memory spaces.	1+1 Or $\frac{1}{2}+\frac{1}{2}+\frac{1}{2}+\frac{1}{2}$
CHAR	VARCHAR							
CHAR datatype is used to store character strings of fixed length	VARCHAR datatype is used to store character strings of variable length							
In CHAR If the length of the string is less than set or fixed-length then it is padded with extra memory space.	In VARCHAR If the length of the string is less than the set or fixed-length then it will store as it is without padded with extra memory spaces.							
26.	Create database MYEARTH; Use MYEARTH; Create Table CITY (CITYCODE CHAR(5) PRIMARY KEY, CITYNAME CHAR(30), SIZE INT(3), AVGTEMP INT, POLLUTIONRATE INT, POPULATION INT);	$\frac{1}{2}+\frac{1}{2}+2$						
27.	def RECORD(): f1=open('Myfile.txt','r') str1=f1.read() print(len(str1)) RECORD() OR def CLRECORD(): f1=open('Myfile.txt','r') l1=f1.readlines() print(len(l1))	1 mark for function definition+1 mark for function body +1 mark for function calling						

	CLRECORD()	
28.	a) SHOW TABLES; b) ALTER TABLE <TNAME> ADD COLUMN <CNAME> DATATYPE; c) ALTER TABLE <TNAME> DROP COLUMN <CNAME>	1+1+1
29.	def convert(l1): for i in range(0,len(l1)): if l1[i]%2==0: l1[i]=l1[i]//2 else: l1[i]=l1[i]*2 print(l1) l1=[3,4,5,16,9] convert(l1)	½ mark for function definition+1 mark for correct for loop +1 mark for correct logic +½mark for function calling
30.	def PUSH_IN(L): L1=[] for i in L: if i%3==0: L1.append(i) If len(L1)==0: print("Empty Stack") else: print(L1) L=[4,6,9,12,5] PUSH_IN(L) Or def POP(Arr): if(len(Arr)==0): print("Underflow , No element in stack") return else: return Arr.pop() A=[] # Implemented stack POP(A)	½ mark for function definition+1 mark for correct for loop +1 mark for correct logic +½mark for function calling Or ½mark for function definition+1 mark for checking underflow condition +1 mark for returning delete value from stack +½mark for function calling
31.	(i) star (ii)Broadband (iii)Switch/Hub (iv)Radio Wave (v) Block B1	1+1+1+1+1

32.	<p>a) 5#8#5#4#</p> <p>b) Selection : This operation chooses the subset of tuples from the relation that satisfies the given condition mentioned in the syntax of selection.</p> <p>Projection : This operation selects certain required attributes, while discarding other attributes.</p> <p>OR</p> <p>a) 300 @ 200</p> <p>300 @ 100 120 @ 100 300 @ 120</p> <p>b) An attribute is a descriptive property which is owned by each entity of an entity set while a domain is the set of values allowed for an attribute. Thus, this is the main difference between Attribute and Domain. Attributes help to describe an entity while domains help to define the range of values that suit a specific attribute. Hence, this is another difference between Attribute and Domain. Example Name and age are two examples of attributes. Moreover, the name has to be alphabetic, and age has to be positive integer to explain the domain.</p>	<p>a) 2 marks for correct output. b) 1 mark for correct definition of selection + 1 mark for correct definition of projection + 1 mark for appropriate examples.</p> <p>a) 2 marks for correct output. b) 1 mark for correct definition of selection + 1 mark for correct definition of projection + 1 mark for appropriate examples.</p>
33.	<p>“Comma Separated Values”, Text editor and spreadsheet program.</p> <p>Program:</p> <pre>import csv def ADDR(): fout=open("record.csv","a",newline="\n") wr=csv.writer(fout) rollno=int(input("Enter rollno :: ")) name=input("Enter name :: ") mobile=int(input("Enter mobile number :: ")) lst=[rollno,name,mobile] wr.writerow(lst) fout.close() def COUNTR(): fin=open("record.csv","r",newline="\n") data=csv.reader(fin) d=list(data) print(len(d)) fin.close() ADDR() COUNTR() Or Difference between text file and csv file: (Any one difference may be given) Text file:</pre>	<p>1+1</p> <p>1½ for correct definition of ADDR + 1½ for correct definition of COUNTR</p> <p>1</p>

	<ul style="list-style-type: none"> · Extension is .txt · human readable in text editor · Stores data in the form of characters <p>CSV file</p> <ul style="list-style-type: none"> · Extension is .csv · Human readable in text editor and spreadsheet both · Stores data like a text file. <p>Program:</p> <pre>import csv def add(): fout=open("abc.csv","a",newline='\n') wr=csv.writer(fout) fid=int(input("Enter Furniture Id :: ")) fname=input("Enter Furniture name :: ") fprice=int(input("Enter price :: ")) FD=[fid,fname,fprice] wr.writerow(FD) fout.close() def search(): fin=open("abc.csv","r",newline='\n') data=csv.reader(fin) found=False print("The Details are") for i in data: if int(i[2])>5000: found=True print(i[0],i[1],i[2]) if found==False: print("Record not found")</pre>	<p>2marks for correct definition of add() +2 marks for correct definition of search()</p>
34.	<p>a) Alter table Teacher add primary key T_ID; b) Alter table Teacher add column P_ID int(1); c) Alter table Teacher add constraint (c1_01) foreign key (P_ID) references Teacher(P_ID); or Alter table Posting modify column Place varchar(10);</p>	1+1+2
35.	<p>Statement1:import pickle Statement2:fout=open('temp.dat', 'wb') Statement 3: pickle.load(fin) Statement 4: pickle.dump(rec,fout)</p>	1+1+1+1

- **ALL ANSWERS IN MARKING SCHEME ARE SUGGESTIVE ANY OTHER CORRECT ANSWER MUST BE AWARDED APPROPRIATE MARKS.**