

DEBLOCK SHOCK

HIGH PERFORMANCE “HEAVY DUTY” PENETRATION OIL + CERFLON®

DESCRIPTION

Powerful spray to free non-destructively rusted, corroded and seized parts. The shock freezing effect (< -43 °C) causes a thermo shock and microscopic cracks in the layer of rust. This allows the lubricating ingredients to penetrate instantly and deep into the seized parts. The Cerflon® particles in the product assure low friction and improve the lubricating action when loosening bolts and nuts.

BASIC BENEFITS

- Makes easier and faster disassembly of heavily rusted parts.
- Lubricates and reduces friction and wear in moving parts.
- Waterproofs and displaces moisture.
- Universal application.
- Free of silicones.

PROPERTIES

- Outstanding penetration.
- Released parts remain lubricated and protected from rust and corrosion.
- Avoids electrical dysfunctions.
- Dissolves dirt and rust.
- Degreases water displacing.
- Seals ignition systems.

APPLICATION

The outstanding and universal properties of DEBLOCK SHOCK assure a wide range of professional and DIY applications. The product is applicable in industry, workshop, farming, marine, motorcycles, bicycles, and more.

Spray on at a distance of about 10cm for at least 5 seconds. Leave to operate for a few minutes. Repeat if necessary. Do not spray empty the valve. In general, DEBLOCK SHOCK does not need to be removed for further treatment (except painting). Shake well before use.

TYPICALS

Form:	Aerosol
pH-value:	Not determined
Melting point/melting range:	Undetermined
Boiling point/boiling range:	-44° C
Flash point:	-97° C
Flammability (solid, gaseous):	Not applicable
Ignition temperature:	> 200° C
Decomposition temperature:	Not determined
Vapour pressure at 20° C:	8300 hPa
Density at 20° C:	0.598 g/cm³
Solubility in/Miscibility with water:	Not miscible or difficult to mix

PACKAGING

500 ml aerosol (12 x 500 ml carton)