




LCD Bar Screen - Model A1

28" Wall Mounted

December 7th, 2023



◉ CMS & DMS

◉ Multi-Language

◉ 2.4G WIFI

Guangdong HUSHIDA Electronic Technology Co.,Ltd.

Product Features

- Standard Android keyboard, optional third-party input method
- Supports up to 1080P decoding and various LVDS signal displays; HDMI supports up to 1920*1080P/60Hz
- Built-in real-time clock power supply battery, supports scheduled power on and off
- Support PAL/NTSC/SECAM, 480i/576i video formats
- Supports external serial device modules (extended sensors or one-dimensional codes, two-dimensional code scanners, printers, card reader modules, etc.)
- TF card expansion, maximum support 64GB
- OSD language Chinese, English, can support multiple languages
- Support Ethernet 10/100Mbps, support 2.4G WIFI, 802.11b/g/n protocol (need to match antenna)
- Perfectly supports industry mainstream publishing software and industry application software, ready to install and use
- Supports browsing various image formats such as JPG, BMP, PNG, GIF and supports horizontal and vertical screen switching of videos, pictures and text, and can be rotated at 90°, 180°, and 270°
- Port configuration: USB OTG, USB HOST, RJ45, Micro SD, LINE OUT, HDMI OU, DC2.0 IN
- Support OTA remote USB, TF, PC and network upgrade

Specifications

Display

Size	28 inch
Screen Type	LCD A Grade
Backlight Type	E-LED
Aspect Ratio	16:9
Responsive Time	///
Display Area	698.4(H)×130.95(V)mm
Resolution	1920(H)×360(V)
Refresh Frequency	60Hz
Chromaticity	0.167b(8 bit)
Contrast(Typ)	1200:1
Viewing Angle	178°(H/V)
Screen Brightness(Typ)	500cd/m ²
Life Time	≥30000 hours

Operation System

System Version	Android 7.1
Ram	1G DDR3
Rom	8G
CPU	Nano 4 Cores A40i ARM Cortex A7 1.2GHz
Media Format	wmv, avi, flv, rm, rmvb, mpeg, ts, mp4
Interface	USB OTG * 1, USB HOST * 1, RJ45, Micro SD, Line Out, HDMI OUT, DC 12V in * 1
Network	Supports 10/100M, 2.4G WIFI, 802.11 b/g/n, External Antenna

Electrical

Power Input	AC 100-240V~50/60Hz
Max power consumption	45W

Physical Parameters

Machine Size (l × w × t)	729.7×161.5×56.5mm
--------------------------	--------------------

Packaging size (l * w * h)	605*130*400mm
VESA hole (l * w)	100*100mm
Wall mounting screw	4*8mm
Net Weight	4.2kg
Gross Weight	5.1kg

Accessories

Power Cable	X1
Wall Mount Bracket	X1

Enviroment

Working Temperature	0°C~50°C
Working Humidity	10%~90%RH
Stocking Temperature	-20°C~60°C
Stocking Humidity	10%~90%RH
Working Altitude	Below 5000meters

Contact HUSHIDA Team

Email: support@hushidaglobal.com

WhatsApp: +1 909 905 7781

Phone: +86 18576560374

Website: <https://hushidaglobal.com>

Retail Website: <https://www.hushidasmart.com>

“互动视界，智达未来”

**“Interactive Vision, Intelligent
Future”**

