

RBR-48 Industrial Digital Printer



SPECIFICATIONS:-

Machine model	XC11-48
Printer Head	48 pcs ricoh print head (Arrangement 6×8)
Print Thickness	2-30 mm range is adjustable
Max. Print width	1900 mm / 2700 mm / 3200 mm
Max. Fabric width	1950 mm / 2750 mm / 3250 mm
Production mode	1000 m ² /h (1 pass) 600 m ² /h (2 pass) 400 m ² /h (3 pass)
Image type	JPEG/TIFF/BMP file format, RGB/CMYK color mode
Ink Color	Twelve color available: KCMY LC LM R GRY O B G K
Types of ink	Reactive/Disperse/pigment/Acid/reducing ink
RIP Software	Neostampa/Wasatch/Texprint
Transfer Medium	Continuous conveyor belt, automatic winding
Head Cleaning	Auto head cleaning & auto scraping device
Power	Power ≤ 30kW (No oven included, the oven is separately equipped)
Power supply	380vac plus or minus 10%, three phase five wire
Compressed air	Air flow 0.3m ³ /min, air pressure 0.8mpa
Working environment	Temperature 18-28 degrees, humidity 50%-70%
Width	1900 mm / 2700 mm / 3200 mm
Overall dimensions	4800mm(L)×3900mm(W)×2250mm(H)/5600mm(L)×3900mm(W)×2250mm(H)/ 6100mm(L)×3900mm(W)×2250mm(H)/
Weight	5000 KG / 6000 KG / 7800 KG

