



SYNGEAR 70W-75 GL-4+ V9003-00

70W75 GL-4+ FULL SYNTHETIC is a low viscosity, full synthetic manual gearbox lubricant containing sophisticated extreme pressure additives and base oils. It is designed to give maximum protection to gearboxes and transaxles while providing easy shifting and enhanced fuel economy. Designed for 5 and 6 speed manual gearboxes.

SUMMARY OF BENEFITS

- Smooth shift and enhanced fuel economy
- Enhanced oxidation stability
- Full Synthetic for longer life
- Superior wear protection
- Excellent cold temperature flowability
- Outstanding wear protection

SPECIFICATIONS

- MTF BOT 338
- API GL-4+
- ZF TE-ML 11 (manual)
- TREMEC T-56

TECHNICAL DATA

CHARACTERISTICS	SYNGEAR 70W75 GL-4+
Specific gravity at 15 C	0.859
Kinematic viscosity at 40 C, mm ² /s (cSt)	38
Kinematic viscosity at 100 C, mm ² /s (cSt)	7.5
Viscosity index	177

- Safety Data Sheet for this product can be obtained by visiting Vixol Australia Pty Ltd Website www.vixol.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

Vixol Australia Pty Ltd
7 Foden Avenue Campbellfield Vic 3061 Australia
Tel: +61 03 9333 7701 Local sales: 1300 0894684
Email: sales@vixol.com.au www.vixol.com.au