

Product Data Sheet

FOXAROOF (OD-304)

Roof Paint - Exterior

DESCRIPTION

High quality water based roof paint based on acrylic copolymer .

PRINCIPLE CHARACTERISTIC

Good adhesion
Weathering resistance
High durability.
Special formulation for anti fungus.. Not fading and smelly.
Lead and mercury free.

RECOMMENDED USE

Specially designed for protection and decoration of old and new roofs including asbestos and cement.

SYSTEM SPECIFICATION

Metal
:
Finish
(2-3 coat) : FOXAROOF : OD-304
Asbestos
:
Prime
r (1 coat) : FOXASEALER WB : OD-101
Finish
(2-3 coat) : FOXAROOF : OD-304

SPECIFICATION DATA AT 20°C

Gloss	Semi gloss
Colours	See colours card
Specific gravity	1.10 ± 0.1 kg/litre
Solids by volume	40±2%
Coverage theoretical	Varies considerably according to the roughness and porosity of the surface 12 -14 m ² / litre (on smooth surfaces of average porosity)
Drying time	Touch dry

:
10
mi
nu
te
s
(d

ep
en
d
on
:
2
ho
ur
s

temperature & humidity)

Hard dry

Painti
ng
interv
al
Shelf
life

Min 1 hours

12 month (cool and dry place)

SURFACE PREPARATION

Surface must be clean, dry, free from all defective or poorly adhering material, dirty, grease, wax, etc.
Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and dusted off.
Steel surface should be manually prepared by power tool or hand tool Cleaning.
For optimum performance new galvanised and aluminium surfaces should be cleaned and degreased, then pre-treated with an appropriate pre-treatment primer to ensure good adhesion.

INSTRUCTION FOR USE

Stir well before use, to achieve uniformity of colour and good homogeneity. It is recommended to apply two (2) layers, in order to get better result.
Clean all equipment with clean water immediately after use.

RECOMMENDED THINNING

Method of application	Air Spray	Roller/Brush
Thinner No	Water	Water
Thinning	10 %	10 %
Nozzle orifice	1.5 - 2 mm	-
Nozzle pressure	3-4 bar /43-57 psi	-

SAFETY PRECAUTION

Keep container tightly close and keep out from the children
Keep away from food, drink, and animal feeding stuff.
Care must be taken when transporting paint. Keep container in a secure up-right position.
Avoid contact with skin and eyes.
Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.
Ensure that there is adequate ventilation in the area where the product is being applied.
Do not breathe the vapour or spray.
Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulation.

HEALTH AND SAFETY

For detailed information on the health and safety hazards and precaution for use of this product, please see the **MATERIAL SAFETY DATA SHEET**.

PACKING SIZE AND STORAGE

Packing size	5 and 20 litres.
Storage	The product must be stored in accordance with national regulation. Preferred storage conditions are to keep the containers in the dry space provided with adequate ventilation. The container should be sealed tightly.