

PRO-C2 5w30

HIGH PERFORMANCE FULL SYNTHETIC ENGINE OIL

DESCRIPTION

Synthetic high performance engine oil produced with special selected base oils with a high viscosity index and a well balanced choice of advanced additives. Provides optimum protection and extended engine life and reliability. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics. This motor oil also contributes to the extension of the lifetime of particle filters.

PROPERTIES

- Fuel economy.
- Very stable viscosity index.
- Superior resistance against shearing.
- Fast cold start.
- Safe lubrication film at extreme temperatures.
- Flexible and extended oil drain intervals.
- High protection against wear.
- Mid SAPS / DPF- compatible.

APPLICATION

Specifically recommended for Peugeot and Citroën gasoline and diesel engines equipped with diesel particulate filters. Most Japanese OEM's, including Toyota, Honda, Subaru and Nissan.

TYPICALS

| | |
|-------------------|--------------------------|
| Density at 15 °C | 0,853 kg/l |
| Viscosity -30 °C | 5550 mPa.s |
| Viscosity 40 °C | 61,70 mm ² /s |
| Viscosity 100 °C | 10,50 mm ² /s |
| Viscosity index | 160 |
| Flash point COC | 236 °C |
| Pour point | -45 °C |
| Total base number | 7,7 mgKOH/g |
| Sulphated ash | 0,76 % |

SPECIFICATIONS

ACEA C2
API SN/CF
FIAT 9.55535-S1
PSA B71 2290
Renault Rn 0700

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
20 L can
60 L drum
208 L drum

