

型号Model	Mpa	BD-7.5A	BD-7.5TA (带桶)	BD-10A	BD-10TA (带桶)	BD-15A	BD-20A	BD-30A	BD-40A	BD-50A	BD-60A	BD-75A	BD-100A	BD-125A	BD-150A	BD-175A	BD-200A	BD-250A	BD-300A	BD-350A	
排气量/排气压力 (M³/min) Free Air Delivery / Discharge Pressure	0.7	1.0		1.35		1.8	2.5	3.8	5.2	6.5	8.0	10.5	14.1	16.0	20.5	24.1	28.3	32.0	38.5	43.8	
	0.8	0.95		1.2		1.6	2.3	3.65	5.0	6.3	7.5	9.8	12.8	15.0	19.0	22.9	27.0	30.5	35.8	41.4	
	1.0	0.85		1.0		1.3	2.0	3.1	4.3	5.5	7.0	8.6	11.6	13.6	17.2	20.5	24.5	28.0	32.2	37.8	
	1.25	0.7		0.8		1.0	1.7	2.7	3.8	4.9	6.0	7.6	10.0	12.2	14.8	16.8	20.5	24.0	28.5	33.0	
环境温度 Ambient Temp	℃					-5 ~ +40℃															
冷却方式 Cooling Model		风冷或水冷 Air or Water-Cooling																			
排气温度 Discharge Temperature	℃	≤环境温度+10℃≤Environment Temp+10℃ (风冷型Air-Cooling) < 40℃ (水冷型Water-Cooling)																			
润滑油量 Lubricant	升/L	6				9		18	30		50		65		90		112		120		
噪音 Noise	dB(A)	62±2				64±2			65±2		67±2		68±2		70±2		73±2		75±2		
驱动方式 Drivin way		皮带传动 Belt drive				直联传动 Direct drive															
电源 Electricity (V/ph/Hz)		220V/380V/415/3ph/50Hz/60Hz																			
功率 Power	KW	5.5		7.5		11	15	22	30	37	45	55	75	90	110	132	160	185	220	250	
启动方式 Straing Method		Y-△启动 Y-△Starter or 选装变频启动 (Optional Starter)																			
外型尺寸 Dimension	长/风冷 Length	mm	960	1750	960	1180	1100		1250		1500		1750		1750		2200		3190		3384
	宽/风冷 Width	mm	580	1150	580	500	710		950		1000		1150		1150		1500		1890		1894
	高/风冷 Height	mm	770	1500	770	1300	1020		1120		1350		1500		1500		1720		1740		1900
重量 Weight	KG	178	210	178	220	286	327	500		680		1038		1200	1500	2000	2500	3900	4200	4600	5000
出口管径 Air Outlet Pipe Diameter	inch	ZG1/2"	ZG1"	ZG1/2"	ZG1"	ZG1"		ZG1¼"		ZG1½"		ZG2"			DN65		DN80		DN100		