

LCD Bar Screen - Model A1 49.5" Wall Mounted

December 7th, 2023



CMS & DMS

Multi-Language

●2.4G WIFI

Guangdong HUSHIDA Electronic Technology Co.,Ltd.

Product Features

- Standard Android keyboard, optional third-party input method
- Supports up to 1080P decoding and various LVDS signal displays; HDMI supports up to 1920*1080P/60Hz
- Built-in real-time clock power supply battery, supports scheduled power on and off
- Support PAL/NTSC/SECAM, 480i/576i video formats
- Supports external serial device modules (extended sensors or one-dimensional codes, two-dimensional code scanners, printers, card reader modules, etc.)
- TF card expansion, maximum support 64GB
- OSD language Chinese, English, can support multiple languages
- Support Ethernet 10/100Mbps, support 2.4G WIFI, 802.11b/g/n protocol (need to match antenna)
- Perfectly supports industry mainstream publishing software and industry application software, ready to install and use
- Supports browsing various image formats such as JPG, BMP, PNG, GIF and supports horizontal and vertical screen switching of videos, pictures and text, and can be rotated at 90°, 180°, and 270°
- Port configuration: USB OTG, USB HOST, RJ45, Micro SD, LINE OUT, HDMI OU,
 DC2.0 IN
- Support OTA remote USB, TF, PC and network upgrade

Specifications

Display

HUSHID	WSHIDA ZHUZ
Size	49.5 inch
Screen Type	LCD A Grade
Backlight Type	E-LED JANUA
Aspect Ratio	16:9
Responsive Time	III JSHIDA
Display Area	1209(H)×340(V)mm
Resolution	1960(H)×545(V)
Refresh Frequency	60Hz
Chromaticity	0.167b(8 bit)
Contrast(Typ)	1200:1
Viewing Angle	178°(H/V)
Screen Brightness(Typ)	500cd/m²
Life Time	≥30000 hours
LHUSHIDA	ZHUSHIDA ZHUSHIDA

Operation System

SA CHUS	
System Version Android 7.1	
Ram 1G DDR3	
Rom 8G	
CPU Nano 4 Cores A40i ARM Cortex A7 1.2GH	z
Media Format wmv, avi, flv, rm, rmvb, mpeg, ts, mp4	
Interface USB OTG * 1, USB HOST * 1, RJ45, Micro SI Out, HDMI OUT, DC 2.0 in * 1	D, Line
Network Supports 10/100M, 2.4G WIFI, 802.11 b/g/r External Antenna	n,

Electrical

Liectrical			
Power Input	AC 100-24	40V~50/60Hz	
Max power consump	tion 110W	, ISHIDA	

3 HUSHIDA Physical Parameters

Å	Physical Parame	FHR2HIDY PHR2	
AQL	Machine Size (I × w × t)	1248.2×378×59mm	HOP.
SHILL	Packaging size (l × w × h)	1327*165*452mm	JUSHIDA
CHIDA	Net Weight	14.8kg	7
PHOP	IIDA ZHUSHI	IDA SAIDA	7 HAZH

Gross Weight	17.2kg	, MUSHIDA
7 HOS.	å Zhushid.	- HUSHI

& HUSHIDA

Accessories

Accessori	es		
Power Cable	X1	Pur	
HISHIDA	5 HO	THUSHIE	
ZHO CÂ			

Enviroment

	Enviroment		
AIDA	Working Temperature	0°C~50°C	A
	Working Humidity	10%~90%RH	HUSHIL
HISHIDA	Stocking Temperature	-20°C~60°C	-14
AC	Stocking Humidity	10%~90%RH	PHARM
, HUSHI	Working Altitude	Below 5000meters	
5	JIDA SHI	JSN. SHIDA	7H

Contact HUSHIDA Team

Email: support@hushidaglobal.com

WhatsApp: +1 909 905 7781

Phone: +86 18576560374

Website: https://hushidaglobal.com

Retail Website: https://www.hushidasmart.com

"互动视界,智达未来"

"Interactive Vision, Intelligent

Future"

