

INSTALL INSTRUCTIONS

2014-2024 Honda Grom Engine Cage



What's Included:

- Engine Cage
- T bar Lower engine mount
- Pucks
- Crossbar
- Hardware

Special Notes:

- **A helping hand goes along way**
- **You will need a jack to support engine**
- **Some aftermarket exhaust will not work with this cage**

Instructions:

- 1. Place bike on the kick stand or in wheel chock**
- 2. Support engine with jack and remove the rear top bolt (keep this, you will reuse)**
- 3. Place one side of the cage up to the bike and reinstall bolt thru cage into the rear top motor mount**
- 4. Place opposing side cage onto bolt**
- 5. Put the nut into the socket (use a piece of paper to wedge nut into socket so it wont fall out and have your neighbors calling for a exorcism due to the screaming) and install nut onto bolt but DO NOT TIGHTEN YET**
- 6. Remove jack**
- 7. Install lower T bar onto engine using the supplied M8 Bolts, DO NOT TIGHTEN YET**
- 8. Using the supplied $\frac{3}{8}$ cap screws start them into T bar thru the lower cage mounts DO NOT TIGHTEN YET**
- 9. Install Crossbar under the air box to the top cage mounts DO NOT TIGHTEN YET**
- 10. Tighten T bar to engine**
- 11. Tighten Rear engine bolt**
- 12. Tighten crossbar**
- 13. Tighten lower mount bolts**
- 14. Install Pucks and set screws**
- 15. Take Pictures, It'll never look this nice again ;)**