

EVERPURE® SEN FILTER CARTRIDGE

Endurance retrofit kits and Endurance
SC manifolds

INSTALLATION TIPS OPERATION TIPS

REPLACEMENT CARTRIDGE FOR

EVERPURE ENDURANCE® HIGH FLOW

SYSTEMS SEN Replacement Cartridge 1 PK: EV9692-65



APPLICATIONS

Multiple Equipment and Combination
Applications

High Volume Installations

FEATURES • BENEFITS

Increased capacity for extended reduction
of chemical and mechanical contaminants

Sanitary cartridge replacement is simple,
quick and clean; internal filter parts are
never exposed to handling or contamination

Protects drink system seals, pump, tubing
and small orifices from clogging,
corrosion and abrasive wear

Reduces chlorine taste & odor and other
offensive contaminants that can adversely
affect the taste of beverages

Balanced cartridge for optimum
performance in varying water qualities

Improves the taste of fountain beverages
and helps retain the drink's carbonation

Compatible with Endurance systems,

Install vertically so cartridge hangs down.

Allow 2½" (6.35 cm) clearance below
the cartridge for easy cartridge
replacement.

Flush cartridge by running water through

system for five (5) minutes at full flow.
Change cartridges when capacity is
reached or when pressure falls below
10 psi (0.7 bar).

It is recommended to replace cartridge at
least once per year.

Always flush the filter cartridge at time of

Proprietary Fibredyne™ II media effectively inhibits the growth of
bacteria on the filter media that can decrease product life

Exclusive Fibredyne™ II media provides superior chlorine taste &
odor reduction and micro-filters dirt and particles as small as 0.2*
micron in size by mechanical means

NSF/ANSI Standard 53 certified to reduce cysts such as
Cryptosporidium and *Giardia* by mechanical means

* Validated by ISO 17025 accredited lab for 99.999% reduction of
Pseudomonas diminuta following the ASTM F838-05 protocol for
the validation of 0.2 µm sterilizing grade filters.

SIZING

installation and cartridge change.
Service Flow Rate: 3.75 gpm (14.1 Lpm)

Rated Capacity: 50,000 gallons (189,270
L) Note: This capacity is only achieved
when it has the Pentair Everpure Pleated
Microfilter Pretreatment upstream from
the system.

FOODSERVICE EV9692-65 SPECIFICATION SHEET

EVERPURE® SEN FILTER

CARTRIDGE EV9692-65

SPECIFICATIONS

Overall Dimensions

20.75" H x 3.25" D (52.7 x 8.3 cm)

Service Flow Rate

3.75 gpm (14.1 Lpm)

Rated Capacity

50,000 gallons (189,270 L)
20.75"

Note: This capacity is only achieved when it has the Pentair Everpure Pleated Microfilter Pretreatment upstream from the system.

Pressure Requirements

10 - 125 psi (0.7 - 8.6 bar), non-shock

Temperature Requirements

35 - 100°F (2 - 38°C)

STANDARD NO. 42 —
AESTHETIC EFFECTS
Bacteriostatic Effects
Chemical Reduction
Taste & Odor
Chlorine
Mechanical Filtration
Nominal Particulate, Class

STANDARD NO. 53—
HEALTH EFFECTS
Mechanical Filtration
Cyst Reduction
Turbidity Reduction

WARRANTY

or use of our products.

EPA Est. No. 002623-IL-002

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/

WATER QUALITY SYSTEMS

Everpure water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.

System Tested and Certified by
NSF International against NSF/
ANSI Standards 42 and 53 for the
reduction of:

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA •
FOODSERVICE.PENTAIR.COM 800.942.1153 (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO AUSTRALIA, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC 3175, AUSTRALIA
011.1300 576 190 TEL • 011.61.39.562.7237 FAX • AU.EVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA
86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301
91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO EUROPE, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN 30, B-2200 HERENTALS,
BELGIUM +32.(0).14.283.504 TEL • +32.(0).14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL

EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143,

JAPAN 81.(0)42.775.3011 TEL • 81.(0)42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL

EVERPURE-SHURFLO SOUTHEAST ASIA, SOUTHEAST ASIA, 390 HAVELOCK ROAD, #04-01 KING'S CENTRE, SINGAPORE
169662 65.6768.5800 TEL • 65.6737.5149 FAX • CSEVERPURE@PENTAIR.COM EMAIL

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

© 2016 Pentair Filtration Solutions, LLC. All Rights Reserved.

EV9692-65 MR16