

Date:





TECHNICAL SPECIFICATIONS

Due in attal Oranaka Italia	_
Project(s) Symbol(s):	
Type of Equipment:	Hand-held ULV sprayer

GENERAL INFORMATION	
Place and date of delivery	Freight: Air Sea Land
	Packing and labelling: The type of equipment contained within must be clearly shown on the packaging in both English and <>. All containers should also be marked with "Provided by FAO – <project symbol="">". The consignment must also indicate "Goods in transit for <>".</project>

EQUIPMENT		
ltem	Specifications	Quantity
Micron Ulva+ (for ULV formulation)	 Weight (empty): 0.8 Kg with 1 litre bottle; Weight (ready to spray): 2.6 Kg with 1 litre bottle; Disc speed: 7500 rpm-10000 rpm; Flow rate range: 25-100 ml/min; Droplet size: 50-100 µm (VMD); Spray pass interval: 2-10 m; Power supply: 9-12 Volt DC (6-8 D-cell/R20 batteries); Power consumption: 1.5-2.0 watts (up to 20 hrs spraying with good quality batteries). 	
Usual spare parts	 'O ring', BS 121, viton; 'O ring', BS 012, viton; Atomiser disc assembly; Nut, union – black; Bottle, 1 litre twin neck; Switch plug complete with connector; 	







Switch sleeve.	

TECHNICAL CLEARANCE	
Approving Officer	
Name and Signature	Date