

JOB SAFETY ANALYSIS FORM

JOB SAFETY ANALYSIS	Job Title: Weed/Brush Timmer Handheld, Gasoline Powered	JSA Number	DATE:	<input type="checkbox"/> NEW <input type="checkbox"/> REVISED Page: of
	TITLE OF PERSON WHO DOES JOB:	SUPERVISOR:	ANALYSIS BY: REVIEWED BY: APPROVED BY:	
	PLANT LOCATION:	DEPARTMENT:		
SEQUENCE OF BASIC JOB STEPS	POTENTIAL HAZARDS	RECOMMENDED ACTION OR PROCEDURE		
General Use	Eye injury from flying debris	Safety glasses with side shields or appropriate safety goggles		
	Trauma from flying debris, rotating parts and burns	Protective clothing, situational awareness and appropriate guards in place.		
	Foot injury from equipment contacts foot	Wear steel toed safety boots or shoes		
	Noise from equipment operation	Use hearing protection.		
Pre-Start Checklist: <ul style="list-style-type: none"> ● Perform pre-operational inspection and document inspection. PPE Required <ul style="list-style-type: none"> ● Safety glasses with side shields or appropriate goggles. ● Face shield. ● Hearing protection (ear plugs/ear muffs). ● Protective clothing (optional) (long sleeves/long pants). ● Safety shoes/boots. Equipment Procedures/Requirements: <ul style="list-style-type: none"> ● Operate equipment in strict accordance with manufacturer's instructions. ● Only authorized users can operate equipment. ● Report any observed defect or safety hazard to your supervisor immediately. ● Where any object handled would possibly cause injury to feet if dropped, safety shoes/boots will be worn. 				

JOB SAFETY ANALYSIS FORM

- Where any object handled could possibly cause cuts, punctures or abrasions to hands, appropriate gloves will be worn. (Exception: where rotating machinery presents a greater hazard of entangling gloves, they are optional with a written justification).
- Keep hands, hair and loose clothing clear of all moving parts.

Additional Precautions for Fuel Powered Engines:

- Always operate in an open well-ventilated area or vent the engine exhaust directly outdoors.
- Never fuel the engine while running or in the presence of an open flame.
- Wipe up spilled fuel immediately and wait for fumes to disperse before starting the engine.
- Never remove the radiator pressure cap from liquid cooled engines while they are hot to prevent scalding.
- Stop the engine before performing any maintenance or troubleshooting. The ignition system should be disabled to prevent accidental start of the engine.
- Keep all guards and shields in place.
- Keep hands, hair and clothing away from all moving parts.