



BIO MOULD RELEASE OIL

B7036-00

BIO MOULD RELEASE OIL is a basic fortified vegetable based fluid that is biodegradable with excellent surface conditioning characteristics to enable quick release of the mould and impart an excellent surface finish.

APPLICATIONS

- Suitable for all types of moulds and formwork where concrete, plaster or clay brick, tile or paver products are being manufactured.
- A ecologically friendly mould oil derived from vegetable oils and is completely non toxic and non irritant to the skin.
- Will adhere to the steel mould and prevent surface corrosion which might discolour the product finish or create defects in the product surface.
- will ensure high quality fair faced and stain free concrete surface finishes..

PROPERTIES

CHARACTERISTICS	BIO MOULD RELEASE OIL
Grade ISO	32
Viscosity @ 40 C cSt	30.0-35
Viscosity @ 100 C cst	N/A
Pour Point C	-2

PACKAGE SIZE

205 Litre, 20 Litre.

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.

- Safety Data Sheet for this product can be obtained by visiting Vixol Australia Pty Ltd Website www.vixol.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

Vixol Australia Pty Ltd
7 Foden Avenue Campbellfield Vic 3061 Australia
Tel: +61 03 9333 7701 Local sales: 1300 0894684
Email: sales@vixol.com.au www.vixol.com.au