

- Create a list of variables based off the highlighted areas. The variable list needs to contain all the answers that the end user will be giving you to complete the forms.
 - Use standard naming conventions. See [Appendix C of our A2J Authoring Guide](#) for more information on the community naming standards.
 - Ex. from Figure 1:
 - [Plaintiff name full TE]
 - [Defendent name full TE]
 - [Plaintiff is father or mother TF]

- Look for areas on the form that will need to be repeated or will need addendums. For example, does the form ask about the user’s children (perfect for a repeat loop) or is there a limited amount of space on the form for information that looks like it will require more space (perfect for adding an addendum).

1. Plaintiff is the Father/ Mother of the following child(ren) who are living with and in the care of Defendant:

	Child’s First Name and Last Initial	Year of Birth
a.		
b.		
c.		
d.		

2. Plaintiff wants to exercise scheduled visitation with said child(ren).

3. Visitation is is not in the best interest of the child(ren).

Figure 2: Spot of the sample form that will require a repeat loop.

- Add in the logic next. In Figure 5, the IF/ELSE expression is testing whether the user has said the Plaintiff is the father or the mother. If the user says the Plaintiff is the father, the variable [Plaintiff is father TF] will be “true” and the first box next to “father” will be checked. Otherwise (ELSE), the box next to “mother” will be checked on the final form. (The boxes will not display twice to the end user. This is just how the logic looks in HotDocs. Anything in green is ultimately hidden from the end user.)

A hearing for visitation was held in this case on the date listed above. Plaintiff was present. Defendant was present. Defendant was not present but was properly notified of the hearing.

At the hearing, the Court determined it has jurisdiction over the subject matter and the parties in this action. Venue is proper. Based on the evidence and testimony, the Court makes the following findings of fact:

1. Plaintiff is the «IF Plaintiff is father TF» Father/ Mother. «ELSE IF Plaintiff is father TF» Father/ Mother. «END IF»
2. of the following child(ren) who are living with and in the care of Defendant:

Figure 5: Sample IF/ELSE logic for a true/false variable in an .rtf template.

- Test! Test! Test! Every time you finish a section, test it. It’s easier to fix it as you go along, than to wait to test until the end and have big errors.
- Import your .cmp (HotDocs component file) into A2J Author and start creating your A2J Guided Interview.