Inspection Procedure

(motorcycles) November '14

Owners Card & Insurance	
missing, not in agreement, expired	
Owner_	Vehicle
<u>VIN</u>	
not in agreement, loose, missing defaced, misplaced VIN_	
	nontransparent material obstructs view, as etchings on front windows, defects in acute area, indscreen or more than 3" from top
Mirrors cracked, broken, discolored, don't hole less than 12 ½ sq.inch for flat/ 10 sq.in	d adjustment dadjustment a mirror on either side
Horn silent, not audible @ 200' equipped with illegal siren or whistle	
Brake Control/Master Cylinover 80% travel, fades, excessive frict lines disconnected, flattened, restricted worn belts (hydraulic booster), levers	tion leaks ed, inoperative,
	Frail not between 14 to 2 inches positive of sturdy, less than 18" between grip ends,

lamp fails to operate with correct switch, aux. equipment on, in or in front of lamp Fuel Cap missing
Fuel leaks, not secure, throttle sticks, improper routing, improper material/tank contacts high temp. or moving surfaces, intrudes passenger or cargo compartment
Shocks/Suspension Continues free rocking after release missing, severe leakage, mounts broken
Flooring not in condition to support, rusted through openings that would allow exhaust gases to enter
Fenders missing, wrong size, wrong type, protruding parts, metal or glass
License Plate not in agreement, loose, obscured, missing, not illuminated
Battery not secure
Motor Mounts missing, cracked, broken
Frame not solid, temporary repairs, pieces missing, cracks, rotted, broken, missing chain guard, dangerous, stand fails to operate, no hand-hold, no footrests for each rider, highway bars wider than 26" highway bars more than 15" from foot controls
Exhaust leaks, loose, no muffler, repaired muffler, cracks holes, passes through occupant compartment, inadequate heat shield, not secure with proper clamps and hangers, muffler cutout
Steering >1/4" wheel movement in relation to axle shaft, not contacting stops, tire rubs,

linkage components not secure, missing cotter pins		
less than 2/32, tread indicators contact road, exposed ply or cord, repaired, bump, bulge, separation, "not for highway use", tire contacts body or chassis, Front recut or regrooved below tread design, extends beyond body smaller than recommended, below recommended load rating studded from Apr. 15 -Nov. 1	Rear	
Wheels missing lugs, out of round, bent, cracked, broken, improperly repaired, doesn't track within 1" of front wheel,		
Brakes lines leak, flattened, restricted, mechanical damage, lining broken, loose, contaminated, drum/disc out of specs, scored more than .015, bonded-1/32, rivited-1/32, indicator shows pads need replacement	Front Rear	
Road Test		
Stopping Distance over maximum		
Speedometer fails to work properly		
Odometer vehicle less than 25 years old, and odometer fails to function correctly		
Forward vehicle fails to operate in forward		
Questionable Behavior shimmy, wander, pull		

Old mileage _	
New mileage_	