Some differences in default configuration variables for Central Managers:

8.6.13	8.8.12
	C_GAHP_CONTACT_SCHEDD_DELAY = 5
	C_GAHP_MAX_FILE_REQUESTS = 10 CGAHP_SCHEDD_INTERACTION_TIME = 5
	COLLECTOR_HOST_FOR_NEGOTIATOR = \$(FULL_HOSTNAME)
	COLLECTOR_QUERY_MAX_WORKTIME = 0
	COLLECTOR_QUERY_WORKERS_PENDING = 50 COLLECTOR_QUERY_WORKERS_RESERVE_FOR_HIGH_PRIO = 1
	CONDOR_Q_SHOW_OLD_SUMMARY = false
CURB_MATCHMAKING = false	CURB_MATCHMAKING = RecentDaemonCoreDutyCycle > 0.98
	DAGMAN_AGGRESSIVE_SUBMIT = false DAGMAN_ALLOW_ANY_NODE_NAME_CHARACTERS = false
DAGMAN_ALLOW_LOG_ERROR = false	
DAGMAN_MAX_SUBMITS_PER_INTERVAL = 5	DAGMAN_MAX_SUBMITS_PER_INTERVAL = 100
	DAGMAN_QUEUE_UPDATE_INTERVAL = 300
	DAGMAN_REPORT_GRAPH_METRICS = false
DATABASE_PURGE_INTERVAL = DATABASE_REINDEX_INTERVAL = DBMSD = \$(SBIN)/condor_dbmsd DBMSMANAGER_NAME =	
DEFAULT_JOB_MAX_RETRIES = 10	DEFAULT_JOB_MAX_RETRIES = 2
	DEFRAG_DRAINING_START_EXPR = FALSE
	DELEGATE_FULL_JOB_GSI_CREDENTIALS = false
<pre>EMAIL_NOTIFICATION_CC = ENABLE_ADDRESS_REWRITING = true</pre>	
	ENABLE_HTTP_PUBLIC_FILES = false

	<pre>ENABLE_MULTIFILE_TRANSFER_PLUGINS = false</pre>
ENABLE_WEB_SERVER = false	
FILE_TRANSFER_DISK_LOAD_THROTTLE =	FILE_TRANSFER_DISK_LOAD_THROTTLE = 2.0
	FILE_TRANSFER_STATS_LOG = \$(LOG)/transfer_history
	GAHP_SSL_CADIR = GAHP_SSL_CAFILE =
HISTORY_HELPER_MAX_CONCURRENCY = 2	HISTORY_HELPER_MAX_CONCURRENCY = 50
	HTTP_PUBLIC_FILES_ADDRESS = 127.0.0.1:80 HTTP_PUBLIC_FILES_ROOT_DIR = /usr/share/nginx/html HTTP_PUBLIC_FILES_STALE_AGE = 604800
<pre>IS_OWNER = (START ? False)</pre>	IS_OWNER = False
	JOB_DEFAULT_LEASE_DURATION = 2400
JOB_PROXY_OVERRIDE_FILE =	
	JOB_ROUTER_ROUND_ROBIN_SELECTION = false
	KEYRING_SESSION_CREATION_TIMEOUT = 20
MASTER_SQLLOG =	
	MAX_ACCEPTS_PER_CYCLE = 8
	MAX_CONCURRENT_DOWNLOADS = 100 MAX_CONCURRENT_UPLOADS = 100
	MAX_DRAINING_ACTIVATION_DELAY = 20
	MAX_PENDING_STARTD_CONTACTS = 0
	MAX_REAPS_PER_CYCLE = 0 MAX_REMAP_RECURSIONS = 128
MAX_RUNNING_SCHEDULER_JOBS_PER_OWNER =	MAX_RUNNING_SCHEDULER_JOBS_PER_OWNER = 200
	MAX_TIMER_EVENTS_PER_CYCLE = 3
	MAX_UDP_MSGS_PER_CYCLE = 1
MAX_XML_LOG = 190000000	

MOUNT_UNDER_SCRATCH =	MOUNT_UNDER_SCRATCH = "/tmp,/var/tmp"
	NEGOTIATOR_DEPTH_FIRST = false
	NEGOTIATOR_JOB_CONSTRAINT =
	NEGOTIATOR_MAX_TIME_PER_CYCLE = 1200
NEGOTIATOR_MAX_TIME_PER_SCHEDD = 31536000	NEGOTIATOR_MAX_TIME_PER_SCHEDD = 120
<pre>NEGOTIATOR_PREFETCH_REQUESTS = false NEGOTIATOR_PREFETCH_REQUESTS_MAX_TIME = 120</pre>	NEGOTIATOR_PREFETCH_REQUESTS_MAX_TIME = 60 NEGOTIATOR_PREFETCH_REQUESTS = true
NEGOTIATOR_RESOURCE_REQUEST_LIST_SIZE = 20	NEGOTIATOR_RESOURCE_REQUEST_LIST_SIZE = 200
	NEGOTIATOR_SOCKET_CACHE_SIZE = 500
OBITUARY_LOG_LENGTH = 20	OBITUARY_LOG_LENGTH = 200
PREEN_MAX_SCHEDD_CONNECTION_TIME = 20	
	SCHEDD_ALLOW_LATE_MATERIALIZE = true
	SEC_CREDENTIAL_REFRESH_INTERVAL = -1
SHARED_PORT_ADDRESS_REWRITING = false	
STARTD_COMPUTE_AVAIL_STATS = false	
STARTD_MAX_AVAIL_PERIOD_SAMPLES = 100	
START_SCHEDULER_UNIVERSE = TotalSchedulerJobsRunning < 200	START_SCHEDULER_UNIVERSE = TotalSchedulerJobsRunning < 500
	SUBMIT_DEFAULT_SHOULD_TRANSFER_FILES =
SUBMIT_SKIP_FILECHECKS =	SUBMIT_SKIP_FILECHECKS = true
SYSTEM_VALID_SPOOL_FILES = job_queue.log, job_queue.log.tmp, history, Accountant.log, Accountantnew.log, local_univ_execute, .quillwritepassword, .pgpass, .schedd_address, .schedd_address.super, .schedd_classad, OfflineLog	SYSTEM_VALID_SPOOL_FILES = job_queue.log, job_queue.log.tmp, history, Accountant.log, Accountantnew.log, local_univ_execute, .pgpass, .schedd_address, .schedd_address.super, .schedd_classad, OfflineLog
	TRUST_LOCAL_UID_DOMAIN = true

WARN_ON_UNUSED_SUBMIT_FILE_MACROS =	WARN_ON_UNUSED_SUBMIT_FILE_MACROS = true
WEB_ROOT_DIR =	