

Query Service V2 - Migration Guide

v1 CLI Flags vs. v2 Configuration Options

Common Settings

Feature	v1 CLI Flag	v2 Configuration Option	Notes
Additional HTTP Headers	--query.additional-headers	http: headers:	
HTTP Host Port	--query.http-server.host-port	http: endpoint:	
GRPC Host Port	--query.grpc-server.host-port	grpc: endpoint:	
Base Path	--query.base-path	base_path:	
Static Files Directory	--query.static-files	ui: assets_path:	
Static Assets Debug	--query.log-static-assets-access	ui: log_access:	
UI Config	--query.ui-config	ui: config_file	
Bearer Token Propagation	--query.bearer-token-propagation	bearer_token_propagation:	
Max Clock Skew Adjustment	--query.max-clock-skew-adjustment	max_clock_skew_adjust:	
Enable Tracing	--query.enable-tracing	enable_tracing:	
HTTP TLS Configurations	--query.http.tls.*	http: tls:	

	The “ <code>tls.enabled</code> ” flag is equivalent to defining or not defining the “ <code>tls:</code> ” section in the config	...	
GRPC TLS Configurations	-- <code>query.grpc.tls.*</code> The “ <code>tls.enabled</code> ” flag is equivalent to defining or not defining the “ <code>tls:</code> ” section in the config	<code>grpc:</code> <code> tls:</code> ...	