

ETHERNET ACTIVATOR

BUILD ONTO
YOUR NETWORK



SCAN FOR MORE



Add **beadedstream** Digital Temperature Cables (DTCs) on to your LAN with the Ethernet Activator. Take advantage of structured cabling that already exists in your building. Save time. Save money. Use existing Cat 5/6, switches, routers, the Internet, and in-house MIS expertise to build out your temperature monitoring network.

ETHERNET ACTIVATOR



SPECIFICATIONS

Access Remotely

- Receive real-time data and remotely (LAN) configure

Programmatic Interfaces

- HTTP, HTTP POST, TCP Socket, Multicast, DHCP

Responsiveness

- Does not require temperature conversion
- Real-time graphing and logging

Capacity

- 500 ft (152.5 m) - maximum DTC length

Connections

- RJ12 jack (DTC). Supports 1 DTC up to 125 sensors.
- Ethernet RJ45 jack (data)
- Micro USB (power/configuration)

Power and Protection

- 5V USB charger to standard duplex outlet (USA) included.
- Over 27kV static discharge protection on data line

Weight and Dimensions

- 0.3 lbs (0.15 kg)
- 4.5 in x 2.5 in x 1.25 in (11.5 cm x 9 cm x 3 cm)

Mounting

- DIN Rail