

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals)	Field in use
cbc:ID	34	Order identifier A transaction instance must have an identifier. The identifier enables referencing the transaction for various purposes such as from other transactions that are part of the same process. Sales order reference	20	yes
cbc:SalesOrderID	112233	An identifier of a referenced sales order, issued by the Seller. Order issue date		no
cbc:IssueDate	2018-09-01	The date on which the transaction instance was issued. Order issue time	N/A	yes
cbc:IssueTime	14:12:32	The time assigned by the buyer on which the order was issued. The Order Change Sequence Number assigned by the Buyer to ensure the proper sequencing of changes.	N/A	yes
cbc:SequenceNumberID	12	Document level internal note Free form text applying to the Order. This element may contain notes or any other similar information that is not contained explicitly in another structure.		yes
cbc:Note		Information text for the whole order Currency The default currency for the order.		yes
cbc:DocumentCurrencyCode	NOK	Currency codes: https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/ Buyer contact The element is used for the reference of who ordered the products/services. Example being the name of the person ordering, employee number or a code identifying this person or department/group. Also known as "Buyer reference", and should also be sent in the corresponding invoice.	3	yes
cbc:CustomerReference	9000012345	Buyers accounting string Used by the buyer to specify a reference that should be repeated in e.g. invoice to enable the buyer to automatically book e.g. to the right project, or account.	30	yes
cbc:AccountingCost	Project123	Order validity end date The end date for when the order is valid. The end date for the time period within which the seller must respond. An order should contain the validity end date Used to reference the initial order.		no
cac:ValidityPeriod/cbc:EndDate	2013-01-31	Quotation document reference A requirement to give a unique reference to the quotation that is the base for the order.		yes
cac:OrderReference/cbc:ID	12345	Order document reference Used to reference the initial order that was rejected and a new order is issued.		no
cac:QuotationDocumentReference/cbc:ID	RejectedOrder123	Originator document reference A reference to Originator Document. To be able to give a reference to the internal requisition on the buyer site on which the order is based.		no
cac:OrderDocumentReference/cbc:ID		Additional documents/Document identifier An identifier for the referenced document.		no
cac:OriginatorDocumentReference/cbc:ID	MAFO	Additional documents/Document description Textual description of the document.		no
cac:AdditionalDocumentReference/cbc:ID	Doc2	Additional documents/Attached document The attached document embedded as binary object, coded as Base64. The binary object has two supplementary components: a Mime Code, which specifies the Mime type of the attachment and a Filename that is provided by (or on behalf of) the sender of the document.		no
cac:AdditionalDocumentReference/cbc:AttachmentDataBinaryObject/cbc:EmbeddedDocumentBinaryObject/@mimeCode		https://docs.peppol.eu/poacc/ugrade-3/codelist/IANA/mimeCode		no
cac:AdditionalDocumentReference/cbc:AttachmentDataBinaryObject/cbc:EmbeddedDocumentBinaryObject/@filename		https://docs.peppol.eu/poacc/ugrade-3/codelist/IANA/fileName		no
cac:AdditionalDocumentReference/cbc:AttachmentDataBinaryObject/cbc:EmbeddedDocumentBinaryObject/@id		External reference Reference to external document		no
cac:Attachment/cbc:ExternalReference/cbc:URI	https://www.supplier.se/evalsheet001.html	Contract information, reference to contract Reference identifier		no
cac:Contract/cbc:ID	34322	Positive identification of the reference such as a unique identifier. Buyer information Buyer party electronic address Identifies the buyer party's electronic address	50	yes
cac:BuyerCustomerParty/cac:Party/cbc:EndpointID/@schemeID	schemeID="0192" 987654325	Scheme ID's: 0212 - Finnish Organization Identifier 0213 - Finnish Organization Value Added Tax Identifier 0216 - OV/Code https://docs.peppol.eu/poacc/ugrade-3/codelist/eas/ Buyer party identification An identification for the buyer party.	50	yes
cac:BuyerCustomerParty/cac:Party/cbc:PartyIdentification/cbc:ID/@schemeID	schemeID="1008" 7300010000001	Scheme ID's: 0212 - Finnish Organization Identifier 0216 - OV/Code https://docs.peppol.eu/poacc/ugrade-3/codelist/ICV/ Buyer name		no
cac:BuyerCustomerParty/cac:Party/cbc:PartyName/cbc:Name	Helseforetak	Name of buyer The name of the party who orders the listed items. Postal address of the buyer	N/A	yes
cac:BuyerCustomerParty/cac:Party/cbc:PostalAddress/cbc:StreetName	Sinsenveien 40	Address line 1 The main address line in a postal address usually the street name and number.		no
cac:BuyerCustomerParty/cac:Party/cbc:PostalAddress/cbc:AdditionalStreetName	Oppgang 8	Address line 2 An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building.		no
cac:BuyerCustomerParty/cac:Party/cbc:PostalAddress/cbc:CityName	Oslo	City The common name of the city where the postal address is. The name is written in full rather than as a code.		no
cac:BuyerCustomerParty/cac:Party/cbc:PostalAddress/cbc:PostZone	0501	Post code The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code.		no
cac:BuyerCustomerParty/cac:Party/cbc:PostalAddress/cbc:CountrySubentity		Country subdivision For specifying a region, county, state, province etc. within a country by using text.		no
cac:BuyerCustomerParty/cac:Party/cbc:PostalAddress/cbc:AddressLine	Address Line 3	Address line 3 An additional address line in an address that can be used to give further details supplementing the main line.		no
cac:BuyerCustomerParty/cac:Party/cbc:PostalAddress/cbc:CountryIdentificationCode	NO	Country code https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/ Buyer TAX Identifier The buyers registered Value Added Tax Identifier. To be stated in case reverse charge is to apply to the purchase.		yes
cac:BuyerCustomerParty/cac:Party/cbc:PartyTaxScheme/cbc:CompanyID	NO9311867455MVA	Tax scheme Mandatory element. E.g. "VAT" or "GST"		no
cac:BuyerCustomerParty/cac:Party/cbc:PartyTaxScheme/cbc:TaxScheme/cbc:ID	VAT	Buyers legal registration name The official name of the party as registered with the relevant fiscal authority.		no
cac:BuyerCustomerParty/cac:Party/cbc:PartyLegalEntity/cbc:RegistrationName	Helseforetak AS	Buyers legal registration identifier Identifies a company as registered with the company registration scheme.	N/A	yes
cac:BuyerCustomerParty/cac:Party/cbc:PartyLegalEntity/cbc:CompanyID/@schemeID	schemeID="10082" 931186755	Scheme ID's: 0212 - Finnish Organization Identifier 0216 - OV/Code https://docs.peppol.eu/poacc/ugrade-3/codelist/ICD/ (same codelist as in cell C26) Buyers legal registration address city name	50	yes
cac:BuyerCustomerParty/cac:Party/cbc:PartyLegalEntity/cbc:RegistrationAddress/cbc:CityName	Oslo	Associates with the registered address of the party within a Corporate Registration Scheme. The name of a city, town, or village. Country code A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency. Codes for the representation of names of countries and their subdivisions. Codes must be according to the alpha-2 representation.		no
cac:BuyerCustomerParty/cac:Party/cbc:PartyLegalEntity/cbc:RegistrationAddress/cbc:CountryIdentificationCode	NO	Country codes: https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/		no
cac:BuyerCustomerParty/cac:Party/cbc:Contact/cbc:Name	Ole Olsen	Contact person name The name of the contact person.		no
cac:BuyerCustomerParty/cac:Party/cbc:Contact/cbc:Telephone	23055000	Contact telephone number A phone number for the contact person. If the person has a direct number, this is that number.		no
cac:BuyerCustomerParty/cac:Party/cbc:Contact/cbc:ElectronicMail	post@helseforetak.no	Contact email address The e-mail address for the contact person. If the person has a direct e-mail this is that email.		no

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals)	Field in use
		<b>Seller information</b> Seller party electronic address Identifies the seller party's electronic address		
		Scheme ID examples: <b>0212</b> - Finnish Organization Identifier <b>0213</b> - Finnish Organization Value Add Tax Identifier <b>0216</b> - OV/Code <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/au/">https://docs.peppol.eu/poacc/ugrade-3/codelist/au/</a> (same codelist as in cell C25) Party identification	50	yes
<code>cac:SellerSupplierParty/cac:Party/cbc:EndpointID @schemeID</code>	schemaID="0192" 123456785			
		Scheme ID examples: <b>0212</b> - Finnish Organization Identifier <b>0216</b> - OV/Code <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/">https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/</a> (same codelist as in cell C26) Seller party trading name	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PartyName/cbc:Name</code>	Medical	The trading name of the party. Address line 1 The main address line in a postal address usually the street name and number.	256	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PostalAddress/cbc:StreetName</code>	Storgt. 12	Address line 2 An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PostalAddress/cbc:AdditionalStreetName</code>	4. etasje	City The common name of the city where the postal address is. The name is written in full rather than as a code.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PostalAddress/cbc:CityName</code>	Oslo	Post code The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PostalAddress/cbc:PostalZone</code>	0585	Country subdivision For specifying a region, county, state, province etc. within a country by using text.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PostalAddress/cbc:CountrySubentity</code>	Region	Address line 3 An additional address line in an address that can be used to give further details supplementing the main line.		no
<code>cac:SellerSupplierParty/cac:Party/cac:PostalAddress/cac:AddressLine/cbc:Line</code>	Address Line 3	Country code A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency. Codes for the representation of names of countries and their subdivisions. Codes must be according to the alpha-2 representation.		no
		Country codes: <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/">https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/</a> Seller legal registration name The official name of the party as registered with the relevant fiscal authority.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PostalAddress/cac:Country/cbc:IdentificationCode</code>	NO	Seller legal registration identifier Identifies a company as registered with the company registration scheme.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PartyLegalEntity/cbc:RegistrationName</code>	Medical AS	Scheme ID examples: <b>0212</b> - Finnish Organization Identifier <b>0216</b> - OV/Code <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/">https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/</a> (same codelist as in cell C26) Sellers legal registration address city name Associates with the registered address of the party within a Corporate Registration Scheme. The name of a city, town, or village.	256	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PartyLegalEntity/cbc:CompanyID @schemeID</code>	schemaID="0088" 123456789	Country code A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency. Codes for the representation of names of countries and their subdivisions. Codes must be according to the alpha-2 representation.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PartyLegalEntity/cac:RegistrationAddress/cbc:CityName</code>	Oslo	Country code <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/">https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/</a> Contact person name The name of the contact person.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PartyLegalEntity/cac:RegistrationAddress/cac:Country/cbc:IdentificationCode</code>	NO	Contact telephone number A phone number for the contact person. If the person has a direct number, this is that number.	50	yes
<code>cac:SellerSupplierParty/cac:Party/cac:PartyLegalEntity/cac:RegistrationAddress/cbc:Name</code>	Nils Nilsen	Contact email address The e-mail address for the contact person. If the person has a direct e-mail this is that email.		no
<code>cac:SellerSupplierParty/cac:Party/cac:PartyLegalEntity/cac:RegistrationAddress/cbc:Telephone</code>	22150510	Originator party information regarding the originator of the order		no
<code>cac:SellerSupplierParty/cac:Party/cac:PartyLegalEntity/cac:RegistrationAddress/cbc:ElectronicMail</code>	post@medical.no	Scheme ID examples: <b>0212</b> - Finnish Organization Identifier <b>0216</b> - OV/Code <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/">https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/</a> (same codelist as in cell C26) Originator name The name of the party. Contact person name The name of the contact person. Contact telephone number A phone number for the contact person. If the person has a direct number, this is that number. Contact email address The e-mail address for the contact person. If the person has a direct e-mail this is that email.	50	yes
<code>cac:OriginatorCustomerParty/cac:Party/cac:PartyIdentification/cbc:ID @schemeID</code>	schemaID="0088" 730001000001	Invoice party information regarding the receiver of the invoice based on the order (invoicee) Invoice party electronic address Identifies the invoice party's electronic address		no
<code>cac:OriginatorCustomerParty/cac:Party/cac:PartyName/cbc:Name</code>	Helsetravetling	Scheme ID examples: <b>0212</b> - Finnish Organization Identifier <b>0213</b> - Finnish Organization Value Add Tax Identifier <b>0216</b> - OV/Code <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/au/">https://docs.peppol.eu/poacc/ugrade-3/codelist/au/</a> (same codelist as in cell C25) Invoice identifier An identifier for the invoice party.		no
<code>cac:OriginatorCustomerParty/cac:Party/cac:PartyLegalEntity/cbc:RegistrationName</code>	Julie Jensen	Scheme ID examples: <b>0212</b> - Finnish Organization Identifier <b>0216</b> - OV/Code <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/">https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/</a> (same codelist as in cell C26) Invoice name The name of the party who should be invoiced for the ordered items (invoicee). Address line 1 The main address line in a postal address usually the street name and number. Address line 2 An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building. City The common name of the city where the postal address is. The name is written in full rather than as a code. Post code The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code. Country subdivision For specifying a region, county, state, province etc. within a country by using text.	50	yes
<code>cac:OriginatorCustomerParty/cac:Party/cac:PartyLegalEntity/cac:RegistrationAddress/cbc:CityName</code>	Oslo	Address line 3 An additional address line in an address that can be used to give further details supplementing the main line.		no
<code>cac:OriginatorCustomerParty/cac:Party/cac:PartyLegalEntity/cac:RegistrationAddress/cbc:Telephone</code>	67915012	Country code A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency. Codes for the representation of names of countries and their subdivisions. Codes must be according to the alpha-2 representation.		no
<code>cac:OriginatorCustomerParty/cac:Party/cac:PartyLegalEntity/cac:RegistrationAddress/cbc:ElectronicMail</code>	post@helse.no	Country codes: <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/">https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/</a> Invoice TAX identifier The invoicee registered Value Added Tax identifier		no
<code>cac:AccountingCustomerParty/cac:Party/cbc:EndpointID @schemeID</code>	schemaID="0192" 987654321			
		Scheme ID examples: <b>0212</b> - Finnish Organization Identifier <b>0213</b> - Finnish Organization Value Add Tax Identifier <b>0216</b> - OV/Code <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/">https://docs.peppol.eu/poacc/ugrade-3/codelist/CD/</a> (same codelist as in cell C26) Invoice name The name of the party who should be invoiced for the ordered items (invoicee). Address line 1 The main address line in a postal address usually the street name and number. Address line 2 An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building. City The common name of the city where the postal address is. The name is written in full rather than as a code. Post code The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code. Country subdivision For specifying a region, county, state, province etc. within a country by using text.	50	yes
<code>cac:AccountingCustomerParty/cac:Party/cac:PartyName/cbc:Name</code>	Accounting	Address line 3 An additional address line in an address that can be used to give further details supplementing the main line.		no
<code>cac:AccountingCustomerParty/cac:Party/cac:PostalAddress/cbc:StreetName</code>	Sinsenveien 42	Country code A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency. Codes for the representation of names of countries and their subdivisions. Codes must be according to the alpha-2 representation.		no
<code>cac:AccountingCustomerParty/cac:Party/cac:PostalAddress/cbc:AdditionalStreetName</code>	Oppgang A	Country codes: <a href="https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/">https://docs.peppol.eu/poacc/ugrade-3/codelist/ISO3166/</a> Invoice TAX identifier The invoicee registered Value Added Tax identifier		no
<code>cac:AccountingCustomerParty/cac:Party/cac:PostalAddress/cbc:CityName</code>	Oslo			
<code>cac:AccountingCustomerParty/cac:Party/cac:PostalAddress/cbc:PostalZone</code>	501			
<code>cac:AccountingCustomerParty/cac:Party/cac:PostalAddress/cbc:CountrySubentity</code>	Region			
<code>cac:AccountingCustomerParty/cac:Party/cac:PostalAddress/cac:AddressLine/cbc:Line</code>	Address Line 3			
<code>cac:AccountingCustomerParty/cac:Party/cac:PostalAddress/cac:Country/cbc:IdentificationCode</code>	NO			
<code>cac:AccountingCustomerParty/cac:Party/cac:PartyLegalEntity/cbc:CompanyID</code>	N09311867455MVA			

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals)	Field in use
<code>cac:AccountingCustomerParty/cac:Party/cac:TaxScheme/cbc:ID</code>	VAT	Tax scheme identifier. E.g. "VAT" or "GST"		no
<code>cac:AccountingCustomerParty/cac:Party/cac:PartyLegalEntity/cbc:RegistrationName</code>	Helteforetak AS	Invoice's legal registration name The official name of the invoice party as registered with the relevant fiscal authority. Buyer legal registration identifier identification scheme identifier The identification scheme identifier of the buyer legal registration identifier.		no
<code>cac:AccountingCustomerParty/cac:Party/cac:PartyLegalEntity/cbc:CompanyID @schemeID</code>	schemeID="0082" 931186723	Scheme ID's: <b>0212</b> - Finnish Organization Identifier <b>0216</b> - OVCode <a href="https://docs.peppol.eu/poacc/upgrade-3/codelist/ICD/">https://docs.peppol.eu/poacc/upgrade-3/codelist/ICD/</a> (same codelist as in cell C26)		no
<code>cac:AccountingCustomerParty/cac:Party/cac:PartyLegalEntity/cbc:RegistrationAddress/cbc:CityName</code>	Oslo	City name Associates with the registered address of the party within a Corporate Registration Scheme. The name of a city, town, or village.		no
<code>cac:AccountingCustomerParty/cac:Party/cac:PartyLegalEntity/cbc:RegistrationAddress/cbc:Country/cbc:IdentificationCode</code>	NO	Country code A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency. Codes for the representation of names of countries and their subdivisions. Codes must be according to the alpha-2 representation.		no
<code>cac:Delivery/cac:DeliveryLocation/cbc:ID @schemeID</code>	schemeID="0088" 730001000001	Country codes: <a href="https://docs.peppol.eu/poacc/upgrade-3/codelist/ISO3166/">https://docs.peppol.eu/poacc/upgrade-3/codelist/ISO3166/</a> Delivery information Delivery location ID An identifier for the location to where the ordered items should be delivered.	50	yes
<code>cac:Delivery/cac:DeliveryLocation/cbc:Name</code>		Delivery location name A name of the location to where the ordered items should be delivered.	256 / 4000	yes
<code>cac:Delivery/cac:DeliveryLocation/cac:Address/cbc:StreetName</code>	Solheimsvetin 10	Address line 1 The main address line in a postal address usually the street name and number.	50	yes
<code>cac:Delivery/cac:DeliveryLocation/cac:Address/cbc:AdditionalStreetName</code>	Add	Address line 2 An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building.	50	yes
<code>cac:Delivery/cac:DeliveryLocation/cac:Address/cbc:CityName</code>	Lørenskog	City The common name of the city where the postal address is. The name is written in full rather than as a code.	50	yes
<code>cac:Delivery/cac:DeliveryLocation/cac:Address/cbc:PostalZone</code>	1473	Post code The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code.	50	yes
<code>cac:Delivery/cac:Address/cbc:CountrySubentity</code>	Region	Country subdivision For specifying a region, county, state, province etc. within a country by using text.	50	yes
<code>cac:Delivery/cac:DeliveryLocation/cac:Address/cac:AddressLine/cbc:Line</code>	3rd Address line	Address line 3 An additional address line in an address that can be used to give further details supplementing the main line.	65	yes
<code>cac:Delivery/cac:DeliveryLocation/cac:Address/cac:Country/cbc:IdentificationCode</code>	NO	Country code A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency. Codes for the representation of names of countries and their subdivisions. Codes must be according to the alpha-2 representation.	50	yes
<code>cac:Delivery/cac:RequestedDeliveryPeriod/cbc:StartDate</code>	2012-10-10	Requested delivery period Period start date The date on which the period starts. The start dates counts in part of the period.Format = "YYYY-MM-DD"	N/A	yes
<code>cac:Delivery/cac:RequestedDeliveryPeriod/cbc:StartTime</code>	12:30:00	Period start time The time at which this period begins. Format = "hh:mm:ss"		no
<code>cac:Delivery/cac:RequestedDeliveryPeriod/cbc:EndDate</code>	2012-10-20	Period end date The date on which the period ends. The end date counts in part of the period.Format = "YYYY-MM-DD"	N/A	yes
<code>cac:Delivery/cac:RequestedDeliveryPeriod/cbc:EndTime</code>	18:00:00	Period end time The time at which this period ends. Format = "hh:mm:ss"		no
<code>cac:Delivery/cac:DeliveryParty/cac:PartyIdentification/cbc:ID @schemeID</code>	schemeID="0082" 13691234	Party identification Identification of the delivery party. The party to whom the goods are delivered. Scheme ID's: <b>0212</b> - Finnish Organization Identifier <b>0216</b> - OVCode <a href="https://docs.peppol.eu/poacc/upgrade-3/codelist/ICD/">https://docs.peppol.eu/poacc/upgrade-3/codelist/ICD/</a> (same codelist as in cell C26)	50	yes
<code>cac:Delivery/cac:DeliveryParty/cac:PartyName/cbc:Name</code>	Heiseovdeling	Delivery party name In this BIS: The name of the party that should receive the delivery	256 / 4000	yes
<code>cac:Delivery/cac:DeliveryParty/cac:Contact/cbc:Name</code>	Ole	Delivery party name In this BIS: The name of the party that should receive the delivery		no
<code>cac:Delivery/cac:DeliveryParty/cac:Contact/cbc:Telephone</code>	987098709	Contact telephone number A phone number for the contact person. If the person has a direct number, this is that number.		no
<code>cac:Delivery/cac:DeliveryParty/cac:Contact/cbc:ElectronicMail</code>	ole@helteforetak.no	Contact email address The e-mail address for the contact person. If the person has a direct e-mail this is that email.	256	yes
<code>cac:DeliveryTerms/cbc:ID</code>	FOB	Delivery terms identifier Delivery terms identifier, normally incoterms	10	yes
<code>cac:DeliveryTerms/cbc:SpecialTerms</code>	CAD	Delivery special terms A description of special conditions relating to the Delivery Terms.		no
<code>cac:DeliveryTerms/cac:DeliveryLocation/cbc:ID</code>	FOB Oslo	Delivery terms location The location to which the delivery terms refer. Used to qualify the delivery terms e.g. "Terms of delivery are FOB Rotterdam"		no
<code>cac:PaymentTerms/cbc:Note</code>	Payment terms description Example 1: true	Payment terms Payment terms for the order described in text Allowance and charge information Allowances and charges for the order AllowanceChargeIndicator	6	yes
<code>cac:AllowanceCharge/cbc:ChargeIndicator</code>	Example 2: false	Indicator used to state if the following is an allowance or charge: true = Charge, false = Allowance		no
<code>cac:AllowanceCharge/cbc:AllowanceChargeReasonCode</code>	Example 1: ABX	Document level allowance or charge reason code The reason for the document level allowance or charge, expressed as a code. For allowances a subset of codelist UNCL5189 is to be used, and for charges codelist UNCL7161 applies. The Document level allowance reason code and the Document level allowance reason shall indicate the same allowance reason		no
<code>cac:AllowanceCharge/cbc:AllowanceChargeReason</code>	Example 2: Miscellaneous services	Charge reason code <a href="https://docs.peppol.eu/poacc/upgrade-3/codelist/UNCL7161/">https://docs.peppol.eu/poacc/upgrade-3/codelist/UNCL7161/</a> Allowance and charges reason A textual reason for the allowance or the charge. Can also be its name. The Document level allowance reason code and the Document level allowance reason shall indicate the same allowance reason		no
<code>cac:AllowanceCharge/cbc:MultiplierFactorNumeric</code>	Example 1: N/A	Document level allowance or charge percentage The percentage that may be used, in conjunction with the document level allowance base amount, to calculate the document level allowance or charge amount. To state 20%, use value 20.		no
<code>cac:AllowanceCharge/cbc:Amount @currencyID</code>	Example 2: 652.50	Currency identifier Currency identifier, value must be the same as what is used in ir01-007, DocumentCurrencyCode		no
<code>cac:AllowanceCharge/cbc:BaseAmount @currencyID</code>	Example 1: N/A	Currency ID: <a href="https://docs.peppol.eu/poacc/upgrade-3/codelist/ISO4217/">https://docs.peppol.eu/poacc/upgrade-3/codelist/ISO4217/</a> Document level allowance or charge base amount The base amount that may be used, in conjunction with the document level allowance or charge percentage, to calculate the document level allowance or charge amount. Must be rounded to maximum 2 decimals		no

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals)	Field in use
<b>cac:AllowanceCharge/cac:TaxCategory/cbc:ID</b>	Example 1: Z Example 2: S	TAX category code The TAX category code that applies to the document level allowance or charge.		no
<b>cac:AllowanceCharge/cac:TaxCategory/cbc:Percent</b>	Example 1: 0 Example 2: 25	TAX rate The TAX rate, represented as percentage that applies to the document level allowance or charge. As this element is of data type percentage, please note that no % sign should be used. To state 25 %, use value 25.00		no
<b>cac:AllowanceCharge/cac:TaxCategory/cac:TaxScheme/cbc:ID</b>	VAT	Tax scheme identifier. E.g. "VAT" or "IGST"		no
<b>cac:TaxTotal/cbc:TaxAmount @currencyID</b>	currencyID="WOK" 100.00	TAX total amount The total TAX amount that is "added to the document total w/o TAX". This is the sum of all TAX subcategory amounts. The expected Tax Total in the corresponding invoice.		no
<b>cac:AnticipatedMonetaryTotal/cbc:LineExtensionAmount @currencyID</b>	currencyID="WOK" 6525.00	Anticipated monetary total Estimated total amounts for the order Sum of line amounts Sum of line amounts in the document. The total of Line Extension Amounts net of tax and settlement discounts. Must be rounded to maximum 2 decimals. Document total without TAX The "Sum of line amounts" plus "sum of allowances on document level" plus "sum of charges on document level". Must be rounded to maximum 2 decimals.	2	yes
<b>cac:AnticipatedMonetaryTotal/cbc:TaxExclusiveAmount @currencyID</b>	currencyID="WOK" 6272.50	Anticipated monetary total Document total including TAX The total value including TAX. Must be rounded to maximum 2 decimals.	2	no
<b>cac:AnticipatedMonetaryTotal/cbc:TaxInclusiveAmount @currencyID</b>	currencyID="WOK" 6372.50	Anticipated monetary total Sum of allowances on document level Sum of all allowances on header level in the document. Allowances on line level are included in the line amount and summed up into the "sum of line amounts". Must be rounded to maximum 2 decimals.	2	no
<b>cac:AnticipatedMonetaryTotal/cbc:AllowanceTotalAmount @currencyID</b>	currencyID="WOK" 652.50	Anticipated monetary total Sum of charges on document level Sum of all charge on header level in the document. Charges on line level are included in the line amount and summed up into the "sum of line amounts". Must be rounded to maximum 2 decimals.		no
<b>cac:AnticipatedMonetaryTotal/cbc:ChargeTotalAmount @currencyID</b>	currencyID="WOK" 400.00	Anticipated monetary total Prepaid amounts Any amounts that have been paid a-priori. Must be rounded to maximum 2 decimals.		no
<b>cac:AnticipatedMonetaryTotal/cbc:PrepaidAmount @currencyID</b>	currencyID="WOK" 10.00	Anticipated monetary total Rounding of document total The amount to be added to the total to round the amount to be paid. Must be rounded to maximum 2 decimals.		no
<b>cac:AnticipatedMonetaryTotal/cbc:PayableAmount @currencyID</b>	currencyID="WOK" 0.50	Anticipated monetary total Payable amount The amount that is expected to be paid. Must be rounded to maximum 2 decimals.		yes
<b>cac:AnticipatedMonetaryTotal/cbc:PayableAmount @currencyID</b>	currencyID="WOK" 6363	Anticipated monetary total Order line Specification of order lines Order line note Free-form text applying to the Order Line. This element may contain notes or any other similar information that is not contained explicitly in another structure. Is to capture any free form description related to the order line as a whole. Line item identifier Identifies the Line Item assigned by the buyer, the 1 identifier must be unique within the order. Response code A code that indicates status of the referenced order line Response codes: 1 - Order line is added 2 - Deleted 3 - Changed 4 - No action 74 - Reopened		no
<b>cac:OrderLine/cbc:Note</b>	Freetext note on line 1	Freetext note on line 1		256 yes
<b>cac:OrderLine/cac:LineItem/cbc:ID</b>		Line item identifier Identifies the Line Item assigned by the buyer, the 1 identifier must be unique within the order. Response code A code that indicates status of the referenced order line Response codes: 1 - Order line is added 2 - Deleted 3 - Changed 4 - No action 74 - Reopened	N/A	yes
<b>cac:OrderLine/cac:LineItem/cbc:LineStatusCode</b>		Response code A code that indicates status of the referenced order line Response codes: 1 - Order line is added 2 - Deleted 3 - Changed 4 - No action 74 - Reopened	2	yes
<b>cac:OrderLine/cac:LineItem/cbc:Quantity @unitCode</b>	unitCode="EA" 120	Ordered quantity The quantity of items for the Line Item. The quantity for the order line. Ordered quantity unit of measure The unit of measure that applies to the ordered quantity.		6 yes
<b>cac:OrderLine/cac:LineItem/cbc:LineExtensionAmount @currencyID</b>	currencyID="WOK" 6300.00	Ordered quantity The quantity of items for the Line Item. The quantity for the order line. Ordered quantity unit of measure The unit of measure that applies to the ordered quantity.		2 yes
<b>cac:OrderLine/cac:LineItem/cbc:PartialDeliveryIndicator</b>	FALSE	Partial delivery indicator Indicates if the line items must be delivered in a single shipment. Default is that partial delivery is allowed (true)		5 yes
<b>cac:OrderLine/cac:LineItem/cbc:AccountingCost</b>	12345678	Buyers accounting string The buyer's accounting information applied to the Line Item, expressed as text.		no
<b>cac:OrderLine/cac:LineItem/cac:Delivery/cbc:ID @schemeID</b>	schemeID="0088" 730001000001	Delivery location ID An identifier for the location where the ordered line item should be delivered. Deliver to location identifier identification scheme identifier The identification scheme identifier of the Deliver to location identifier.		no
<b>cac:OrderLine/cac:LineItem/cac:Delivery/cbc:RequestedDeliveryPeriod/cbc:Start</b>	2/10/2010	SchemeID https://docs.peppol.eu/poacc/upgrade-3/codelists/ICD/ Order line requested delivery period Requested delivery period for the order line Period start date The date on which the period starts. The start date counts as part of the period. Format = "YYYY-MM-DD"		N/A yes
<b>cac:OrderLine/cac:LineItem/cac:Delivery/cbc:RequestedDeliveryPeriod/cbc:Start</b>	12:30:00	Period start time The time at which this period begins. Format = "hh:mm:ss"		no
<b>cac:OrderLine/cac:LineItem/cac:Delivery/cbc:RequestedDeliveryPeriod/cbc:End</b>	2/25/2010	Period end date The date on which the period ends. The end date counts as part of the period. Format = "YYYY-MM-DD"		N/A yes
<b>cac:OrderLine/cac:LineItem/cac:Delivery/cbc:RequestedDeliveryPeriod/cbc:End</b>	18:00:00	Period end time The time at which this period ends. Format = "hh:mm:ss"		no
<b>cac:OrderLine/cac:LineItem/cac:OriginatorParty/cac:PartyIdentification/cbc:ID @schemeID</b>	schemeID="0082" 123456789	Originator information Information regarding the originator of the order line Party name Name of the originator		no
<b>cac:OrderLine/cac:LineItem/cac:OriginatorParty/cac:PartyName/cbc:Name</b>	Josef K.	Originator information Information regarding the originator of the order line Party name Name of the originator		no
<b>cac:OrderLine/cac:LineItem/cac:AllowanceCharge/cbc:ChargeIndicator</b>	Example 1: true Example 2: false	Order line allowance and charges A group of business terms providing information about allowances or charges applicable to the individual order line. Use "true" when informing about Charges and "false" when informing about Allowances		no

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals)	Field in use
		Line level allowance or charge reason code The reason for the line level allowance or charge expressed as a code. For allowances a subset of codes UNCL15189 is to be used, and for charges codes UNCL1761 applies. The Document level allowance reason code and the Document level allowance reason shall indicate the same allowance reason		
	Example 1: ABK	Allowance reason codes <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL15189/">https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL15189/</a>		
<code>ca:OrderLine/cac:LineItem/cac:AllowanceCharge/cbc:AllowanceChargeReasonCode</code>	Example 2: 95	Charge reason code <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL1761/">https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL1761/</a>		no
		Line level allowance or charge reason The reason for the line level allowance or charge expressed as text. The Document level allowance reason code and the Document level allowance reason shall indicate the same allowance reason		
	Example 1: Miscellaneous services	Allowance reason codes <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL15189/">https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL15189/</a>		
<code>ca:OrderLine/cac:LineItem/cac:AllowanceCharge/cbc:AllowanceChargeReason</code>	Example 2: Discount	Charge reason code <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL1761/">https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL1761/</a>		no
		Line level allowance or charge percentage The percentage that may be used, in conjunction with the line level allowance base amount, to calculate the line level allowance or charge amount.		
<code>ca:OrderLine/cac:LineItem/cac:AllowanceCharge/cbc:FactorNumeric</code>	Example 2: 5	Line level allowance or charge amount The amount of an allowance or a charge, without TAX. Must be rounded to maximum 2 decimals		no
		currencyID="NOK" Currency identifier, value must be the same as what is used in ir01-007, DocumentCurrencyCode.		
	Example 1: 600.00	Currency codes: <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/ISO4217/">https://docs.peppol.eu/peppol/ugrade-3/codelist/ISO4217/</a>		
<code>ca:OrderLine/cac:LineItem/cac:AllowanceCharge/cbc:Amount @currencyID</code>	Example 2: 300.00	Line level allowance or charge base amount The base amount that may be used, in conjunction with the line level allowance or charge percentage, to calculate the line level allowance or charge amount. Must be rounded to maximum 2 decimals		no
		currencyID="NOK" Currency identifier, value must be the same as what is used in ir01-007, DocumentCurrencyCode.		
<code>ca:OrderLine/cac:LineItem/cac:AllowanceCharge/cbc:BaseAmount @currencyID</code>	Example 2: 6000.00	Currency codes: <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/ISO4217/">https://docs.peppol.eu/peppol/ugrade-3/codelist/ISO4217/</a>		no
		The net price of the item including all allowances, charges and taxes but excluding TAX. Although price is an optional element in an order it is recommended as best practice to either state the price or provide reference to an appropriate source from which the price can be identified such as a contract, catalogue or a quote.		
<code>ca:OrderLine/cac:LineItem/cac:Price/cbc:PriceAmount @currencyID</code>	currencyID="NOK" 50.000	Currency codes: <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/ISO4217/">https://docs.peppol.eu/peppol/ugrade-3/codelist/ISO4217/</a>		6 yes
		Item price base quantity The actual quantity to which the price applies.		
<code>ca:OrderLine/cac:LineItem/cac:Price/cbc:BaseQuantity @unitCode</code>	Unit codes: <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL38c20/">https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL38c20/</a>			3 no
		Price discount information Information on discounts connected to the price		
<code>ca:OrderLine/cac:LineItem/cac:AllowanceCharge/cbc:ChargeIndicator</code>	FALSE	AllowanceChargeIndicator Only discounts are allowed for the price, hence the only valid value is false (meaning an allowance)		no
		Item description Free-form field that can be used to give a text description of the item. A detailed description of the item.		
<code>ca:OrderLine/cac:LineItem/cac:Item/cbc:Description</code>	Needle 4mm	Item name A short name for an item. A short name given to an item, such as a name from a Catalogue, as distinct from a description.		256 yes
<code>ca:OrderLine/cac:LineItem/cac:Item/cbc:Name</code>	Needle 4mm	Buyers item identifier An identifier, assigned by the buyer, for the item. Associates the item with its identification according to the buyer's system.		256 yes
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:BuyersItemIdentification/cbc:ID</code>	123456	The Sellers item identifier An identifier, assigned by the seller, for the item. Associates the item with its identification according to the seller's system.		128 yes
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:ManufacturersItemIdentification/cbc:ID</code>	man0659	Manufacturers item identifier An identifier, assigned by the items manufacturer, for the item.		128 yes
		Item standard identifier An item identifier based on a registered scheme. Associates the item with its identification according to a standard system.		no
		Scheme ID is: 0212 - Finnish Organization Identifier 0216 - OVCode 0160 - GTIN - Global Trade Item Number <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/ICD/">https://docs.peppol.eu/peppol/ugrade-3/codelist/ICD/</a> (same codes as in cell C26)		no
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:StandardItemIdentification/cbc:ID @schemeID</code>	schemeID="0160" 756000012345	Item specification reference Reference to an item specification document		no
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:ItemSpecificationDocumentReference/cbc:ID</code>	12345678	Item classification code A code for classifying the item by its type or nature. Classification codes are used to allow grouping of similar items for a various purposes: e.g. public procurement (CPV), e-Commerce (UNSPSC) etc.		
		Item classification identifier The identification scheme identifier of the item classification identifier		
		Item classification identifier version identification scheme identifier The identification scheme version identifier of the item classification identifier		
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:CommodityClassification/cbc:ItemClassificationCode @listID @listVersionID</code>	listID="MP" listVersionID="151951" 12345678	Item type identification code <a href="https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL1743/">https://docs.peppol.eu/peppol/ugrade-3/codelist/UNCL1743/</a>		no
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:ClassifiedTaxCategory/cbc:ID</code>	S	Line TAX information Item TAX category code The TAX category code for the item.		50 yes
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:ClassifiedTaxCategory/cbc:Percent</code>	25	Line TAX rate The TAX percentage rate that applies to the line amount.		2 yes
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:ClassifiedTaxCategory/cac:TaxScheme/cbc:ID</code>	VAT	Tax scheme. E.g. "VAT" or "GST" Additional item property information A group of business terms providing information about properties of the goods and services invoiced.		yes
		Item property name The name of the property. The name must be sufficiently descriptive to define the value. The definition may be supplemented with the property unit of measure when relevant.		
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:AdditionalItemProperty/cbc:Name</code>	Length	Item property code Code for the item property according to a property code system.		no
<code>ca:OrderLine/cac:LineItem/cac:Item/cac:AdditionalItemProperty/cbc:Value</code>	30 mm	Item property value The value of the item property.		no

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals) Field in use
----------------------------	---------------------	----------------------------	--

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals)	Field in use
----------------------------	---------------------	----------------------------	-------------------------------	--------------

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals)	Field in use
----------------------------	---------------------	----------------------------	-------------------------------	--------------



XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals) Field in use
----------------------------	---------------------	----------------------------	--

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals) Field in use
----------------------------	---------------------	----------------------------	--

XML element - PEPPOL Order	PEPPOL example data	PEPPOL element description	Max length (or # of decimals)	Field in use
----------------------------	---------------------	----------------------------	-------------------------------	--------------