

All units mm unless otherwise specified

All units mm unless otherwise specified																	
		Wheel			Spacer		Tire			Fitment				Alignment			
OEM	Diameter (in)	Width (in)	Width	Offset	Thickness	Width	Sidewall ratio	Overall height	Wheel > hub	Tire > hub	Wheel < hub	Tire < hub	Camber	Camber offset	Tire > hub	Tire < hub	
Front	18	8	203.2	42		225	45	248.22	59.6	70.5	143.6	154.5	-1	4.33	66.17	158.83	
Rear	18	9	228.6	30		255	40	249.72	84.3	97.5	144.3	157.5	-1.8	7.84	89.66	165.34	
		Wheel			Spacer		Tire			Fitment				Alignment			
E38 M-Parallel	Diameter (in)	Width (in)	Width	Offset	Thickness	Width	Sidewall ratio	Overall height	Wheel > hub	Tire > hub	Wheel < hub	Tire < hub	Camber	Camber offset	Tire > hub	Tire < hub	
Front	18	8.5	215.9	13		245	40	241.72	94.95	109.5	120.95	135.5	-3	12.65	96.85	148.15	
Rear	18	9.5	241.3	25		275	35	238.22	95.65	112.5	145.65	162.5	-3	12.47	100.03	174.97	
Front Difference		0.5	12.7	-29		20	-5	-6.5	35.35	39	-22.65	-19	-2	8.32	30.68	-10.68	
Rear Difference		0.5	12.7	-5		20	-5	-11.5	11.35	15	1.35	5	-1.2	4.62	10.38	9.62	
		Wheel			Spacer		Tire			Fitment				Alignment			
Apex ARC-8 stagger	Diameter (in)	Width (in)	Width	Offset	Thickness	Width	Sidewall ratio	Overall height	Wheel > hub	Tire > hub	Wheel < hub	Tire < hub	Camber	Camber offset	Tire > hub	Tire < hub	
Front	18	8.5	215.9	38		245	40	241.72	69.95	84.5	145.95	160.5	-2	8.44	76.06	168.94	
Rear	18	9.5	241.3	22		275	35	238.22	98.65	115.5	142.65	159.5	-2.5	10.39	105.11	169.89	
Front Difference		0.5	12.7	-4		20	-5	-6.5	10.35	14	2.35	6	-1	4.10	9.90	10.10	
Rear Difference		0.5	12.7	-8		20	-5	-11.5	14.35	18	-1.65	2	-0.7	2.55	15.45	4.55	
		Wheel			Spacer		Tire			Fitment				Alignment			
Apex ARC-8 square	Diameter (in)	Width (in)	Width	Offset	Thickness	Width	Sidewall ratio	Overall height	Wheel > hub	Tire > hub	Wheel < hub	Tire < hub	Camber	Camber offset	Tire > hub	Tire < hub	
Front	18	9.5	241.3	35		265	35	231.22	85.65	97.5	155.65	167.5	-2.5	10.09	87.41	177.59	
Rear	18	9.5	241.3	35	12	265	35	231.22	97.65	109.5	143.65	155.5	-2	8.07	101.43	163.57	
Front Difference		1.5	38.1	-7		40	-10	-17	26.05	27	12.05	13	-1.5	5.75	21.25	18.75	
Rear Difference		0.5	12.7	5		10	-5	-18.5	13.35	12	-0.65	-2	-0.2	0.23	11.77	-1.77	
		Wheel			Spacer		Tire			Fitment				Alignment			
LTW5 / CL	Diameter (in)	Width (in)	Width	Offset	Thickness	Width	Sidewall ratio	Overall height	Wheel > hub	Tire > hub	Wheel < hub	Tire < hub	Camber	Camber offset	Tire > hub	Tire < hub	
Front	18	9.5	241.3	35		275	35	238.22	85.65	102.5	155.65	172.5	-2	8.31	94.19	180.81	
Rear	18	10	254	43	20	285	35	245.22	104	119.5	150	165.5	-2.5	10.70	108.80	176.20	
Front Difference		1.5	38.1	-7		50	-10	-10	26.05	32	12.05	18	-1	3.98	28.02	21.98	
Rear Difference		1	25.4	13		30	-5	-4.5	19.7	22	5.7	8	-0.7	2.85	19.15	10.85	
		Wheel			Spacer		Tire			Fitment				Alignment			
LTW5 / MPSS	Diameter (in)	Width (in)	Width	Offset	Thickness	Width	Sidewall ratio	Overall height	Wheel > hub	Tire > hub	Wheel < hub	Tire < hub	Camber	Camber offset	Tire > hub	Tire < hub	
Front	18	9.5	241.3	35		265	35	231.22	85.65	97.5	155.65	167.5	-1	4.04	93.46	171.54	
Rear	18	10	254	43	20	285	35	245.22	104	119.5	150	165.5	-1.8	7.70	111.80	173.20	
Front Difference		1.5	38.1	-7		40	-10	-17	26.05	27	12.05	13	-0.30	27.30	12.70		
Rear Difference		1	25.4	13		30	-5	-4.5	19.7	22	5.7	8	-0.14	22.14	7.86		