

Hushida A3 Digital Signage Parameters Sheet

	Model	LY-32	LY-43	LY-49	LY-55	LY-65	LY-75	LY-86	LS-32	LS-43	LS-49	LS-55	LS-65	LS-75	LS-86	LS-98
	Size	32"	43"	49"	55"	65"	75"	86"	32"	43"	49"	55"	65"	75"	86"	98"
	Panel Type	LED(A Grade)														
	Backlight Type	E-LED							D-LED							
	Display Area	698.4*392.9mm	941*529mm	1073.7*604mm	1213*684mm	1431*806mm	1650.2*928.3mm	1914*1069mm	698.4*392.9mm	941*529mm	941*529mm	1232.5*703mm	1451*826.5mm	1650*928mm	1914*1069mm	2206.9*1243.6mm
	Resolution	1920×1080 2K FHD & 2K UHD														3840*2160 4K FHD & 4K UHD
	Brightness	2000nit Automatic photosensitive														3000nit Automatic photosensitive
	Visible Angle	178° Horizontal / 178° Vertical														
	Life Time	>50000H														
	Chips	RK3288 Cortex-A17 Four Core														RK3188 2-CORE
	Running Memory	2G DDR4														
	GPU	Mali-T764														Android 5.1
	System	Android 7.1														
	ROM	8GB														
	Interface	Power、WIFI、AUDIO、LAN、USB*2、TF、DC、HDMI														
	Video Format	MPEG1、MPEG2、MPEG4、H.264、WMV、MKV、TS、flv														
	Audio Format	MP3														
	Image Format	JPG、JPEG、BMP、PNG、GIF														
	Text Format	txt														
	Device Size (L*W*T)	898.4*592.9*180mm	1140*730*180mm	1275*805*180mm	1411.3*884*170mm	1630*1007.1*180mm	1840*1140*240mm	2098*1279*240mm	1600*580*180mm	1900*742*190mm	1900*742*190mm	1950*880*190mm	2100*1012.5*190mm	1800*1140*240mm	2119*1299*280mm	2466.9*1503.6*300mm
	Intelligent direct ventilation cooling	Intelligent cooling system, uniquely designed air duct and motherboard, automatically adjust the air speed and air volume														
	Temperature sensing	Intelligent temperature sensing system, the display is automatically turned off when the temperature is 65°C														
	Self heating	-5°C self-starting heating/optional														
	Enclosure Material	Aluminum Alloy/Sheet Metal														
	Waterproof Audio	10W														
	leakage protector	Yes														
	Timer	Customized switch can be set by day, week and month														
	Power	Industrial grade power supply														
	Power System	Two-phase three-wire system														
	Power Consumption	180W	300W	480W	480W	480W	800W	1000W	200W	480W	480W	480W	800W	680W	--	2000W
	Working Temperature	-30°C~+50°C														
	Working Humidity	5%~95%														
	Attachments	User manual, warranty card, certificate of conformity, WIFI, set of Wall bracket+screws(If nessecery)														
	Certification	CCC, CECF, CE, ROHS, FCC														

Copy rights 2022 · Guang Dong Hushida Electronic Technology Co.,Ltd | All rights reserved